



**SHERWIN
WILLIAMS.**

EXTERIOR ALKYD SEMI-TRANSPARENT WOOD PRESERVATIVE STAIN A14T5

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>						
<p>Exterior Alkyd Semi-Transparent Wood Preservative Stain provides a long lasting, mildew resistant film with excellent penetration for protecting most exterior, above ground, wood surfaces.</p> <p>Color: All semi-transparent colors</p> <p>Coverage: Rough/porous: 100-200 sq ft/gal Smooth: 350 sq ft/gal</p> <p>Drying Time, @ 77°F, 50% RH: temperature and humidity dependent Touch: 3 hours Recoat: 24 hours</p> <p>Flash Point: 103°F, PMCC</p> <p>Finish: 0-5 units @ 85°</p> <p>Tinting with Blend-A-Color:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 15%;">Base</td> <td style="width: 15%;">oz/gal</td> <td style="width: 15%;">Strength</td> </tr> <tr> <td>Clear Base</td> <td>2-4</td> <td>100%</td> </tr> </table> <p>Vehicle Type: Alkyd</p> <p style="text-align: center;">A14T5</p> <p>VOC (less exempt solvents): 672 g/L; 5.61 lb/gal</p> <p>Volume Solids: 12 ± 2%</p> <p>Weight Solids: 18 ± 2%</p> <p>Weight per Gallon: 6.8 lb</p> <p>Not OTC Compliant</p> <p>Provides performance which is comparable to the products that are formulated in accordance with federal specification: TT-S-708A</p>	Base	oz/gal	Strength	Clear Base	2-4	100%	<p>Wood, Plywood</p> <p>1 ct. Exterior Alkyd Semi-Transparent Wood Preservative Stain</p> <p>optional</p> <p>2 cts. Exterior Alkyd Semi-Transparent Wood Preservative Stain</p> <p style="text-align: center;"><u>APPLICATION</u></p> <p>Apply at temperatures above 50°F. No reduction necessary.</p> <p>Brush Use a natural bristle brush.</p> <p>Roller Use a 3/8" - 3/4" nap synthetic or lamb-swool roller cover.</p> <p>Spray—Airless Pressure 2000 psi Tip015"-.017"</p> <p>Important: All stains tend to lap (dark lines where two freshly coated areas overlap). To minimize lapping:</p> <ul style="list-style-type: none"> • Do not stain in direct sun or on a hot surface. • Always stain into a wet edge. • Stain up and down vertical siding and across horizontal siding. • Use two coats on badly weathered or unfinished wood. • Apply a second coat when lap marks appear on the first coat. 	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all existing paint and replace any deteriorated substrate. Although this can be applied over earlier semi-transparent stains, some of the old color may be visible through this semi-transparent film.</p> <p>Remove all surface contamination by washing with ProClean Professional® Prep Wash Concentrated Cleaner or other appropriate cleaner to remove all dirt, air pollution, chalk, etc., especially in areas not exposed to direct weathering such as under eaves and porch ceilings. Rinse and allow the surface to dry. If after cleaning, the surface still appears dirty, suspect mildew.</p> <p>Remove before painting by washing with ProClean Professional Mildew Eliminator or a solution of 1 pint liquid bleach and 1 gallon water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p>
Base	oz/gal	Strength						
Clear Base	2-4	100%						

105.20

EXTERIOR ALKYD SEMI-TRANSPARENT WOOD PRESERVATIVE STAIN A14T5



**SHERWIN
WILLIAMS.**

SURFACE PREPARATION

Apply appropriate Sherwin-Williams patching material to cracks, nail holes, or other surface imperfections. Filled areas will take the stain differently than bare wood.

Caulk around windows, doors, and other openings with Sherwin-Williams exterior caulk after spot priming any bare surfaces in these areas. Do not get caulk or primer on areas to receive stain, the stain will appear different over primer and caulk

Smooth or Rough Wood Siding and Plywood. Sand any exposed, deteriorated wood to a fresh surface.

Mill Glaze is a glossy finish on new, smooth sawn wood or on the peaks of some textured wood. This must be removed by sanding to allow the stain to penetrate.

Pressure Treated Wood

Test the absorbency of the wood by sprinkling water on the surface. If the water penetrates into the wood quickly, the wood is ready to finish. If the water beads up or does not penetrate, allow the wood to weather 1 to 2 weeks and test for absorbency again. Prepare the surface like any other wood surface.

Due to the green tone of many brands of pressure treated lumber, the color of the stain may look different from the color selected. Check the color on a test area prior to staining the entire project.

CLEANUP INFORMATION

Clean spills and spatters immediately with mineral spirits. Clean tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABEL.

For exterior use only.
Do not use on composition board.
Do not use on roofs.
Must be tinted before using.
Use DeckScapes Waterborne Semi-Transparent Deck Stain for exterior wood deck floors.

LABEL CAUTIONS

CAUTION contains ALIPHATIC HYDROCARBONS. Contents are COMBUSTIBLE. Keep away from heat and open flame. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 12/6/2004 A14T00005 18 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.