



**SHERWIN
WILLIAMS.**

Uses:

- Trim Packs/Molding
- Doors/Windows
- Paneling
- Railing/Furniture

Features:

- Sands easily in 1 hour
- Seals wood grain
- High Build
- Finish coat in 1½ hours

WOOD CLASSICS®

**FASTDRY SANDING SEALER
B26V43**

<u>CHARACTERISTICS</u>	<u>SPECIFICATION</u>	<u>SURFACE PREPARATION</u>												
<p>The Wood Classics System is designed for use on architectural wood in commercial, institutional, and residential new construction and also for refinishing.</p> <p>Wood Classics FastDry Sanding Sealer provides a high build surface and sands fast, easy, and effectively in 1 hour, giving an extremely smooth surface for topcoating. The Sanding Sealer provides an alternative to the first coat of varnish in a 2 coat system.</p> <p>Wood Classics FastDry Sanding Sealer can be topcoated in 1½ hours with most clear alkyd topcoats.</p> <p>Color: Clear Amber</p> <p>Coverage: 350 - 500 sq ft/gal 3.5 - 4.5 mils wet; 1.0 - 1.2 mils dry</p> <p>Drying Time, @ 77°F, 50% RH: temperature and humidity dependent To touch: 20 minutes To sand: 1 hours To topcoat: 1-1/2 hours</p> <p>Finish: 45-65 units @ 60°</p> <p>Flash Point: 52°F, PMCC</p> <p>Shading with Wood Classics Stain:</p> <table border="0"> <tr> <td>Base</td> <td>oz/gal</td> <td>Strength</td> </tr> <tr> <td>Clear</td> <td>0-2</td> <td>N/A</td> </tr> </table> <p>Tinting with Blend-A-Color Toner:</p> <table border="0"> <tr> <td>Base</td> <td>oz/gal</td> <td>Strength</td> </tr> <tr> <td>Clear</td> <td>0-1</td> <td>N/A</td> </tr> </table> <p>Vehicle Type: Linseed Vinyl Toluene Alkyd B26V43</p> <p>VOC (less exempt solvents): 522 g/L; 4.36 lb/gal</p> <p>Volume Solids: 31 ± 2%</p> <p>Weight Solids: 38 ± 2%</p> <p>Weight per Gallon: 7.0 lb</p> <p>OTC Compliant in quarts</p>	Base	oz/gal	Strength	Clear	0-2	N/A	Base	oz/gal	Strength	Clear	0-1	N/A	<p>Suggested system: Smoothness and Speed</p> <p>1st: Wood Classics Stain (optional) 2nd: Wood Classics <i>FastDry</i> Sanding Sealer 3rd: Wood Classics <i>FastDry</i> Oil Varnish</p> <p>Shading finishes Up to 1 oz. of Wood Classics Stain or 1 oz of Blend-A-Color Toner (or similar universal colorant) can be added to Wood Classics to shade the topcoats.</p> <p>White or light colors When used over a white or very light stain color, alkyd coatings, such as this product, will impart a slight yellow cast to the final appearance.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Wood must be dry and cleaned of dirt, grease, wax, polish, and marks. Old finishes in poor condition should be completely removed and the surface treated as a new surface.</p> <p>Sand wood to a smooth surface using 100-120 grit paper. Remove sanding dust with a vacuum or tack cloth.</p> <p>Avoid sanding wood that has only stain on it, sanding will remove some of the stain creating an uneven appearance.</p> <p>New wood should be stored inside for a minimum of 24 hours prior to staining. Stain or varnish applied to wood that has not been dried thoroughly can exhibit blotching, discoloration, or cracking.</p>
Base	oz/gal	Strength												
Clear	0-2	N/A												
Base	oz/gal	Strength												
Clear	0-1	N/A												

106.06

WOOD CLASSICS[®]

FAST DRY SANDING SEALER

B26V43



**SHERWIN
WILLIAMS.**

APPLICATION

Be sure the temperature is above 50°F and the humidity is below 85%.

Do not shake. Stir thoroughly and occasionally during use.

No reduction necessary.

Brush—Use a natural bristle brush. Brush out evenly, avoid unnecessary brushing into already coated areas. Avoid over-brushing which causes bubbling.

Spray—Airless

Pressure 2000 psi
Tip008" - .013"

Spray—Conventional

Air Pressure 50 psi
Fluid Pressure 10-20 psi
Cap/Tip 704/FF

HVLP

Unit Graco 3800 or 4900
Gun 960
Tip 1.4 -1.6 mm

Allow to dry 1 hour then sand with 180 or finer grit sandpaper. Although not as effective as sandpaper, steel wool and synthetic abrasive pads may be used for very light sanding.

Remove all sanding dust with a tack cloth or vacuum.

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

For interior use only.
Do not use on floors.
Do not use under Polyurethane Varnish or lacquers.

LABEL CAUTIONS

CAUTION contains ALIPHATIC HYDROCARBONS. Contents are FLAMMABLE. Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN
HOTW 10/19/2004 B26V00043 04 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.