



**SHERWIN  
WILLIAMS.**

As of 10/14/08, Complies with:		
OTC	Yes	LEED® Clv2.0 Yes
SCAQMD	No	LEED® NCv2.2Yes
CARB	Yes	LEED® CSv2.0Yes
MPI Spec # (none)		LEED® H Yes
NAHB	Yes	

# BUILDERS SOLUTION™ SYSTEM

## INTERIOR LATEX EG-SHEL

### A62 SERIES

#### CHARACTERISTICS

**Builders Solution™ Interior Latex Eg-Shel Topcoat** is a high quality product designed for the professional. This product is recommended for interior application on walls and ceilings of primed plaster, wallboard, wood, masonry, and primed metal.

The **Builders Solution System** is a two-coat system that delivers a superior final appearance for the Builder and an upgraded, washable wall finish to the new homeowner.

The **Builders Solution System** delivers superior results when compared to entry-level Builders products.

- Superior washability
- Superior final appearance
- High Build Surfacer that hides minor surface defects
- Minimizes callbacks
- Improved touch-up

#### SPECIFICATIONS

**Color:** Most colors  
**Coverage:** 350 - 400 sq ft/gal  
@ 4.0 mils wet; 1.7 mils dry

**Drying Time, @ 77°F, 50% RH:**  
temperature and humidity dependent

Touch: 1 hour

Recoat: 4 hours

**Finish:** 10-20 units @ 85°

**Flash Point:** N/A

**Tinting with Blend-A-Color:**

**Base oz/gal Strength**

Extra White 0-5 100%

Deep Base 4-12 100%

**Vehicle Type:** Vinyl Acrylic

**A62W00051**

**VOC (less exempt solvents):**  
99 g/L; 0.82 lb/gal

**Volume Solids:** 41 ± 2%

**Weight Solids:** 54 ± 2%

**Weight per Gallon:** 10.9 lb

#### **Drywall**

1 ct. Builders Solution Primer/  
Surfacer

1 or 2 cts. Builders Solution Latex Eg-Shel

#### **Masonry**

1 ct. Builders Solution Primer/  
Surfacer

or Loxon Concrete & Masonry  
Primer

1 or 2 cts. Builders Solution Latex Eg-Shel

#### **Metal**

1 ct. Pro Industrial Pro-Cryl Primer

1 or 2 cts. Builders Solution Latex Eg-Shel

#### **Plaster**

1 ct. Builders Solution Primer/  
Surfacer

1 or 2 cts. Builders Solution Latex Eg-Shel

#### **Wood**

1 ct. Premium Wall & Wood Primer

1 or 2 cts. Builders Solution Latex Eg-Shel

#### SURFACE PREPARATION

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer.

#### **Drywall**

Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

#### **Masonry, Concrete, Cement, Block**

All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with PrLoxon Concrete & Masonry Primer.

101.64



**SHERWIN  
WILLIAMS.**

# BUILDERS SOLUTION™ SYSTEM

## INTERIOR LATEX EG-SHEL

### A62 SERIES

#### SURFACE PREPARATION

##### **Plaster**

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

##### **Wood**

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.

##### **Mildew**

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

##### **Caulking**

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

#### APPLICATION

The **Builders Solution System** is designed to deliver the best performance when applied by airless spray.

Apply at temperatures above 50°F. No reduction needed.

##### **Spray—Airless**

Pressure ..... 2000 psi

Tip ..... .017"-.021"

##### **Brush**

Use a nylon/polyester brush.

##### **Roller**

Use a 3/8" - 3/4" nap synthetic cover.

#### CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

#### CAUTIONS

For interior use only  
Non-photochemically reactive.

##### LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 09/18/2008 A62W00051 15 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.