SuperDeck[®] Revive[™] Deck & Siding Brightener

640359931 (US), 100266402 (Canada)

CHARACTERISTICS

SuperDeck[®] Revive[™] Deck & Siding Brightener is a fastacting, ready-to-use cleaner specially formulated for cedar, redwood and other highly resinous exterior woods as well as

dense woods such as mahogany. Due to the chemical characteristics of these types of woods, traditional cleaners can leave the surface with an unnatural, darkened appearance. **SuperDeck Revive** will help remove unsightly stains caused by mildew and algae, dirt, gray and weathered wood, tannin bleed and nail bleed as well as stubborn mill glaze (a surface barrier to wood coatings found on most newly installed cedar and redwood) and restore the surface to its bright, clean natural look.

Where to use:

SuperDeck Revive can be used on any new or existing exterior structure including wood decks, fences, siding, shakes, shingles, boat docks, boardwalks, outdoor furniture, picnic tables, hot tubs, planters, benches, trellises and gazebos.

Coverage:	150-250 sq. ft. per gallon
Depending upon the wood.	condition and porosity of the
Appearance:	Water white, turbid
pH:	1
Solvent:	Water
Size:	1 gallon

640359931

V.O.C. (less exempt solvents):

<50 grams per litre; 0.42 lbs. per gallon As per 40 CFR 59.406

Volume Solids:	4.3 ± 2%
Weight Solids:	6.4 ± 2%
Weight per Gallon:	8.50 lbs
Flash Point:	N.A.
Туре:	Oxalic acid

COMPLIANCE

COMPLIANCE		
As of 05/20/2020, Complies with:		
OTC	Yes	
OTC Phase II	Yes	
SCAQMD	Yes	
CARB	Yes	
CARB SCM 2007	Yes	
Canada	Yes	
LEED [®] v4 & v4.1 Emissions	No	
LEED [®] v4 & v4.1 VOC	Yes	
EPD-NSF [®] Certified	No	
MIR-Manufacturer Inventory	No	
MPI [®]	No	

APPLICATION

Use in a well ventilated area and only as directed. On a horizontal surface, apply the mixture with a pump sprayer, brush or mop; on a vertical surface (siding or fencing) apply with a pump-up sprayer or deep nap roller working from the bottom to the top of the structure. Coat only 5-10 boards (20 sq. ft.) at a time to maintain adequate surface wetness and allow concentration of cleaning efforts to an area. Immediately and thoroughly rinse any overspray or accidental spills with water. Allow SuperDeck Revive to set on the surface for 10-15 minutes. For best results, lightly scrub surface with a stiff, synthetic bristle brush. Do not allow SuperDeck Revive to completely dry during application.

Thoroughly rinse the surface with fresh water from a hose, removing all residue. Any residue left on the surface may interfere with the drying or adhesion of topcoats.

Rinse surrounding area and vegetation with water. Stubborn stains or missed areas may need to be scrubbed with additional solution and rinse again. Allow approximately 2 days, depending on weather conditions, to allow the wood to thoroughly dry before applying a protective finish.



APPLICATION TIPS

Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.

Thoroughly read and understand all the label cautions prior to using any cleaner.

Be sure that the cleaner is appropriate for the dirt-contamination.

Do not mix together any cleaning compounds containing bleach and ammonia.

Abrasive cleansers may damage a paint film, use very carefully.

Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions would be advised.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (**NIOSH** approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Be sure the surface is free of any loose dirt and debris. Thoroughly wet plants and shrubs and cover to protect them for overspray. Uncover promptly after cleaning. Remove all deck furniture and decorative items. Do not allow SuperDeck Revive to come into contact with finished or aluminum surfaces. Rinse immediately after use on metal to avoid pitting or discoloration. If surface is extremely dry or in direct, hot sunlight, dampen with water. Wear rubber gloves and eye protection. Do not allow SuperDeck Revive to come into prolonged contact with clothing, carpet, or fabric, as damage may occur. Plan the application: for vertical surfaces, work from the bottom to the top. For horizontal surfaces, work backwards so that you do not walk on the surface being treated. Treat small areas one at a time. Exercise caution when working on wet surfaces as they may be slippery. Avoid spraying on windy days.

Using the right cleaner often makes the cleaning easier. Prior to using **SuperDeck Revive**, some general cleaning may be needed. Clean all surfaces completely with the appropriate cleaner based on the conditions. Rinse the surface completely and allow the surface to dry thoroughly.

SuperDeck® Deck Wash

- Mildew stain, Algae stain
- Weathered wood (bleaches wood)
- Gray wood (bleaches wood)

SuperDeck[®] Revive[™]

- Tannin Bleed, Nail stain
- Weathered wood (restores color)
- Gray wood (restores color), Mill Glaze

SuperDeck® Stain & Sealer Remover

- Weathered, gray wood
- Old Paint & Stain

SURFACE PREPARATION

Carefully follow all label instructions. Thoroughly rinse the surface to remove all residue and allow to thoroughly dry before coating.

- Read all the package directions before using. It is always recommended to test any cleaner on a small, inconspicuous area prior to use.
- Do not apply over sealed surfaces.
- To determine if the surface is sealed, test the absorbency by sprinkling water on it. If the water penetrates quickly, the surface is ready to finish. If the water beads up or does not penetrate, remove the coating-sealer and allow to dry. Test for absorbency again.
- Failure to follow application and surface preparation guidelines may result in premature coating failure.

Mildew: Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

CAUTIONS

This product must be applied outdoors to wood intended for exterior use only.

Not for interior use.

Before using, carefully read CAUTIONS on label

DANGER! CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, do not induce vomiting. Call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 05/20/2020 640359931 03 03 FRC,SP

CLEANUP INFORMATION

Rinse equipment and brushes with soap and water immediately after use.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.