



DURATION HOME[®]

INTERIOR LATEX SATIN

A97-1200 SERIES

the ultimate performance coating

As of 09/22/08, Complies with:			
OTC	Yes	LEED [®] Clv2.0	Yes
SCAQMD	Yes	LEED [®] NCv2.2	Yes
CARB	Yes	LEED [®] CSv2.0	Yes
MPI Spec #	44	LEED [®] H	Yes
NAHB	Yes		

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>																								
<p>Duration Home Interior Latex Satin provides:</p> <ul style="list-style-type: none"> • Long lasting beauty • Washability • Resistant to: <ul style="list-style-type: none"> - stains, scuffs, & burnishing • Very low VOC • Very low odor • Very easy application • Anti-Microbial* <p>Color: Most colors To optimize hide and color development, always use the recommended P-Shade primer</p> <p>Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 1.6 mils dry</p> <p>Drying Time, @ 77°F, 50% RH: temperature and humidity dependent Touch: 1 hour Recoat: 4 hours Flash Point: N/A Finish: 15 - 20 units @ 85° Tinting with Blend-A-Color:</p> <table border="1"> <thead> <tr> <th>Base</th> <th>oz/gal</th> <th>Strength</th> </tr> </thead> <tbody> <tr> <td>Extra White</td> <td>0-6</td> <td>Special</td> </tr> <tr> <td>Luminous White</td> <td>0-4</td> <td>100%</td> </tr> <tr> <td>High Reflective</td> <td>0-5</td> <td>100%</td> </tr> <tr> <td>Deep Base</td> <td>4-12</td> <td>100%</td> </tr> <tr> <td>Ultradeep</td> <td>4-12</td> <td>100%</td> </tr> <tr> <td>Real Red</td> <td>4-12</td> <td>100%</td> </tr> <tr> <td>Bright Yellow</td> <td>4-12</td> <td>100%</td> </tr> </tbody> </table> <p>Vehicle Type: Styrene Acrylic A97W1251</p> <p>VOC (less exempt solvents): 41 g/L; 0.34 lb/gal</p> <p>Volume Solids: 40 ± 2% Weight Solids: 51 ± 2% Weight per Gallon: 10.5 lb</p> <p>* Anti-microbial - This product contains agents which inhibit the growth of microbes on the surface of this paint film.</p>	Base	oz/gal	Strength	Extra White	0-6	Special	Luminous White	0-4	100%	High Reflective	0-5	100%	Deep Base	4-12	100%	Ultradeep	4-12	100%	Real Red	4-12	100%	Bright Yellow	4-12	100%	<p>Block 1 ct. Loxon Block Surfer 2 cts. Duration Home Interior Latex Satin</p> <p>Drywall 1 ct. PrepRite Classic Latex Primer 2 cts. Duration Home Interior Latex Satin</p> <p>Plaster 1 ct. PrepRite Classic Latex Primer 2 cts. Duration Home Interior Latex Satin</p> <p>Masonry 1 ct. PrepRite Masonry Primer 2 cts. Duration Home Interior Latex Satin</p> <p>Wood, Composition Board 1 ct. PrepRite Classic Latex Primer 2 cts. Duration Home Interior Latex Satin</p> <div style="border: 2px solid black; padding: 5px; margin-top: 10px;"> <p>For better hiding of vivid, brilliant, and deep accent colors, use the recommended Color-Prime System "P"-shade.</p> </div>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with PrepRite[®] ProBlock[®] Primer Sealer.</p> <p>Drywall Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with PrepRite Masonry Primer.</p>
Base	oz/gal	Strength																								
Extra White	0-6	Special																								
Luminous White	0-4	100%																								
High Reflective	0-5	100%																								
Deep Base	4-12	100%																								
Ultradeep	4-12	100%																								
Real Red	4-12	100%																								
Bright Yellow	4-12	100%																								

101.68

DURATION HOME[®]

INTERIOR LATEX SATIN

A97-1200 SERIES



<u>SURFACE PREPARATION</u>	<u>APPLICATION</u>	<u>CAUTIONS</u>
<p>Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p>Caulking Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.</p>	<p>Apply at temperatures above 50°F. No reduction needed.</p> <p>Brush Use a nylon/polyester brush.</p> <p>Roller For the best final appearance when rolling: For the High Reflective White, Luminous, Extra, and Deep bases, use a 3/8" - 1/2" nap Soft Woven roller cover. For the Ultradeep, Real Red, and Bright Yellow bases, use a 3/8" - 1/2" nap SherFab roller cover.</p> <p>Spray—Airless Pressure 2000 psi Tip015"-.019" For touching-up, reduce the product by one pint per gallon.</p> <p><u>CLEANUP INFORMATION</u></p> <p>Clean spills and spatters immediately with soap and warm water. Clean hands and tools immediately after use with soap and warm water. Flush spray equipment after cleaning with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.</p>	<p>For interior use only. Protect from freezing. Non-photochemically reactive.</p> <p>CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>HOTW 01/13/2009 A97W01251 03 00</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>