



# SHERSTRIPE™

## ATHLETIC FIELD MARKING PAINT B2-900 SERIES AND AEROSOLS

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>																																								
<p><b>SherStripe™ Athletic Field Marking Paint</b> is a complete line of fast-drying, latex emulsion formulas designed specifically for lining and marking natural surfaces; such as grass, cinder and dirt playing fields.</p> <p>Use <b>SherStripe™ Athletic Field Marking Paint</b> on baseball, soccer, football, field hockey and any other natural field or surface where striping, marking or coloring is desired.</p> <p><b>SherStripe™ Athletic Field Marking Paint</b> is a safe alternative to lime. The product will not harm eyes or grass. Lines will not blur with rough usage.</p> <p><b>Coverage:</b> 350 - 400 sq ft/gal @ 4 mils wet; 1.2 mils dry</p> <p><b>Drying Time, @ 50% RH:</b> temperature and humidity dependent @ 77°F</p> <p>Touch: 30 minutes Recoat: 1 hour <b>Flash Point:</b> N/A <b>Finish:</b> Flat</p> <p><b>Tinting with Blend-A-Color:</b></p> <table border="0"> <tr> <td><b>Base</b></td> <td><b>oz/gal</b></td> <td><b>Strength</b></td> </tr> <tr> <td>Ultradeep Base</td> <td>4-12</td> <td>100%</td> </tr> </table> <p><b>Vehicle Type:</b> Vinyl Polymer <b>B02W00900, Bright White</b></p> <p><b>VOC (less exempt solvents):</b> 85 g/L; 0.71 lb/gal</p> <p><b>Volume Solids:</b> 31 ± 2% <b>Weight Solids:</b> 52 ± 2% <b>Weight per Gallon:</b> 12.0 lb</p>	<b>Base</b>	<b>oz/gal</b>	<b>Strength</b>	Ultradeep Base	4-12	100%	<p><b>Natural Turf Athletic Fields</b> 1-2 cts. SherStripe Athletic Field Marking Paint</p> <p><b>Recommended Coverage:</b> Coverage depends on method of application, type of field, and width of lines desired. When applied according to recommended line marking machine methods, a gallon of properly thinned paint will mark approximately 1,000 - 1,200 lineal foot 4" line at 1.6 mils wet.</p> <p>Actual spread rates may vary based on the following:</p> <ul style="list-style-type: none"> <li>• Surface profile</li> <li>• Poor surface conditions</li> <li>• Roughness and porosity of surface</li> <li>• Method of application</li> <li>• Amount of reduction</li> <li>• Environmental conditions</li> <li>• Amount of film build</li> </ul>	<p>When painting a field where the grass is abnormally dry, water the field and allow the water to be absorbed prior to applying any field marking paint. This will prevent the grass from absorbing water directly from the coating which, under some circumstances, can cause the lines to appear burnt in.</p> <p>The surface should be clean of debris. Cut grass to desired level and perform all preliminary preparations to the field surface before lines are marked.</p> <p>If surface is wet from rain, dew or watering, allow to dry thoroughly before application.</p> <p>Under good weather conditions and with ordinary wear, it is not necessary to remark the field after each use.</p>																																		
<b>Base</b>	<b>oz/gal</b>	<b>Strength</b>																																								
Ultradeep Base	4-12	100%																																								
	<p><b>Color (bulk package):</b></p> <table border="0"> <tr> <td>Bright White</td> <td>B02W00900</td> </tr> <tr> <td>White</td> <td>B02W00902</td> </tr> <tr> <td>Neutral</td> <td>B02T00954</td> </tr> <tr> <td>Yellow</td> <td>B02Y00956</td> </tr> <tr> <td>Red</td> <td>B02R00955</td> </tr> <tr> <td>Blue</td> <td>B02L00956</td> </tr> <tr> <td>Black</td> <td>B02B00957</td> </tr> </table> <p>(The package colors and the aerosols are different colors.)</p>	Bright White	B02W00900	White	B02W00902	Neutral	B02T00954	Yellow	B02Y00956	Red	B02R00955	Blue	B02L00956	Black	B02B00957	<p><b>Color (Aerosols):</b></p> <table border="0"> <tr> <td>Athletic White</td> <td>6500-77589</td> </tr> <tr> <td>Athletic Yellow</td> <td>6500-77613</td> </tr> <tr> <td>Athletic Orange</td> <td>6500-77621</td> </tr> <tr> <td>Athletic Scarlet</td> <td>6500-77647</td> </tr> <tr> <td>Athletic Royal Blue</td> <td>6500-77654</td> </tr> <tr> <td>Athletic Black</td> <td>6500-77662</td> </tr> <tr> <td>Athletic Maroon</td> <td>6500-77670</td> </tr> <tr> <td>Athletic Purple</td> <td>6500-77688</td> </tr> <tr> <td>Athletic Navy</td> <td>6500-77696</td> </tr> <tr> <td>Athletic Fluorescent Orange</td> <td>6500-77704</td> </tr> <tr> <td>Athletic Fluorescent Green</td> <td>6500-77712</td> </tr> <tr> <td>Athletic Old Gold</td> <td>6500-77720</td> </tr> <tr> <td>Athletic Turf Green</td> <td>6500-77738</td> </tr> </table>	Athletic White	6500-77589	Athletic Yellow	6500-77613	Athletic Orange	6500-77621	Athletic Scarlet	6500-77647	Athletic Royal Blue	6500-77654	Athletic Black	6500-77662	Athletic Maroon	6500-77670	Athletic Purple	6500-77688	Athletic Navy	6500-77696	Athletic Fluorescent Orange	6500-77704	Athletic Fluorescent Green	6500-77712	Athletic Old Gold	6500-77720	Athletic Turf Green	6500-77738
Bright White	B02W00900																																									
White	B02W00902																																									
Neutral	B02T00954																																									
Yellow	B02Y00956																																									
Red	B02R00955																																									
Blue	B02L00956																																									
Black	B02B00957																																									
Athletic White	6500-77589																																									
Athletic Yellow	6500-77613																																									
Athletic Orange	6500-77621																																									
Athletic Scarlet	6500-77647																																									
Athletic Royal Blue	6500-77654																																									
Athletic Black	6500-77662																																									
Athletic Maroon	6500-77670																																									
Athletic Purple	6500-77688																																									
Athletic Navy	6500-77696																																									
Athletic Fluorescent Orange	6500-77704																																									
Athletic Fluorescent Green	6500-77712																																									
Athletic Old Gold	6500-77720																																									
Athletic Turf Green	6500-77738																																									

102.08

# SHERSTRIPE™

## ATHLETIC FIELD MARKING PAINT

### B2-900 SERIES

### AND AEROSOLS



**SHERWIN  
WILLIAMS.**

#### APPLICATION

This product is designed to be applied by a linemarking machine, but may also be applied by brush, roller, or spray. Product is supplied in a heavy-bodied formula.

Before application, reduce field marking paint with appropriate amount of clean water. Blend paint and water thoroughly.

Blending with an electric drill or mixer is recommended. Mix to a uniform consistency without creating air bubbles or foam.

Ensure that SherStripe is stirred to a perfectly smooth consistency before filling line marking machines.

#### **Roller**

Use a 3/8" - 3/4" nap synthetic roller cover.

#### **Line Striper**

See manufacturer's specifications for proper settings.

**Reduction:** Reduce as needed up to 4 parts paint to 1 part water with clean water. The amount of reduction may affect the hide, coverage and color intensity.

#### CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.

Follow manufacturer's safety recommendations when using mineral spirits.

#### CAUTIONS

For exterior use only.  
Protect from freezing.  
Non-photochemically reactive.

#### LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 02/29/2008 B02W00900 07 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.