



**SHERWIN
WILLIAMS®**



108.42

HARMONY®
WALL PRIMER
INTERIOR LATEX
B11W700

As of 05/01/09, Complies with:			
OTC	Yes	LEED® Clv2.0	Yes
SCAQMD	Yes	LEED® NCv2.2	Yes
CARB	Yes	LEED® CSv2.0	Yes
MPI Spec #	No	LEED® H	Yes
NAHB	Yes	LEED® Schools	Yes

<p>CONDITIONS AND SEALS DAMAGED DRYWALL</p>	<p align="center"><u>CHARACTERISTICS</u></p> <p>Color: White</p> <p>Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 1.3 mils dry</p> <p>Drying Time, @ 77°F, 50% RH: Drying and recoat times are temperature, humidity and film thickness dependent.</p> <p>Touch: 1 hour Recoat: 4 hours</p> <p>Finish: 0 - 5 units @ 85°</p> <p>Flash Point: N/A</p> <p>Tinting - For best color development, use the recommended "P"-shade primer. If desired, up to 4 oz per gallon of Blend-A-Color Toner can be used to approximate the topcoat color. Check color before use. Addition of Blend-A-Color Tinting Toner may increase the VOC.</p> <p>Vehicle Type: EVA</p> <p align="center">B11W00700</p> <p>VOC (EPA Method 24): 0 g/L; 0.0 lb/gal</p> <p>Volume Solids: 33 ± 2% Weight Solids: 52 ± 2% Weight per Gallon: 11.6 lb</p> <p>Water Vapor Permeance ASTM E96 A 6.9 perms</p> <p>Must be topcoated within 14 days with architectural latex or oil finishes or wallcovering. Apply wallcovering after 24 hours drying.</p> <p>When spot priming on some surfaces, a non-uniform appearance of the final coat may result, due to differences in holdout between primed and unprimed areas. To avoid this, prime the entire surface rather than spot priming.</p>	<p align="center"><u>SURFACE PREPARATION</u></p> <p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.</p> <p>Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer.</p> <p>Drywall Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon® Concrete and Masonry Primer.</p>
<p>For use on these surfaces:</p> <ul style="list-style-type: none"> • Drywall • Wood • Plywood • Previously painted surfaces <p>Harmony® Interior Latex Primer provides a low-odor, anti-microbial*, interior primer formulated without silica. You can use this product, without typical odor complaints, in occupied areas because of the very low odor during application and drying.</p> <p>This primer has been designed for use with the Harmony Interior Latex topcoats providing a complete low odor/low VOC system. If desired, you can topcoat with any Sherwin-Williams interior latex or oil architectural topcoat</p> <p>Anti-microbial This product contains agents which inhibit the growth of microbes on the surface of this paint film.</p>		

108.42

HARMONY[®]

WALL PRIMER

INTERIOR LATEX

B11W700



**SHERWIN
WILLIAMS[®]**

SURFACE PREPARATION

Plaster

Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking

Fill gaps between walls, ceilings, crown moldings, and other trim with the appropriate caulk after priming the surface.

APPLICATION

Use at temperatures above 50°F.
No reduction necessary.

Brush

Use a nylon/polyester brush

Roller

Use a 1/4" - 3/4" nap synthetic cover

Spray - Airless

Pressure 2000 psi

Tip017"-.021"

CLEANUP INFORMATION

Clean spills, spatters, hands and tools with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

For interior use only.
Protect from freezing.
Non-photochemically reactive.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**
HOTW 05/13/2009 B11W00700 10 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.