



**SHERWIN
WILLIAMS®**

As of 08/19/09, Complies with:			
OTC	Yes	LEED® Civ2.0	No
SCAQMD	No	LEED® NCv2.2	No
CARB	No	LEED® CSv2.0	No
MPI Spec #	No	LEED® H	No
NAHB	No		

FAST DRYING PRIMER

INTERIOR/EXTERIOR OIL-BASED Y24W8980

PREVIOUSLY PREPRITE® QUICK SEAL EXTERIOR/INTERIOR FAST DRY PRIMER

DRIES FAST AND BLOCKS STAINS	CHARACTERISTICS	SURFACE PREPARATION
<ul style="list-style-type: none"> Assures uniform appearance of exterior and interior topcoats Fast dry Stain killing sealer Topcoat with latex or oil paints Use for new construction or repainting Can be applied down to 40°F <p>For use on these surfaces:</p> <ul style="list-style-type: none"> Wood Hardboard PVC Piping Previously Painted Surfaces <p>Fast Drying Primer is not ideal for whole house exterior priming. Best choices are Exterior Oil-Based Wood Primer or Exterior Latex Wood Primer. Fast Drying Primer is a compromise solution for exteriors that should be discussed only after other options have been definitely ruled out. Contractors need to be cautioned that fast dry exterior oil-based primers are quick fixes that will not be as durable as the recommended primers.</p>	<p>Color: White</p> <p>Coverage: 350 - 400 sq ft/gal @ 4 mils wet; 1.7 mils dry</p> <p>Drying Time, @ 50% RH: Drying and recoat times are temperature, humidity and film thickness dependent.</p> <p style="text-align: center;">77°F 40°F</p> <p>Touch: 30 minutes 1 hour Recoat 1 hour 2 hours</p> <p>Finish: 0-10 units @ 85°</p> <p>Flash Point: 90°F, PMCC</p> <p>Tinting - For best color development, use the recommended "P"-shade primer. If desired, up to 4 oz per gallon of Blend-A-Color Toner can be used to approximate the topcoat color. Check color before use.</p> <p>Vehicle Type: Vinyl Toluene Copolymer Y24W08980</p> <p>VOC (less exempt solvents): 337 g/L; 2.81 lb/gal</p> <p>Volume Solids: 56 ± 2% Weight Solids: 79 ± 2% Weight per Gallon: 13.7 lb</p> <p>Must be topcoated within 14 days with architectural latex or oil finishes or wallcovering. Apply wallcovering after 24 hours drying.</p> <p>When spot priming on some surfaces, a non-uniform appearance of the final coat may result, due to differences in holdout between primed and unprimed areas. To avoid this, prime the entire surface rather than spot priming.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.</p> <p>Wood, Hardboard, Paneling Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p> <p>Plaster Bare plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p>

109.32

FAST DRYING PRIMER

INTERIOR/EXTERIOR OIL-BASED

Y24W8980



**SHERWIN
WILLIAMS®**

SURFACE PREPARATION

Mildew

Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

Caulking

Fill gaps between windows, doors, trim, and other through-wall openings with the appropriate caulk after priming the surface.

APPLICATION

Apply at temperatures above 40°F.
No reduction necessary.

Brush

Use a natural bristle brush.

Roller

Use a 1/4"-3/4" nap synthetic cover.

Airless Spray

Pressure 2000 psi

Tip015"-.019"

CLEANUP INFORMATION

Clean spills and spatters immediately with mineral spirits. Clean tools immediately after use with mineral spirits. Follow manufacturer's safety recommendations when using mineral spirits.

CAUTIONS

Non-photochemically reactive.

LABEL CAUTIONS

ALIPHATIC HYDROCARBONS, CRYSTALLINE SILICA. Contents are FLAMMABLE. Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVER-EXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

HOTW 05/16/2009 Y24W08980 04 00

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.