

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 31, 2023

23 00 [2383]

## PRODUCT NUMBER

CC930

## PRODUCT NAME

ULTRA 7000® Speed-Plus Performance Clearcoat (Part A)

## MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

4440 Warrensville Center Road

Warrensville Heights, OH 44128

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

CC930 = | Acute | Chronic | Fire |

## Product Weight

8.07 lb/gal

## Specific Gravity

0.97

## FLASH POINT

7 °F PMCC

## Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Acetone 67-64-1	N	Y	N	N	11	14
n-Butyl Propionate 590-01-2	N	N	N	N	11	12
n-Butyl Acetate 123-86-4	N	Y	N	N	27	30

## Volatile Organic Compounds - U.S. EPA / Canada

	CC930	
	LB/Gal	g/L
Coating Density	8.07	967
	By wt	By vol
Total Volatiles	49.3%	56.6%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	11.4%	13.9%
Organic Volatiles	37.9%	42.7%
Percent Non-Volatile	50.7%	43.4%
VOC Content	LB/Gal	g/L
Total	3.06	367
Less exempt solvents	3.55	426
Of solids	7.05	845
Of solids	0.74 lb/lb	0.74 kg/kg
	By wt	
By wt LVP-VOC	37.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.39**

**Volatile Organic Compounds - California**

	CC930	
	LB/Gal	g/L
Coating Density	8.07	967
	By wt	By vol
Total Volatiles	49.3%	56.6%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.4%	13.9%
Organic Volatiles	37.9%	42.7%
Percent Non-Volatile	50.7%	43.4%
VOC Content	LB/Gal	g/L
Total	3.06	367
Less exempt solvents	3.55	426
Of solids	7.05	845
Of solids	0.74 lb/lb	0.74 kg/kg
	By wt	
By wt LVP-VOC	37.9%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.36**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	CC930	
	LB/Gal	g/L
Coating Density	8.07	967
	By wt	By vol
Total Volatiles	49.3%	56.6%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.4%	13.9%
Organic Volatiles	37.9%	42.7%
Percent Non-Volatile	50.7%	43.4%
VOC Content	LB/Gal	g/L
Total	3.06	367
Less exempt solvents	3.55	426
Of solids	7.05	845
Of solids	0.74 lb/lb	0.74 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	CC930	
	By wt	By vol
Total Volatiles	49.3%	56.6%
VOC Content	LB/Gal	g/L
Total	3.98	477

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	CC930	
	By wt	By vol
Total Volatiles	49.3%	56.6%
VOC Content	LB/Gal	g/L
Total	3.98	477

## **Volatile Organic Compounds - Mexico**

	CC930	
	LB/Gal	g/L
Coating Density	8.07	967
	By wt	By vol
Total Volatiles	49.3%	56.6%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.4%	13.9%
Organic Volatiles	37.9%	42.7%
Percent Non-Volatile	50.7%	43.4%
VOC Content	LB/Gal	g/L
Total	3.06	367
Less exempt solvents	3.55	426
Of solids	7.05	845
Of solids	0.74 lb/lb	0.74 kg/kg

## **Hazardous Air Pollutants (Clean Air Act, Section 112(b))**

	CC930	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

## **Air Quality Data**

### **Density of Organic Solvent Blend**

7.04 lb/gal

### **Photochemically Reactive**

No

## **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.