

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 31, 2023

23 00 [1892]

PRODUCT NUMBER

E2W805

PRODUCT NAME

0.5 VOC Urethane Primer (Part A), White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

4440 Warrensville Center Road

Warrensville Heights, OH 44128

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

E2W805 = | Acute | Chronic | Fire |

Product Weight

14.18 lb/gal

Specific Gravity

1.71

FLASH POINT

10 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Acetone 67-64-1	N	Y	N	N	11	24
t-Butyl Acetate 540-88-5	N	Y	N	N	5	9

Volatile Organic Compounds - U.S. EPA / Canada

	E2W805	
	LB/Gal	g/L
Coating Density	14.18	1698
	By wt	By vol
Total Volatiles	18.3%	38.2%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	11.2%	24.1%
T-Butyl Acetate	4.8%	9.4%
Organic Volatiles	2.3%	4.7%
Percent Non-Volatile	81.7%	61.8%
VOC Content	LB/Gal	g/L
Total	0.33	39
Less exempt solvents	0.49	59
Of solids	0.53	64
Of solids	0.02 lb/lb	0.02 kg/kg
	By wt	
By wt LVP-VOC	0.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.38**

Volatile Organic Compounds - California

	E2W805	
	LB/Gal	g/L
Coating Density	14.18	1698
	By wt	By vol
Total Volatiles	18.3%	38.2%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.2%	24.1%
Organic Volatiles	7.1%	14.1%
Percent Non-Volatile	81.7%	61.8%
VOC Content	LB/Gal	g/L
Total	1.00	120
Less exempt solvents	1.32	158
Of solids	1.62	194
Of solids	0.08 lb/lb	0.08 kg/kg
	By wt	
By wt LVP-VOC	5.7%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.21**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	E2W805	
	LB/Gal	g/L
Coating Density	14.18	1698
	By wt	By vol
Total Volatiles	18.3%	38.2%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.2%	24.1%
Organic Volatiles	7.1%	14.1%
Percent Non-Volatile	81.7%	61.8%
VOC Content	LB/Gal	g/L
Total	1.00	120
Less exempt solvents	1.32	158
Of solids	1.62	194
Of solids	0.08 lb/lb	0.08 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	E2W805	
	By wt	By vol
Total Volatiles	18.3%	38.2%
VOC Content	LB/Gal	g/L
Total	2.58	310

Volatile Organic Compounds - EU Directive 2010/75/EU

	E2W805	
	By wt	By vol
Total Volatiles	18.3%	38.2%
VOC Content	LB/Gal	g/L
Total	2.58	310

Volatile Organic Compounds - Mexico

	E2W805	
	LB/Gal	g/L
Coating Density	14.18	1698
	By wt	By vol
Total Volatiles	18.3%	38.2%
Exempt solvents		
Water	0.0%	0.0%
Acetone	11.2%	24.1%
Organic Volatiles	7.1%	14.1%
Percent Non-Volatile	81.7%	61.8%
VOC Content	LB/Gal	g/L
Total	1.00	120
Less exempt solvents	1.32	158
Of solids	1.62	195
Of solids	0.08 lb/lb	0.08 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	E2W805	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.78 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.