ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

06 00 [1983]

PRODUCT NUMBER

E61R751

PRODUCT NAME

KEM-FLASH® 500 Primer, Red Oxide

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

E61R751 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT12.83 lb/gal1.5465 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.1	< 1
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	4	8
Cumene 98-82-8	N	Υ	Υ	Υ	0.2	< 1
Trimethylbenzene 25551-13-7	N	N	N	N	2	4
Methyl Isobutyl Ketone 108-10-1	N	Υ	Υ	Υ	14	27

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Zinc (as Zn)	N	Υ	Υ	N	3	
Zinc Compound	N	N	Υ	N	7	

Volatile Organic Compounds - U.S. EPA / Canada

	E61R751		
	LB/Gal	g/L	
Coating Density	12.83	1537	
	By wt	By vol	
Total Volatiles	24.9%	46.4%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	24.8%	46.3%	
Percent Non-Volatile	75.1%	53.6%	
VOC Content	LB/Gal	g/L	
Total	3.18	381	
Less exempt solvents	3.18	382	
Of solids	5.94	712	
Of solids	0.33 lb/lb	0.33 kg/kg	
	By wt		
By wt LVP-VOC	24.8%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.43

Volatile Organic Compounds - California

	E61R751		
	LB/Gal	g/L	
Coating Density	12.83	1537	
	By wt	By vol	
Total Volatiles	24.9%	46.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	24.9%	46.4%	
Percent Non-Volatile	75.1%	53.6%	
VOC Content	LB/Gal	g/L	
Total	3.19	383	
Less exempt solvents	3.19	383	
Of solids	5.96	715	
Of solids	0.33 lb/lb	0.33 kg/kg	
	By wt		
By wt LVP-VOC	24.8%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.33

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	E61R751		
	LB/Gal	g/L	
Coating Density	12.83	1537	
	By wt	By vol	
Total Volatiles	24.9%	46.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	24.8%	46.3%	
Percent Non-Volatile	75.1%	53.6%	
VOC Content	LB/Gal	g/L	
Total	3.18	381	
Less exempt solvents	3.18	382	
Of solids	5.94	712	
Of solids	0.33 lb/lb	0.33 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	E61R751		
	By wt	By vol	
Total Volatiles	24.9%	46.4%	
VOC Content	LB/Gal	g/L	
Total	3.19	383	

Volatile Organic Compounds - EU Directive 2010/75/EU

	E61R751	
	By wt	By vol
Total Volatiles	24.8%	46.3%
VOC Content	LB/Gal	g/L
Total	3.18	381

Volatile Organic Compounds - Mexico

	E61R751		
	LB/Gal	g/L	
Coating Density	12.83	1537	
	By wt	By vol	
Total Volatiles	24.9%	46.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	24.9%	46.4%	
Percent Non-Volatile	75.1%	53.6%	
VOC Content	LB/Gal	g/L	
Total	3.19	383	
Less exempt solvents	3.19	383	
Of solids	5.96	715	
Of solids	0.33 lb/lb	0.33 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	E61R751		
	LB/Gal	kg/L	
Volatile HAPS	1.88	0.225	
Of solids	3.51	0.420	
Of solids	0.19 lb/lb	0.19 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.88 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.