ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

PRODUCT NUMBER

09 00 [0193]

F63W102

PRODUCT NAME

Polane® 8890 Polyurethane Enamel, Low Gloss White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F63W102 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT11.57 lb/gal1.3985 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.2	0.4
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	5	8
Cumene 98-82-8	N	Υ	Υ	Υ	0.3	0.6
1,3,5-Trimethylbenzene 108-67-8	N	N	N	N	1	2
1,2,4-Trimethylbenzene 95-63-6	N	N	Υ	N	1	2
Trimethylbenzene 25551-13-7	N	N	N	N	3	4
n-Butyl Acetate 123-86-4	N	Υ	N	N	13	20
t-Butyl Acetate 540-88-5	N	Υ	N	N	5	7

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lead (as Pb)	N	N	Υ	N	0.00005	

Volatile Organic Compounds - U.S. EPA / Canada

	F63W102		
	LB/Gal	g/L	
Coating Density	11.57	1386	
	By wt	By vol	
Total Volatiles	30.2%	48.2%	
Federally exempt solvents			
Water	0.0%	0.0%	
T-Butyl Acetate	4.7%	7.5%	
Organic Volatiles	25.5%	40.7%	
Percent Non-Volatile	69.8%	51.8%	
VOC Content	LB/Gal	g/L	
Total	2.94	353	
Less exempt solvents	3.18	382	
Of solids	5.69	681	
Of solids	0.36 lb/lb	0.36 kg/kg	
	By wt		
By wt LVP-VOC	25.5%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.18

Volatile Organic Compounds - California

	F63W102	
	LB/Gal	g/L
Coating Density	11.57	1386
	By wt	By vol
Total Volatiles	30.2%	48.2%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	30.2%	48.2%
Percent Non-Volatile	69.8%	51.8%
VOC Content	LB/Gal	g/L
Total	3.48	418
Less exempt solvents	3.48	418
Of solids	6.73	806
Of solids	0.43 lb/lb	0.43 kg/kg
	By wt	
By wt LVP-VOC	30.1%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.12

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F63W102		
	LB/Gal	g/L	
Coating Density	11.57	1386	
	By wt	By vol	
Total Volatiles	30.2%	48.2%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	30.2%	48.2%	
Percent Non-Volatile	69.8%	51.8%	
VOC Content	LB/Gal	g/L	
Total	3.48	418	
Less exempt solvents	3.48	418	
Of solids	6.73	806	
Of solids	0.43 lb/lb	0.43 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	F63W102	
	By wt	By vol
Total Volatiles	30.2%	48.2%
VOC Content	LB/Gal	g/L
Total	3.48	418

Volatile Organic Compounds - EU Directive 2010/75/EU

	F63\	W102
	By wt	By vol
Total Volatiles	30.2%	48.2%
VOC Content	LB/Gal	g/L
Total	3.48	418

Volatile Organic Compounds - Mexico

F63W102		
LB/Gal	g/L	
11.57	1386	
By wt	By vol	
30.2%	48.2%	
0.0%	0.0%	
30.2%	48.2%	
69.8%	51.8%	
LB/Gal	g/L	
3.48	418	
3.48	418	
6.73	806	
0.43 lb/lb	0.43 kg/kg	
	LB/Gal 11.57 By wt 30.2% 0.0% 30.2% 69.8% LB/Gal 3.48 3.48 6.73	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F63W102		
	LB/Gal	kg/L	
Volatile HAPS	0.06	0.008	
Of solids	0.13	0.015	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.25 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.