ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Jan 20, 2024

37 00 [3463]

PRODUCT NUMBER

F63W13

PRODUCT NAME

POLANE® B Polyurethane Enamel (Part A), Strobe White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 W. Prospect Avenue
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F63W13 = | Acute | Chronic | Fire |

Product Weight	Specific Gravity	FLASH POINT
10.44 lb/gal	1.26	41 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Toluene **108-88-3**	N	Y	Y	Y	4	6
Ethylbenzene **100-41-4**	N	Y	Y	Y	0.5	< 1
Xylene **1330-20-7**	N	Y	Y	Y	3	5
Methyl Ethyl Ketone **78-93-3**	N	Y	N	N	14	22
Cyclohexanone **108-94-1**	N	Y	N	N	14	19
n-Butyl Acetate **123-86-4**	N	Y	N	N	8	11

Volatile Organic Compounds - U.S. EPA / Canada

	F63W13	
	LB/Gal	**g/L**
Coating Density	10.44	1251
	By wt	**By vol**
Total Volatiles	44.7%	64.4%
Federally exempt solvents		
Water	0.2%	0.3%
Organic Volatiles	44.4%	64.1%
Percent Non-Volatile	55.3%	35.6%
VOC Content	**LB/Gal**	**g/L**
Total	4.63	555
Less exempt solvents	4.65	557
Of solids	13.01	1559
Of solids	0.80 lb/lb	0.80 kg/kg
	By wt	
By wt LVP-VOC	44.4%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.95**

Volatile Organic Compounds - California

	F63W13	
	LB/Gal	**g/L**
Coating Density	10.44	1251
	By wt	**By vol**
Total Volatiles	44.7%	64.4%
Exempt solvents		
Water	0.2%	0.3%
Organic Volatiles	44.4%	64.1%
Percent Non-Volatile	55.3%	35.6%
VOC Content	**LB/Gal**	**g/L**
Total	4.63	555
Less exempt solvents	4.65	557
Of solids	13.01	1559
Of solids	0.80 lb/lb	0.80 kg/kg
	By wt	
By wt LVP-VOC	44.4%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.91**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F63W13	
	LB/Gal	g/L
Coating Density	10.44	1251
	By wt	By vol
Total Volatiles	44.7%	64.4%
Exempt solvents		
Water	0.2%	0.3%
Organic Volatiles	44.4%	64.1%
Percent Non-Volatile	55.3%	35.6%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.65	557
Of solids	13.01	1559
Of solids	0.80 lb/lb	0.80 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	F63W13	
	By wt	By vol
Total Volatiles	44.7%	64.4%
VOC Content	LB/Gal	g/L
Total	4.63	555

Volatile Organic Compounds - EU Directive 2010/75/EU

	F63W13	
	By wt	By vol
Total Volatiles	44.7%	64.4%
VOC Content	LB/Gal	g/L
Total	4.63	555

Volatile Organic Compounds - Mexico

	F63W13	
	LB/Gal	g/L
Coating Density	10.44	1251
	By wt	By vol
Total Volatiles	44.7%	64.4%
Exempt solvents		
Water	0.2%	0.3%
Organic Volatiles	44.4%	64.1%
Percent Non-Volatile	55.3%	35.6%
VOC Content	LB/Gal	g/L
Total	4.63	555
Less exempt solvents	4.65	557
Of solids	13.01	1559
Of solids	0.80 lb/lb	0.80 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F63W13	
	LB/Gal	kg/L
Volatile HAPS	0.86	0.104
Of solids	2.43	0.292
Of solids	0.15 lb/lb	0.15 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.24 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.