

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Mar 20, 2024

21 00 [1183]

PRODUCT NUMBER

F63W200

PRODUCT NAME

POLANE® 8910 Polyurethane Enamel, High Gloss White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F63W200 = | Acute | Chronic | Fire |

Product Weight

10.79 lb/gal

Specific Gravity

1.30

FLASH POINT

81 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Y	0.1	< 1
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	20	32
n-Butyl Acetate 123-86-4	N	Y	N	N	3	4

Volatile Organic Compounds - U.S. EPA / Canada

	F63W200	
	LB/Gal	g/L
Coating Density	10.79	1292
	By wt	By vol
Total Volatiles	24.5%	38.5%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	24.5%	38.5%
Percent Non-Volatile	75.5%	61.5%
VOC Content	LB/Gal	g/L
Total	2.64	316
Less exempt solvents	2.64	316
Of solids	4.30	515
Of solids	0.32 lb/lb	0.32 kg/kg
	By wt	
By wt LVP-VOC	24.4%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.78**

Volatile Organic Compounds - California

	F63W200	
	LB/Gal	g/L
Coating Density	10.79	1292
	By wt	By vol
Total Volatiles	24.5%	38.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	24.5%	38.5%
Percent Non-Volatile	75.5%	61.5%
VOC Content	LB/Gal	g/L
Total	2.64	316
Less exempt solvents	2.64	316
Of solids	4.30	515
Of solids	0.32 lb/lb	0.32 kg/kg
	By wt	
By wt LVP-VOC	24.4%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.63**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F63W200	
	LB/Gal	g/L
Coating Density	10.79	1292
	By wt	By vol
Total Volatiles	24.5%	38.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	24.5%	38.5%
Percent Non-Volatile	75.5%	61.5%
VOC Content	LB/Gal	g/L
Total	2.64	316
Less exempt solvents	2.64	316
Of solids	4.30	515
Of solids	0.32 lb/lb	0.32 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	F63W200	
	By wt	By vol
Total Volatiles	24.5%	38.5%
VOC Content	LB/Gal	g/L
Total	2.64	317

Volatile Organic Compounds - EU Directive 2010/75/EU

	F63W200	
	By wt	By vol
Total Volatiles	24.5%	38.5%
VOC Content	LB/Gal	g/L
Total	2.64	316

Volatile Organic Compounds - Mexico

	F63W200	
	LB/Gal	g/L
Coating Density	10.79	1292
	By wt	By vol
Total Volatiles	24.5%	38.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	24.5%	38.5%
Percent Non-Volatile	75.5%	61.5%
VOC Content	LB/Gal	g/L
Total	2.64	316
Less exempt solvents	2.64	316
Of solids	4.30	515
Of solids	0.32 lb/lb	0.32 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F63W200	
	LB/Gal	kg/L
Volatile HAPS	0.01	0.002
Of solids	0.03	0.003
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.87 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.