# **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

06 00 [1713]

Date of Preparation Apr 19, 2024

### **PRODUCT NUMBER**

F63WC182

#### **PRODUCT NAME**

POLANE® D8700 DTM Medium Gloss, White Base

#### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

F63WC182 = | Acute | Chronic | Fire |

Product Weight 12.26 lb/gal	Specific Gravity 1.48		FLASH POINT 81 °F PMCC			
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Y	0.2	0.4
5-Ethyl-2-nonanone 5440-89-1	N	N	N	N	2	3
Diamyl Ketone 927-49-1	N	N	N	N	1	2
Methyl n-Amyl Ketone 110-43-0	N	N	Ν	N	17	31

#### Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	Ν	Ν	Y	Ν	0.000006	
Lead (as Pb)	Ν	N	Y	Ν	0.00006	

# Volatile Organic Compounds - U.S. EPA / Canada

	F63WC182		
	LB/Gal	g/L	
Coating Density	12.26	1469	
	By wt	By vol	
Total Volatiles	22.2%	40.4%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	22.2%	40.4%	
Percent Non-Volatile	77.8%	59.6%	
VOC Content	LB/Gal	g/L	
Total	2.71	325	
Less exempt solvents	2.71	325	
Of solids	4.55	546	
Of solids	0.28 lb/lb	0.28 kg/kg	
	By wt		
By wt LVP-VOC	19.2%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.19

### Volatile Organic Compounds - California

	F63WC182		
	LB/Gal	g/L	
Coating Density	12.26	1469	
	By wt	By vol	
Total Volatiles	22.2%	40.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	22.2%	40.4%	
Percent Non-Volatile	77.8%	59.6%	
VOC Content	LB/Gal	g/L	
Total	2.71	325	
Less exempt solvents	2.71	325	
Of solids	4.55	546	
Of solids	0.28 lb/lb	0.28 kg/kg	
	By wt		
By wt LVP-VOC	19.2%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.80

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F63WC182		
	LB/Gal	g/L	
Coating Density	12.26	1469	
	By wt	By vol	
Total Volatiles	22.2%	40.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	22.2%	40.4%	
Percent Non-Volatile	77.8%	59.6%	
VOC Content	LB/Gal	g/L	
Total	2.71	325	
Less exempt solvents	2.71	325	
Of solids	4.55	546	
Of solids	0.28 lb/lb	0.28 kg/kg	

# Volatile Organic Compounds - EU Directive 2004/42/EC

	F63WC182		
	By wt	By vol	
<b>Total Volatiles</b>	22.8%	41.2%	
VOC Content	LB/Gal	g/L	
Total	2.79	334	

# Volatile Organic Compounds - EU Directive 2010/75/EU

	F63WC182	
	By wt	By vol
<b>Total Volatiles</b>	22.2%	40.4%
VOC Content	LB/Gal	g/L
Total	2.71	325

# Volatile Organic Compounds - Mexico

	F63WC182		
	LB/Gal	g/L	
Coating Density	12.26	1469	
	By wt	By vol	
Total Volatiles	22.2%	40.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	22.2%	40.4%	
Percent Non-Volatile	77.8%	59.6%	
VOC Content	LB/Gal	g/L	
Total	2.71	325	
Less exempt solvents	2.71	325	
Of solids	4.55	546	
Of solids	0.28 lb/lb	0.28 kg/kg	

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F63WC182		
	LB/Gal	kg/L	
Volatile HAPS	0.02	0.003	
Of solids	0.04	0.005	
Of solids	0.00 lb/lb	0.00 kg/kg	

### **Air Quality Data**

Density of Organic Solvent Blend 6.73 lb/gal Photochemically Reactive No

#### Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.