ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

37 00 [0193]

PRODUCT NUMBER

F65A49

PRODUCT NAME

KEM LUSTRAL® Enamel, ASA 49 Gray

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F65A49 = | Acute | Chronic | Fire |

 Product Weight
 Specific Gravity
 FLASH POINT

 7.81 lb/gal
 0.94
 102 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	49	60
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.2	0.2

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Υ	N	0.0000005	
Lead (as Pb)	N	N	Υ	N	0.000009	
Cobalt Compound	N	N	Υ	Υ	0.2	

Volatile Organic Compounds - U.S. EPA / Canada

	F65A49	
	LB/Gal	g/L
Coating Density	7.81	936
	By wt	By vol
Total Volatiles	52.2%	63.2%
Federally exempt solvents		
Water	0.0%	0.0%
4-Methyl-1,3-dioxolan-2- one	0.3%	0.2%
Organic Volatiles	51.9%	62.9%
Percent Non-Volatile	47.8%	36.8%
VOC Content	LB/Gal	g/L
Total	4.05	485
Less exempt solvents	4.06	487
Of solids	11.02	1320
Of solids	1.08 lb/lb	1.08 kg/kg
	By wt	
By wt LVP-VOC	51.7%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.49

Volatile Organic Compounds - California

	F65A49		
	LB/Gal	g/L	
Coating Density	7.81	936	
	By wt	By vol	
Total Volatiles	52.2%	63.2%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	52.2%	63.1%	
Percent Non-Volatile	47.8%	36.8%	
VOC Content	LB/Gal	g/L	
Total	4.07	488	
Less exempt solvents	4.07	488	
Of solids	11.07	1327	
Of solids	1.09 lb/lb	1.09 kg/kg	
	By wt		
By wt LVP-VOC	51.7%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.44

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F65A49		
	LB/Gal	g/L	
Coating Density	7.81	936	
	By wt	By vol	
Total Volatiles	52.2%	63.2%	
Exempt solvents			
Water	0.0%	0.0%	
4-Methyl-1,3-dioxolan-2-	0.3%	0.2%	
one	0.5%	0.2%	
Organic Volatiles	51.9%	62.9%	
Percent Non-Volatile	47.8%	36.8%	
VOC Content	LB/Gal	g/L	
Total	4.05	485	
Less exempt solvents	4.06	487	
Of solids	11.02	1320	
Of solids	1.08 lb/lb	1.08 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	F65A49		
	By wt	By vol	
Total Volatiles	52.2%	63.2%	
VOC Content	LB/Gal	g/L	
Total	4.07	488	

Volatile Organic Compounds - EU Directive 2010/75/EU

	F65A49		
	By wt	By vol	
Total Volatiles	52.0%	63.0%	
VOC Content	LB/Gal	g/L	
Total	4.05	485	

Volatile Organic Compounds - Mexico

	F65A49		
	LB/Gal	g/L	
Coating Density	7.81	936	
	By wt	By vol	
Total Volatiles	52.2%	63.2%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	52.2%	63.1%	
Percent Non-Volatile	47.8%	36.8%	
VOC Content	LB/Gal	g/L	
Total	4.07	488	
Less exempt solvents	4.07	488	
Of solids	11.07	1327	
Of solids	1.09 lb/lb	1.09 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F65A49		
	LB/Gal	kg/L	
Volatile HAPS	0.01	0.001	
Of solids	0.03	0.004	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.46 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.