

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

21 00 [2242]

PRODUCT NUMBER

F75B550

PRODUCT NAME

KEM AQUA® 400 Waterborne Enamel, Black

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F75B550 = | Acute | Chronic | Fire |

Product Weight

8.60 lb/gal

Specific Gravity

1.03

FLASH POINT

129 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
2-Butanol 78-92-2	N	N	Y	N	3	4
Water 7732-18-5	N	N	N	N	51	53

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lead (as Pb)	N	N	Y	N	0.000007	
Cobalt Compound	N	N	Y	Y	0.2	

Volatile Organic Compounds - U.S. EPA / Canada

	F75B550	
	LB/Gal	g/L
Coating Density	8.60	1030
	By wt	By vol
Total Volatiles	57.0%	60.5%
Federally exempt solvents		
Water	51.3%	53.2%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.2%
Organic Volatiles	5.5%	7.0%
Percent Non-Volatile	43.0%	39.5%
VOC Content	LB/Gal	g/L
Total	0.47	56
Less exempt solvents	1.01	121
Of solids	1.19	143
Of solids	0.12 lb/lb	0.12 kg/kg
	By wt	
By wt LVP-VOC	5.5%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.21**

Volatile Organic Compounds - California

	F75B550	
	LB/Gal	g/L
Coating Density	8.60	1030
	By wt	By vol
Total Volatiles	57.0%	60.5%
Exempt solvents		
Water	51.3%	53.2%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.2%
Organic Volatiles	5.5%	7.0%
Percent Non-Volatile	43.0%	39.5%
VOC Content	LB/Gal	g/L
Total	0.47	56
Less exempt solvents	1.01	121
Of solids	1.19	143
Of solids	0.12 lb/lb	0.12 kg/kg
	By wt	
By wt LVP-VOC	5.5%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.11**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F75B550	
	LB/Gal	g/L
Coating Density	8.60	1030
	By wt	By vol
Total Volatiles	57.0%	60.5%
Exempt solvents		
Water	51.3%	53.2%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.2%
Organic Volatiles	5.5%	7.0%
Percent Non-Volatile	43.0%	39.5%
VOC Content	LB/Gal	g/L
Total	0.47	56
Less exempt solvents	1.01	121
Of solids	1.19	143
Of solids	0.12 lb/lb	0.12 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	F75B550	
	By wt	By vol
Total Volatiles	57.0%	60.5%
VOC Content	LB/Gal	g/L
Total	0.47	56

Volatile Organic Compounds - EU Directive 2010/75/EU

	F75B550	
	By wt	By vol
Total Volatiles	57.0%	60.5%
VOC Content	LB/Gal	g/L
Total	0.47	56

Volatile Organic Compounds - Mexico

	F75B550	
	LB/Gal	g/L
Coating Density	8.60	1030
	By wt	By vol
Total Volatiles	57.0%	60.5%
Exempt solvents		
Water	51.3%	53.2%
Non-Organic Volatiles		
Ammonium Hydroxide	0.2%	0.2%
Organic Volatiles	5.5%	7.0%
Percent Non-Volatile	43.0%	39.5%
VOC Content	LB/Gal	g/L
Total	0.47	56
Less exempt solvents	1.01	121
Of solids	1.20	143
Of solids	0.12 lb/lb	0.12 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F75B550	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

6.73 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.