### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Jan 19, 2024

## **PRODUCT NUMBER**

12 00 [1983]

F75S491

#### **PRODUCT NAME**

KEM® 400 Enamel, Silver Metallic

#### **MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

F75S491 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.91 lb/gal0.9555 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	8	10
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	8	8
Xylene 1330-20-7	N	Υ	Υ	Υ	43	47
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	2	2
Cumene 98-82-8	N	Υ	Υ	Υ	0.1	< 1

#### **Regulated Compounds**

	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Cobalt Compound	N	N	Υ	Υ	0.1	

# Volatile Organic Compounds - U.S. EPA / Canada

	F75S491		
	LB/Gal	g/L	
Coating Density	7.91	947	
	By wt	By vol	
Total Volatiles	63.5%	71.4%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	63.5%	71.4%	
Percent Non-Volatile	36.5%	28.6%	
VOC Content	LB/Gal	g/L	
Total	5.02	601	
Less exempt solvents	5.02	601	
Of solids	17.58	2107	
Of solids	1.74 lb/lb	1.74 kg/kg	
	By wt		
By wt LVP-VOC	63.5%	· · · · · · · · · · · · · · · · · · ·	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 3.94

## **Volatile Organic Compounds - California**

	F75S491		
	LB/Gal	g/L	
Coating Density	7.91	947	
	By wt	By vol	
Total Volatiles	63.5%	71.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	63.5%	71.4%	
Percent Non-Volatile	36.5%	28.6%	
VOC Content	LB/Gal	g/L	
Total	5.02	601	
Less exempt solvents	5.02	601	
Of solids	17.58	2107	
Of solids	1.74 lb/lb	1.74 kg/kg	
	By wt		
By wt LVP-VOC	63.5%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 3.92

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F75S491		
	LB/Gal	g/L	
Coating Density	7.91	947	
	By wt	By vol	
Total Volatiles	63.5%	71.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	63.5%	71.4%	
Percent Non-Volatile	36.5%	28.6%	
VOC Content	LB/Gal	g/L	
Total	5.02	601	
Less exempt solvents	5.02	601	
Of solids	17.58	2107	
Of solids	1.74 lb/lb	1.74 kg/kg	

## Volatile Organic Compounds - EU Directive 2004/42/EC

	F75S491		
	By wt	By vol	
Total Volatiles	63.5%	71.4%	
VOC Content	LB/Gal	g/L	
Total	5.02	601	

# Volatile Organic Compounds - EU Directive 2010/75/EU

	F75S491	
	By wt	By vol
Total Volatiles	63.5%	71.4%
VOC Content	LB/Gal	g/L
Total	5.02	601

# **Volatile Organic Compounds - Mexico**

F75S491		
LB/Gal	g/L	
7.91	947	
By wt	By vol	
63.5%	71.4%	
0.0%	0.0%	
63.5%	71.4%	
36.5%	28.6%	
LB/Gal	g/L	
5.02	601	
5.02	601	
17.58	2107	
1.74 lb/lb	1.74 kg/kg	
	LB/Gal 7.91  By wt 63.5%  0.0% 63.5% 36.5%  LB/Gal 5.02 17.58	

## Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F75S491		
	LB/Gal	kg/L	
Volatile HAPS	3.99	0.479	
Of solids	14.00	1.677	
Of solids	1.38 lb/lb	1.38 kg/kg	

## **Air Quality Data**

**Density of Organic Solvent Blend** 

7.03 lb/gal

**Photochemically Reactive** 

Yes

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.