

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation  
Jan 19, 2024

28 00 [1983]

## PRODUCT NUMBER

F75WC1

## PRODUCT NAME

Fast Production Enamel, White

## MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

F75WC1 = | Acute | Chronic | Fire |

## Product Weight

8.39 lb/gal

## Specific Gravity

1.01

## FLASH POINT

45 °F PMCC

## Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	28	38
Toluene 108-88-3	N	Y	Y	Y	6	7
Ethylbenzene 100-41-4	N	Y	Y	Y	0.4	< 1
Xylene 1330-20-7	N	Y	Y	Y	2	3
2-Methyl-1-propanol 78-83-1	N	Y	N	N	13	17
Isobutyl Acetate 110-19-0	N	Y	N	N	2	3

**Volatile Organic Compounds - U.S. EPA / Canada**

	F75WC1	
	LB/Gal	g/L
Coating Density	8.39	1005
	By wt	By vol
Total Volatiles	54.0%	69.8%
Federally exempt solvents		
Water	0.1%	0.1%
Organic Volatiles	53.9%	69.7%
Percent Non-Volatile	46.0%	30.2%
VOC Content	LB/Gal	g/L
Total	4.52	542
Less exempt solvents	4.53	543
Of solids	15.01	1799
Of solids	1.17 lb/lb	1.17 kg/kg
	By wt	
By wt LVP-VOC	53.5%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.09**

**Volatile Organic Compounds - California**

	F75WC1	
	LB/Gal	g/L
Coating Density	8.39	1005
	By wt	By vol
Total Volatiles	54.0%	69.8%
Exempt solvents		
Water	0.1%	0.1%
Organic Volatiles	53.9%	69.7%
Percent Non-Volatile	46.0%	30.2%
VOC Content	LB/Gal	g/L
Total	4.52	542
Less exempt solvents	4.53	543
Of solids	15.01	1799
Of solids	1.17 lb/lb	1.17 kg/kg
	By wt	
By wt LVP-VOC	53.5%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.13**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	F75WC1	
	LB/Gal	g/L
Coating Density	8.39	1005
	By wt	By vol
Total Volatiles	54.0%	69.8%
Exempt solvents		
Water	0.1%	0.1%
Organic Volatiles	53.9%	69.7%
Percent Non-Volatile	46.0%	30.2%
VOC Content	LB/Gal	g/L
Total	4.52	542
Less exempt solvents	4.53	543
Of solids	15.01	1799
Of solids	1.17 lb/lb	1.17 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	F75WC1	
	By wt	By vol
Total Volatiles	54.0%	69.8%
VOC Content	LB/Gal	g/L
Total	4.52	542

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	F75WC1	
	By wt	By vol
Total Volatiles	54.0%	69.8%
VOC Content	LB/Gal	g/L
Total	4.52	542

**Volatile Organic Compounds - Mexico**

	F75WC1	
	LB/Gal	g/L
Coating Density	8.39	1005
	By wt	By vol
Total Volatiles	54.0%	69.8%
Exempt solvents		
Water	0.1%	0.1%
Organic Volatiles	53.9%	69.7%
Percent Non-Volatile	46.0%	30.2%
VOC Content	LB/Gal	g/L
Total	4.52	542
Less exempt solvents	4.53	543
Of solids	15.01	1799
Of solids	1.17 lb/lb	1.17 kg/kg

**Hazardous Air Pollutants (Clean Air Act, Section 112(b))**

	F75WC1	
	LB/Gal	kg/L
Volatile HAPS	0.72	0.086
Of solids	2.39	0.287
Of solids	0.18 lb/lb	0.18 kg/kg

**Air Quality Data****Density of Organic Solvent Blend**

6.49 lb/gal

**Photochemically Reactive**

Yes

**Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.