### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Jan 19, 2024

### **PRODUCT NUMBER**

F77Y15

### **PRODUCT NAME**

Quick Dry Enamel, Safety Yellow

#### **MANUFACTURER'S NAME**

30 00 [3263]

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

F77Y15 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.89 lb/gal0.9535 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	11	13
Toluene 108-88-3	N	Υ	Υ	Υ	18	19
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	4	5
Xylene 1330-20-7	N	Υ	Υ	Υ	25	28
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	2	2
Cumene 98-82-8	N	Υ	Υ	Υ	0.1	< 1
Trimethylbenzene 25551-13-7	N	N	N	N	1	1
Naphthalene 91-20-3	N	Υ	Υ	Υ	0.1	< 1

# Volatile Organic Compounds - U.S. EPA / Canada

	F77Y15	
	LB/Gal	g/L
Coating Density	7.89	945
	By wt	By vol
Total Volatiles	64.8%	72.8%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	64.8%	72.7%
Percent Non-Volatile	35.2%	27.2%
VOC Content	LB/Gal	g/L
Total	5.11	612
Less exempt solvents	5.11	612
Of solids	18.76	2248
Of solids	1.84 lb/lb	1.84 kg/kg
	By wt	
By wt LVP-VOC	64.0%	_

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 3.41

### **Volatile Organic Compounds - California**

	F77Y15		
	LB/Gal	g/L	
Coating Density	7.89	945	
	By wt	By vol	
Total Volatiles	64.8%	72.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	64.8%	72.7%	
Percent Non-Volatile	35.2%	27.2%	
VOC Content	LB/Gal	g/L	
Total	5.11	612	
Less exempt solvents	5.11	612	
Of solids	18.76	2248	
Of solids	1.84 lb/lb	1.84 kg/kg	
	By wt		
By wt LVP-VOC	64.0%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 3.36

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F77Y15	
	LB/Gal	g/L
Coating Density	7.89	945
	By wt	By vol
Total Volatiles	64.8%	72.8%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	64.8%	72.7%
Percent Non-Volatile	35.2%	27.2%
VOC Content	LB/Gal	g/L
Total	5.11	612
Less exempt solvents	5.11	612
Of solids	18.76	2248
Of solids	1.84 lb/lb	1.84 kg/kg

## Volatile Organic Compounds - EU Directive 2004/42/EC

	F77Y15	
	By wt	By vol
Total Volatiles	64.8%	72.8%
VOC Content	LB/Gal	g/L
Total	5.11	612

# Volatile Organic Compounds - EU Directive 2010/75/EU

	F77Y15	
	By wt	By vol
Total Volatiles	64.8%	72.8%
VOC Content	LB/Gal	g/L
Total	5.11	612

# **Volatile Organic Compounds - Mexico**

	F77Y15		
	LB/Gal	g/L	
Coating Density	7.89	945	
	By wt	By vol	
Total Volatiles	64.8%	72.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	64.8%	72.7%	
Percent Non-Volatile	35.2%	27.2%	
VOC Content	LB/Gal	g/L	
Total	5.11	612	
Less exempt solvents	5.11	612	
Of solids	18.76	2248	
Of solids	1.84 lb/lb	1.84 kg/kg	

# Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F77Y15	
	LB/Gal	kg/L
Volatile HAPS	3.75	0.449
Of solids	13.78	1.652
Of solids	1.35 lb/lb	1.35 kg/kg

### **Air Quality Data**

**Density of Organic Solvent Blend** 

7.03 lb/gal

**Photochemically Reactive** 

Yes

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.