### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Jan 19, 2024

# PRODUCT NUMBER

18 00 [1983]

F78B21

### **PRODUCT NAME**

Fast Dry Acrylic Enamel, Gloss Black

#### **MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

F78B21 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.89 lb/gal0.9545 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Toluene 108-88-3	N	Υ	Υ	Υ	13	14
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	7	8
Xylene 1330-20-7	N	Υ	Υ	Υ	38	42
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	2	2

#### **Regulated Compounds**

	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
Cobalt Compound	N	N	Υ	Υ	0.1	

# Volatile Organic Compounds - U.S. EPA / Canada

	F78B21		
	LB/Gal	g/L	
Coating Density	7.89	945	
	By wt	By vol	
Total Volatiles	60.8%	66.8%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	60.8%	66.8%	
Percent Non-Volatile	39.2%	33.2%	
VOC Content	LB/Gal	g/L	
Total	4.79	574	
Less exempt solvents	4.79	574	
Of solids	14.46	1733	
Of solids	1.55 lb/lb	1.55 kg/kg	
	By wt		
By wt LVP-VOC	60.8%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 3.73

## **Volatile Organic Compounds - California**

	F78B21		
	LB/Gal	g/L	
Coating Density	7.89	945	
	By wt	By vol	
Total Volatiles	60.8%	66.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	60.8%	66.8%	
Percent Non-Volatile	39.2%	33.2%	
VOC Content	LB/Gal	g/L	
Total	4.79	574	
Less exempt solvents	4.79	574	
Of solids	14.46	1733	
Of solids	1.55 lb/lb	1.55 kg/kg	
	By wt		
By wt LVP-VOC	60.8%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 3.69

# Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F78B21		
	LB/Gal	g/L	
Coating Density	7.89	945	
	By wt	By vol	
Total Volatiles	60.8%	66.8%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	60.8%	66.8%	
Percent Non-Volatile	39.2%	33.2%	
VOC Content	LB/Gal	g/L	
Total	4.79	574	
Less exempt solvents	4.79	574	
Of solids	14.46	1733	
Of solids	1.55 lb/lb	1.55 kg/kg	

## Volatile Organic Compounds - EU Directive 2004/42/EC

	F78B21		
	By wt	By vol	
Total Volatiles	60.8%	66.8%	
VOC Content	LB/Gal	g/L	
Total	4.79	574	

# Volatile Organic Compounds - EU Directive 2010/75/EU

	F78B21		
	By wt	By vol	
Total Volatiles	60.8%	66.8%	
VOC Content	LB/Gal	g/L	
Total	4.79	574	

# **Volatile Organic Compounds - Mexico**

F78B21		
LB/Gal	g/L	
7.89	945	
By wt	By vol	
60.8%	66.8%	
0.0%	0.0%	
60.8%	66.8%	
39.2%	33.2%	
LB/Gal	g/L	
4.79	574	
4.79	574	
14.46	1733	
1.55 lb/lb	1.55 kg/kg	
	LB/Gal 7.89  By wt 60.8%  0.0% 60.8% 39.2%  LB/Gal 4.79 4.79 14.46	

## Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F78B21		
	LB/Gal	kg/L	
Volatile HAPS	4.55	0.546	
Of solids	13.74	1.646	
Of solids	1.47 lb/lb	1.47 kg/kg	

## **Air Quality Data**

**Density of Organic Solvent Blend** 

7.18 lb/gal

**Photochemically Reactive** 

Yes

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.