

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Nov 6, 2023

18 00 [1963]

## PRODUCT NUMBER

F85W32

## PRODUCT NAME

KEM® Fast Dry High Solids Enamel, White

## MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

F85W32 = | Acute | Chronic | Fire |

## Product Weight

10.13 lb/gal

## Specific Gravity

1.22

## FLASH POINT

10 °F PMCC

## Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Y	Y	Y	1	2
Xylene 1330-20-7	N	Y	Y	Y	7	10
Acetone 67-64-1	N	Y	N	N	2	3
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	22	33

## Volatile Organic Compounds - U.S. EPA / Canada

	F85W32	
	LB/Gal	g/L
Coating Density	10.13	1213
	By wt	By vol
Total Volatiles	33.7%	49.7%
Federally exempt solvents		
Water	0.3%	0.4%
Acetone	2.0%	3.1%
Organic Volatiles	31.3%	46.2%
Percent Non-Volatile	66.3%	50.3%
VOC Content	LB/Gal	g/L
Total	3.17	380
Less exempt solvents	3.28	393
Of solids	6.30	755
Of solids	0.47 lb/lb	0.47 kg/kg
	By wt	
By wt LVP-VOC	31.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.24

**Volatile Organic Compounds - California**

	F85W32	
	LB/Gal	g/L
Coating Density	10.13	1213
	By wt	By vol
Total Volatiles	33.7%	49.7%
Exempt solvents		
Water	0.3%	0.4%
Acetone	2.0%	3.1%
Organic Volatiles	31.3%	46.2%
Percent Non-Volatile	66.3%	50.3%
VOC Content	LB/Gal	g/L
Total	3.17	380
Less exempt solvents	3.28	393
Of solids	6.30	755
Of solids	0.47 lb/lb	0.47 kg/kg
	By wt	
By wt LVP-VOC	31.3%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.11

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	F85W32	
	LB/Gal	g/L
Coating Density	10.13	1213
	By wt	By vol
Total Volatiles	33.7%	49.7%
Exempt solvents		
Water	0.3%	0.4%
Acetone	2.0%	3.1%
Organic Volatiles	31.3%	46.2%
Percent Non-Volatile	66.3%	50.3%
VOC Content	LB/Gal	g/L
Total	3.17	380
Less exempt solvents	3.28	393
Of solids	6.30	755
Of solids	0.47 lb/lb	0.47 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	F85W32	
	By wt	By vol
Total Volatiles	33.7%	49.8%
VOC Content	LB/Gal	g/L
Total	3.37	404

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	F85W32	
	By wt	By vol
Total Volatiles	33.7%	49.7%
VOC Content	LB/Gal	g/L
Total	3.37	404

### Volatile Organic Compounds - Mexico

	F85W32	
	LB/Gal	g/L
Coating Density	10.13	1213
	By wt	By vol
Total Volatiles	33.7%	49.7%
Exempt solvents		
Water	0.3%	0.4%
Acetone	2.0%	3.1%
Organic Volatiles	31.3%	46.2%
Percent Non-Volatile	66.3%	50.3%
VOC Content	LB/Gal	g/L
Total	3.17	380
Less exempt solvents	3.28	393
Of solids	6.30	755
Of solids	0.47 lb/lb	0.47 kg/kg

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F85W32	
	LB/Gal	kg/L
Volatile HAPS	0.84	0.101
Of solids	1.68	0.202
Of solids	0.12 lb/lb	0.12 kg/kg

### Air Quality Data

#### Density of Organic Solvent Blend

6.85 lb/gal

#### Photochemically Reactive

Yes

### Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.