

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

07 00 [3422]

PRODUCT NUMBER

F88W160

PRODUCT NAME

KEM ACRYL® HS 100 Enamel, Gloss White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F88W160 = | Acute | Chronic | Fire |

Product Weight

11.29 lb/gal

Specific Gravity

1.36

FLASH POINT

103 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Styrene 100-42-5	N	Y	Y	Y	2	3
Ethylbenzene 100-41-4	N	Y	Y	Y	0.1	0.2
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	6	9
Cumene 98-82-8	N	Y	Y	Y	0.4	0.6
1,3,5-Trimethylbenzene 108-67-8	N	N	N	N	1	2
1,2,4-Trimethylbenzene 95-63-6	N	N	Y	N	1	2
Trimethylbenzene 25551-13-7	N	N	N	N	3	5
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	12	21

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lead (as Pb)	N	N	Y	N	0.000003	

Volatile Organic Compounds - U.S. EPA / Canada

	F88W160	
	LB/Gal	g/L
Coating Density	11.29	1352
	By wt	By vol
Total Volatiles	28.9%	46.4%
Federally exempt solvents		
Water	0.3%	0.4%
Organic Volatiles	28.7%	46.1%
Percent Non-Volatile	71.1%	53.6%
VOC Content	LB/Gal	g/L
Total	3.23	387
Less exempt solvents	3.24	389
Of solids	6.03	723
Of solids	0.40 lb/lb	0.40 kg/kg
	By wt	
By wt LVP-VOC	28.5%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.51**

Volatile Organic Compounds - California

	F88W160	
	LB/Gal	g/L
Coating Density	11.29	1352
	By wt	By vol
Total Volatiles	28.9%	46.4%
Exempt solvents		
Water	0.3%	0.4%
Organic Volatiles	28.7%	46.1%
Percent Non-Volatile	71.1%	53.6%
VOC Content	LB/Gal	g/L
Total	3.23	387
Less exempt solvents	3.24	389
Of solids	6.03	723
Of solids	0.40 lb/lb	0.40 kg/kg
	By wt	
By wt LVP-VOC	28.5%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.41**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F88W160	
	LB/Gal	g/L
Coating Density	11.29	1352
	By wt	By vol
Total Volatiles	28.9%	46.4%
Exempt solvents		
Water	0.3%	0.4%
Organic Volatiles	28.7%	46.1%
Percent Non-Volatile	71.1%	53.6%
VOC Content	LB/Gal	g/L
Total	3.23	387
Less exempt solvents	3.24	389
Of solids	6.03	723
Of solids	0.40 lb/lb	0.40 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	F88W160	
	By wt	By vol
Total Volatiles	28.9%	46.4%
VOC Content	LB/Gal	g/L
Total	3.23	387

Volatile Organic Compounds - EU Directive 2010/75/EU

	F88W160	
	By wt	By vol
Total Volatiles	28.8%	46.2%
VOC Content	LB/Gal	g/L
Total	3.21	385

Volatile Organic Compounds - Mexico

	F88W160	
	LB/Gal	g/L
Coating Density	11.29	1352
	By wt	By vol
Total Volatiles	28.9%	46.4%
Exempt solvents		
Water	0.3%	0.4%
Organic Volatiles	28.7%	46.1%
Percent Non-Volatile	71.1%	53.6%
VOC Content	LB/Gal	g/L
Total	3.23	387
Less exempt solvents	3.24	389
Of solids	6.04	723
Of solids	0.40 lb/lb	0.40 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F88W160	
	LB/Gal	kg/L
Volatile HAPS	0.26	0.031
Of solids	0.49	0.058
Of solids	0.03 lb/lb	0.03 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

7.02 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.