ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 19, 2024

PRODUCT NUMBER

08 00 [1491]

F93BL350

PRODUCT NAME

MIL-DTL-11195H Type II Fast Dry Lusterless Enamel 3.5 VOC Black 37038 Q2059

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS CO. 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

F93BL350 = | Acute | Chronic | Fire |

 Product Weight
 Specific Gravity
 FLASH POINT

 10.99 lb/gal
 1.32
 102 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.2	0.3
Methyl n-Propyl Ketone 107-87-9	N	N	N	N	6	11
Methyl Isobutyl Ketone 108-10-1	N	Υ	Υ	Υ	1	2
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	16	26
n-Butyl Acetate 123-86-4	N	Υ	N	N	1	2

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Zinc (as Zn)	N	Υ	Υ	N	3	
Mercury (as Hg)	N	N	Υ	N	0.000008	
Lead (as Pb)	N	N	Υ	N	0.0002	
Zinc Compound	N	N	Υ	N	7	

Volatile Organic Compounds - U.S. EPA / Canada

	F93BL350		
	LB/Gal	g/L	
Coating Density	10.99	1317	
	By wt	By vol	
Total Volatiles	26.6%	43.2%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	26.6%	43.2%	
Percent Non-Volatile	73.4%	56.8%	
VOC Content	LB/Gal	g/L	
Total	2.92	350	
Less exempt solvents	2.92	350	
Of solids	5.15	617	
Of solids	0.36 lb/lb	0.36 kg/kg	
	By wt		
By wt LVP-VOC	26.6%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.79

Volatile Organic Compounds - California

	F93BL350		
	LB/Gal	g/L	
Coating Density	10.99	1317	
	By wt	By vol	
Total Volatiles	26.6%	43.2%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	26.6%	43.2%	
Percent Non-Volatile	73.4%	56.8%	
VOC Content	LB/Gal	g/L	
Total	2.92	350	
Less exempt solvents	2.92	350	
Of solids	5.15	617	
Of solids	0.36 lb/lb	0.36 kg/kg	
	By wt		
By wt LVP-VOC	26.6%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.70

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	F93BL350		
	LB/Gal	g/L	
Coating Density	10.99	1317	
	By wt	By vol	
Total Volatiles	26.6%	43.2%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	26.6%	43.2%	
Percent Non-Volatile	73.4%	56.8%	
VOC Content	LB/Gal	g/L	
Total	2.92	350	
Less exempt solvents	2.92	350	
Of solids	5.15	617	
Of solids	0.36 lb/lb	0.36 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	F93BL350		
	By wt	By vol	
Total Volatiles	26.7%	43.3%	
VOC Content	LB/Gal	g/L	
Total	2.93	351	

Volatile Organic Compounds - EU Directive 2010/75/EU

	F93E	3L350
	By wt	By vol
Total Volatiles	26.6%	43.2%
VOC Content	LB/Gal	g/L
Total	2.92	350

Volatile Organic Compounds - Mexico

F93BL350		
LB/Gal	g/L	
10.99	1317	
By wt	By vol	
26.6%	43.2%	
0.0%	0.0%	
26.6%	43.2%	
73.4%	56.8%	
LB/Gal	g/L	
2.92	350	
2.92	350	
5.15	617	
0.36 lb/lb	0.36 kg/kg	
	LB/Gal 10.99 By wt 26.6% 0.0% 26.6% 73.4% LB/Gal 2.92 2.92 5.15	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	F93BL350		
	LB/Gal	kg/L	
Volatile HAPS	0.15	0.018	
Of solids	0.26	0.031	
Of solids	0.01 lb/lb	0.01 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.78 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.