ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

PRODUCT NUMBER

29 00 [1983]

G74YC165

PRODUCT NAME

Fast Production Enamel, Equipment Yellow

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

G74YC165 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT8.06 lb/gal0.9745 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	35	45
Toluene 108-88-3	N	Υ	Υ	Υ	6	6
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.1	< 1
Xylene 1330-20-7	N	Υ	Υ	Υ	1	1
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	13	16

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Cobalt Compound	N	N	Υ	Υ	0.2	

Volatile Organic Compounds - U.S. EPA / Canada

	G74YC165		
	LB/Gal	g/L	
Coating Density	8.06	966	
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	57.1%	71.5%	
Percent Non-Volatile	42.9%	28.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	
Less exempt solvents	4.60	551	
Of solids	16.17	1938	
Of solids	1.33 lb/lb	1.33 kg/kg	
	By wt		
By wt LVP-VOC	56.6%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.25

Volatile Organic Compounds - California

	G74YC165		
	LB/Gal	g/L	
Coating Density	8.06	966	
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	57.1%	71.5%	
Percent Non-Volatile	42.9%	28.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	
Less exempt solvents	4.60	551	
Of solids	16.17	1938	
Of solids	1.33 lb/lb	1.33 kg/kg	
	By wt		
By wt LVP-VOC	56.6%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.16

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	G74YC165		
	LB/Gal	g/L	
Coating Density	8.06	966	
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	57.1%	71.5%	
Percent Non-Volatile	42.9%	28.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	
Less exempt solvents	4.60	551	
Of solids	16.17	1938	
Of solids	1.33 lb/lb	1.33 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	G74YC165		
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	

Volatile Organic Compounds - EU Directive 2010/75/EU

	G74YC165		
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	

Volatile Organic Compounds - Mexico

	G74YC165		
	LB/Gal	g/L	
Coating Density	8.06	966	
	By wt	By vol	
Total Volatiles	57.1%	71.5%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	57.1%	71.5%	
Percent Non-Volatile	42.9%	28.5%	
VOC Content	LB/Gal	g/L	
Total	4.60	551	
Less exempt solvents	4.60	551	
Of solids	16.17	1938	
Of solids	1.33 lb/lb	1.33 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	G74YC165		
	LB/Gal	kg/L	
Volatile HAPS	0.55	0.066	
Of solids	1.95	0.234	
Of solids	0.16 lb/lb	0.16 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.43 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.