ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

11 00 [2513]

PRODUCT NUMBER

H66W41

PRODUCT NAME

SHER-WOOD® HB Pigmented Conversion Varnish, Mid Gloss White Tint Base

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

H66W41 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT11.12 lb/gal1.3455 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.7	1
Xylene 1330-20-7	N	Υ	Υ	Υ	4	6
Ethanol 64-17-5	N	N	N	N	7	14
1-Butanol 71-36-3	N	Υ	Υ	N	2	3
Ethyl 3-Ethoxypropionate 763-69-9	N	N	N	N	2	2
n-Butyl Acetate 123-86-4	N	Υ	N	N	5	8

Volatile Organic Compounds - U.S. EPA / Canada

	H66W41		
	LB/Gal	g/L	
Coating Density	11.12	1332	
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
Federally exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	22.2%	36.9%	
Percent Non-Volatile	77.7%	63.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	
Less exempt solvents	2.47	296	
Of solids	3.92	469	
Of solids	0.28 lb/lb	0.28 kg/kg	
	By wt		
By wt LVP-VOC	22.2%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.64

Volatile Organic Compounds - California

	H66W41		
	LB/Gal	g/L	
Coating Density	11.12	1332	
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	22.2%	36.9%	
Percent Non-Volatile	77.7%	63.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	
Less exempt solvents	2.47	296	
Of solids	3.92	469	
Of solids	0.28 lb/lb	0.28 kg/kg	
	By wt		
By wt LVP-VOC	22.2%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.62

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	H66W41		
	LB/Gal	g/L	
Coating Density	11.12	1332	
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	22.2%	36.9%	
Percent Non-Volatile	77.7%	63.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	
Less exempt solvents	2.47	296	
Of solids	3.92	469	
Of solids	0.28 lb/lb	0.28 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	H66W41		
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	

Volatile Organic Compounds - EU Directive 2010/75/EU

	H66W41		
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	

Volatile Organic Compounds - Mexico

	H66W41		
	LB/Gal	g/L	
Coating Density	11.12	1332	
	By wt	By vol	
Total Volatiles	22.3%	37.0%	
Exempt solvents			
Water	0.1%	0.1%	
Organic Volatiles	22.2%	36.9%	
Percent Non-Volatile	77.7%	63.0%	
VOC Content	LB/Gal	g/L	
Total	2.47	296	
Less exempt solvents	2.47	296	
Of solids	3.92	469	
Of solids	0.28 lb/lb	0.28 ka/ka	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	H66W41		
	LB/Gal	kg/L	
Volatile HAPS	0.53	0.064	
Of solids	0.85	0.102	
Of solids	0.06 lb/lb	0.06 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.70 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.