ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

29 00 [1983]

PRODUCT NUMBER

M60B17

PRODUCT NAME

OPEX® Black Lacquer, Satin Black

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

M60B17 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.37 lb/gal0.8935 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	13	15
Toluene 108-88-3	N	Υ	Υ	Υ	14	14
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.1	< 1
2-Propanol 67-63-0	N	N	N	N	11	13
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	8	9
2-Butoxyethanol 111-76-2	N	N	Y - Glycol Ethers (SARA)	N	3	3
Methyl Ethyl Ketone 78-93-3	N	Υ	N	N	7	8
Isobutyl Acetate 110-19-0	N	Υ	N	N	19	19

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Glycol Ethers (SARA)	N	N	Υ	N	3	

Volatile Organic Compounds - U.S. EPA / Canada

	M60B17	
	LB/Gal	g/L
Coating Density	7.37	882
	By wt	By vol
Total Volatiles	77.1%	83.3%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	77.1%	83.3%
Percent Non-Volatile	22.9%	16.7%
VOC Content	LB/Gal	g/L
Total	5.67	680
Less exempt solvents	5.67	680
Of solids	33.94	4067
Of solids	3.35 lb/lb	3.35 kg/kg
	By wt	
By wt LVP-VOC	77.0%	_

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.36

Volatile Organic Compounds - California

	Me	60B17
	LB/Gal	g/L
Coating Density	7.37	882
	By wt	By vol
Total Volatiles	77.1%	83.3%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	77.1%	83.3%
Percent Non-Volatile	22.9%	16.7%
VOC Content	LB/Gal	g/L
Total	5.67	680
Less exempt solvents	5.67	680
Of solids	33.94	4067
Of solids	3.35 lb/lb	3.35 kg/kg
	By wt	
By wt LVP-VOC	77.0%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.37

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	Me	60B17
	LB/Gal	g/L
Coating Density	7.37	882
	By wt	By vol
Total Volatiles	77.1%	83.3%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	77.1%	83.3%
Percent Non-Volatile	22.9%	16.7%
VOC Content	LB/Gal	g/L
Total	5.67	680
Less exempt solvents	5.67	680
Of solids	33.94	4067
Of solids	3.35 lb/lb	3.35 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	M60B17		
	By wt	By vol	
Total Volatiles	77.1%	83.3%	
VOC Content	LB/Gal	g/L	
Total	5.67	680	

Volatile Organic Compounds - EU Directive 2010/75/EU

	M60B17		
	By wt	By vol	
Total Volatiles	77.1%	83.3%	
VOC Content	LB/Gal	g/L	
Total	5.67	680	

Volatile Organic Compounds - Mexico

Me	60B17
LB/Gal	g/L
7.37	882
By wt	By vol
77.1%	83.3%
0.0%	0.0%
77.1%	83.3%
22.9%	16.7%
LB/Gal	g/L
5.67	680
5.67	680
33.94	4067
3.35 lb/lb	3.35 kg/kg
	LB/Gal 7.37 By wt 77.1% 0.0% 77.1% 22.9% LB/Gal 5.67 5.67 33.94

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	M60B17		
	LB/Gal	kg/L	
Volatile HAPS	1.02	0.122	
Of solids	6.11	0.732	
Of solids	0.60 lb/lb	0.60 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.82 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.