### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Mar 25, 2024

21 00 [2513]

## **PRODUCT NUMBER**

M64GL541

#### **PRODUCT NAME**

KEM AQUA® BP Enamel, Phthalo Green

## **MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

### Hazard Category (for SARA 311.312)

M64GL541 = | Acute | Chronic |

Product WeightSpecific GravityFLASH POINT8.75 lb/gal1.05N.A.

### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
2-Butoxyethanol 111-76-2	N	N	Y - Glycol Ethers (SARA)	N	2	2
Water 7732-18-5	N	N	N	N	62	66

#### **Regulated Compounds**

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Glycol Ethers (SARA)	N	Ν	Υ	Ν	3	

## Volatile Organic Compounds - U.S. EPA / Canada

	M64	M64GL541	
	LB/Gal	g/L	
Coating Density	8.75	1048	
	By wt	By vol	
Total Volatiles	66.0%	70.5%	
Federally exempt solvents			
Water	62.2%	66.1%	
2-Amino-2-Methyl-1- Propanol	0.2%	0.2%	
Organic Volatiles	3.6%	4.2%	
Percent Non-Volatile	34.0%	29.5%	
VOC Content	LB/Gal	g/L	
Total	0.31	37	
Less exempt solvents	0.93	112	
Of solids	1.07	128	
Of solids	0.10 lb/lb	0.10 kg/kg	
	By wt		
By wt LVP-VOC	2.3%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.14

# **Volatile Organic Compounds - California**

	M64GL541		
	LB/Gal	g/L	
Coating Density	8.75	1048	
	By wt	By vol	
Total Volatiles	66.0%	70.5%	
Exempt solvents			
Water	62.2%	66.1%	
Organic Volatiles	3.8%	4.4%	
Percent Non-Volatile	34.0%	29.5%	
VOC Content	LB/Gal	g/L	
Total	0.33	39	
Less exempt solvents	0.98	117	
Of solids	1.13	135	
Of solids	0.11 lb/lb	0.11 kg/kg	
	By wt		
By wt LVP-VOC	2.5%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.09

## Volatile Organic Compounds - South Coast Air Quality Management District, California, US

·			
	M64GL541		
	LB/Gal	g/L	
Coating Density	8.75	1048	
	By wt	By vol	
Total Volatiles	66.0%	70.5%	
Exempt solvents			
Water	62.2%	66.1%	
Organic Volatiles	3.8%	4.4%	
Percent Non-Volatile	34.0%	29.5%	
VOC Content	LB/Gal	g/L	
Total	0.33	39	
Less exempt solvents	0.98	117	
Of solids	1.13	135	
Of solids	0.11 lb/lb	0.11 kg/kg	

# Volatile Organic Compounds - EU Directive 2004/42/EC

	M64GL541		
	By wt	By vol	
Total Volatiles	66.1%	70.6%	
VOC Content	LB/Gal	g/L	
Total	0.33	40	

## Volatile Organic Compounds - EU Directive 2010/75/EU

	M64GL541	
	By wt	By vol
Total Volatiles	64.7%	69.0%
VOC Content	LB/Gal	g/L
Total	0.21	25

## **Volatile Organic Compounds - Mexico**

	M64GL541		
	LB/Gal	g/L	
Coating Density	8.75	1048	
	By wt	By vol	
Total Volatiles	66.0%	70.5%	
Exempt solvents			
Water	62.2%	66.1%	
Organic Volatiles	3.8%	4.4%	
Percent Non-Volatile	34.0%	29.5%	
VOC Content	LB/Gal	g/L	
Total	0.33	39	
Less exempt solvents	0.98	117	
Of solids	1.13	135	
Of solids	0.11 lb/lb	0.11 kg/kg	

# Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	M64GL541		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

## **Air Quality Data**

**Density of Organic Solvent Blend** 

7.59 lb/gal

**Photochemically Reactive** 

No

## **Waste Disposal**

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.