ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

13 00 [2513]

PRODUCT NUMBER

P63G3

PRODUCT NAME

SHER-WOOD® Vinyl Basecoat, Mono Green

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

P63G3 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.32 lb/gal0.8822 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	11	13
Ethanol 64-17-5	N	N	N	N	8	9
Methyl Ethyl Ketone 78-93-3	N	Υ	N	N	6	7
Methyl n-Propyl Ketone 107-87-9	N	N	N	N	20	21
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	5	5
Isobutyl Acetate 110-19-0	N	Υ	N	N	34	35

Volatile Organic Compounds - U.S. EPA / Canada

	P63G3		
	LB/Gal	g/L	
Coating Density	7.32	877	
	By wt	By vol	
Total Volatiles	85.9%	92.0%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	85.9%	92.0%	
Percent Non-Volatile	14.1%	8.0%	
VOC Content	LB/Gal	g/L	
Total	6.28	753	
Less exempt solvents	6.28	753	
Of solids	78.94	9459	
Of solids	6.10 lb/lb	6.10 kg/kg	
	By wt		
By wt LVP-VOC	85.9%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.38

Volatile Organic Compounds - California

	P63G3		
	LB/Gal	g/L	
Coating Density	7.32	877	
	By wt	By vol	
Total Volatiles	85.9%	92.0%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	85.9%	92.0%	
Percent Non-Volatile	14.1%	8.0%	
VOC Content	LB/Gal	g/L	
Total	6.28	753	
Less exempt solvents	6.28	753	
Of solids	78.94	9459	
Of solids	6.10 lb/lb	6.10 kg/kg	
	By wt		
By wt LVP-VOC	85.9%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.28

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	P63G3		
	LB/Gal	g/L	
Coating Density	7.32	877	
	By wt	By vol	
Total Volatiles	85.9%	92.0%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	85.9%	92.0%	
Percent Non-Volatile	14.1%	8.0%	
VOC Content	LB/Gal	g/L	
Total	6.28	753	
Less exempt solvents	6.28	753	
Of solids	78.94	9459	
Of solids	6.10 lb/lb	6.10 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	P63G3		
	By wt	By vol	
Total Volatiles	85.9%	92.0%	
VOC Content	LB/Gal	g/L	
Total	6.28	753	

Volatile Organic Compounds - EU Directive 2010/75/EU

	P63G3		
	By wt	By vol	
Total Volatiles	85.9%	92.0%	
VOC Content	LB/Gal	g/L	
Total	6.28	753	

Volatile Organic Compounds - Mexico

P63G3		
LB/Gal	g/L	
7.32	877	
By wt	By vol	
85.9%	92.0%	
0.0%	0.0%	
85.9%	92.0%	
14.1%	8.0%	
LB/Gal	g/L	
6.28	753	
6.28	753	
78.94	9459	
6.10 lb/lb	6.10 kg/kg	
	LB/Gal 7.32 By wt 85.9% 0.0% 85.9% 14.1% LB/Gal 6.28 6.28 78.94	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	P63G3		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.83 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.