

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Apr 19, 2024

30 00 [2513]

PRODUCT NUMBER

P63W9

PRODUCT NAME

SHER-WOOD® Vinyl Basecoat, Mono White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

P63W9 = | Acute | Chronic | Fire |

Product Weight

8.64 lb/gal

Specific Gravity

1.04

FLASH POINT

22 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	8	11
Toluene 108-88-3	N	Y	Y	Y	4	5
Ethylbenzene 100-41-4	N	Y	Y	Y	0.5	0.5
Xylene 1330-20-7	N	Y	Y	Y	3	3
Ethanol 64-17-5	N	N	N	N	7	9
2-Methyl-1-propanol 78-83-1	N	Y	N	N	2	2
Methyl Ethyl Ketone 78-93-3	N	Y	N	N	15	19
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	4	5
Isobutyl Acetate 110-19-0	N	Y	N	N	21	26

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Y	N	0.000006	
Lead (as Pb)	N	N	Y	N	0.00002	

Volatile Organic Compounds - U.S. EPA / Canada

	P63W9	
	LB/Gal	g/L
Coating Density	8.64	1035
	By wt	By vol
Total Volatiles	65.3%	82.4%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	65.3%	82.4%
Percent Non-Volatile	34.7%	17.6%
VOC Content	LB/Gal	g/L
Total	5.64	676
Less exempt solvents	5.64	676
Of solids	31.98	3833
Of solids	1.88 lb/lb	1.88 kg/kg
	By wt	
By wt LVP-VOC	65.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.11**

Volatile Organic Compounds - California

	P63W9	
	LB/Gal	g/L
Coating Density	8.64	1035
	By wt	By vol
Total Volatiles	65.3%	82.4%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	65.3%	82.4%
Percent Non-Volatile	34.7%	17.6%
VOC Content	LB/Gal	g/L
Total	5.64	676
Less exempt solvents	5.64	676
Of solids	31.98	3833
Of solids	1.88 lb/lb	1.88 kg/kg
	By wt	
By wt LVP-VOC	65.3%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.07**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	P63W9	
	LB/Gal	g/L
Coating Density	8.64	1035
	By wt	By vol
Total Volatiles	65.3%	82.4%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	65.3%	82.4%
Percent Non-Volatile	34.7%	17.6%
VOC Content	LB/Gal	g/L
Total	5.64	676
Less exempt solvents	5.64	676
Of solids	31.98	3833
Of solids	1.88 lb/lb	1.88 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	P63W9	
	By wt	By vol
Total Volatiles	65.3%	82.4%
VOC Content	LB/Gal	g/L
Total	5.64	676

Volatile Organic Compounds - EU Directive 2010/75/EU

	P63W9	
	By wt	By vol
Total Volatiles	65.3%	82.4%
VOC Content	LB/Gal	g/L
Total	5.64	676

Volatile Organic Compounds - Mexico

	P63W9	
	LB/Gal	g/L
Coating Density	8.64	1035
	By wt	By vol
Total Volatiles	65.3%	82.4%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	65.3%	82.4%
Percent Non-Volatile	34.7%	17.6%
VOC Content	LB/Gal	g/L
Total	5.64	676
Less exempt solvents	5.64	676
Of solids	31.98	3833
Of solids	1.88 lb/lb	1.88 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	P63W9	
	LB/Gal	kg/L
Volatile HAPS	0.63	0.075
Of solids	3.58	0.429
Of solids	0.21 lb/lb	0.21 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

6.85 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.