ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

PRODUCT NUMBER

S64T72

PRODUCT NAME

SHER-WOOD® SB Stain Clear Base

MANUFACTURER'S NAME

07 00 [2523]

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

S64T72 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.06 lb/gal0.854 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	4	5
Mineral Spirits 140-Flash 64742-88-7	N	N	N	N	2	2
p-Chlorobenzotrifluoride 98-56-6	N	N	N	N	4	3
Acetone 67-64-1	N	Υ	N	N	65	69
Ethyl 3-Ethoxypropionate 763-69-9	N	N	N	N	1	1

Volatile Organic Compounds - U.S. EPA / Canada

	S64T72	
	LB/Gal	g/L
Coating Density	7.06	846
	By wt	By vol
Total Volatiles	77.9%	81.5%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	64.6%	69.2%
P-Chlorobenzotrifluoride	4.2%	2.7%
Organic Volatiles	9.1%	9.7%
Percent Non-Volatile	22.1%	18.5%
VOC Content	LB/Gal	g/L
Total	0.64	76
Less exempt solvents	2.28	273
Of solids	3.47	416
Of solids	0.41 lb/lb	0.41 kg/kg
	By wt	
By wt LVP-VOC	9.1%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.40

Volatile Organic Compounds - California

	S64T72	
	LB/Gal	g/L
Coating Density	7.06	846
	By wt	By vol
Total Volatiles	77.9%	81.5%
Exempt solvents		
Water	0.0%	0.0%
Acetone	64.6%	69.2%
P-Chlorobenzotrifluoride	4.2%	2.7%
Organic Volatiles	9.1%	9.7%
Percent Non-Volatile	22.1%	18.5%
VOC Content	LB/Gal	g/L
Total	0.64	76
Less exempt solvents	2.28	273
Of solids	3.47	416
Of solids	0.41 lb/lb	0.41 kg/kg
	By wt	
By wt LVP-VOC	9.1%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.36

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	S64T72	
	LB/Gal	g/L
Coating Density	7.06	846
	By wt	By vol
Total Volatiles	77.9%	81.5%
Exempt solvents		
Water	0.0%	0.0%
Acetone	64.6%	69.2%
P-Chlorobenzotrifluoride	4.2%	2.7%
Organic Volatiles	9.1%	9.7%
Percent Non-Volatile	22.1%	18.5%
VOC Content	LB/Gal	g/L
Total	0.64	76
Less exempt solvents	2.28	273
Of solids	3.47	416
Of solids	0.41 lb/lb	0.41 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	S64T72	
	By wt	By vol
Total Volatiles	77.9%	81.5%
VOC Content	LB/Gal	g/L
Total	5.50	659

Volatile Organic Compounds - EU Directive 2010/75/EU

	S64T72		
	By wt	By vol	
Total Volatiles	77.9%	81.5%	
VOC Content	LB/Gal	g/L	
Total	5.50	659	

Volatile Organic Compounds - Mexico

	S64T72		
	LB/Gal	g/L	
Coating Density	7.06	846	
	By wt	By vol	
Total Volatiles	77.9%	81.5%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	64.6%	69.2%	
Organic Volatiles	13.3%	12.3%	
Percent Non-Volatile	22.1%	18.5%	
VOC Content	LB/Gal	g/L	
Total	0.94	112	
Less exempt solvents	3.05	366	
Of solids	5.09	610	
Of solids	0.60 lb/lb	0.60 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	S64T72		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.75 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.