ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

10 00 [2513]

PRODUCT NUMBER

S66T30

PRODUCT NAME

SHER-WOOD® KemVar® Glaze, Natural

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

S66T30 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.39 lb/gal0.8940 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	1	1
Mineral Spirits 140-Flash 64742-88-7	N	N	N	N	46	53
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.2	< 1
Xylene 1330-20-7	N	Υ	Υ	Υ	2	2
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	1	1
1-Butanol 71-36-3	N	Υ	Υ	N	7	7
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	2	2
2-Butoxyethanol 111-76-2	N	N	Y - Glycol Ethers (SARA)	N	4	4

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Glycol Ethers (SARA)	N	N	Υ	N	4	

Volatile Organic Compounds - U.S. EPA / Canada

	S66T30		
	LB/Gal	g/L	
Coating Density	7.39	885	
	By wt	By vol	
Total Volatiles	65.2%	72.6%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	65.2%	72.6%	
Percent Non-Volatile	34.8%	27.4%	
VOC Content	LB/Gal	g/L	
Total	4.81	576	
Less exempt solvents	4.81	576	
Of solids	17.55	2103	
Of solids	1.87 lb/lb	1.87 kg/kg	
	By wt		
By wt LVP-VOC	65.2%	_	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.06

Volatile Organic Compounds - California

	S66T30		
	LB/Gal	g/L	
Coating Density	7.39	885	
	By wt	By vol	
Total Volatiles	65.2%	72.6%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	65.2%	72.6%	
Percent Non-Volatile	34.8%	27.4%	
VOC Content	LB/Gal	g/L	
Total	4.81	576	
Less exempt solvents	4.81	576	
Of solids	17.55	2103	
Of solids	1.87 lb/lb	1.87 kg/kg	
	By wt		
By wt LVP-VOC	65.2%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.04

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	S66T30		
	LB/Gal	g/L	
Coating Density	7.39	885	
	By wt	By vol	
Total Volatiles	65.2%	72.6%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	65.2%	72.6%	
Percent Non-Volatile	34.8%	27.4%	
VOC Content	LB/Gal	g/L	
Total	4.81	576	
Less exempt solvents	4.81	576	
Of solids	17.55	2103	
Of solids	1.87 lb/lb	1.87 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	S66T30		
	By wt	By vol	
Total Volatiles	65.2%	72.6%	
VOC Content	LB/Gal	g/L	
Total	4.81	576	

Volatile Organic Compounds - EU Directive 2010/75/EU

	S66T30		
	By wt	By vol	
Total Volatiles	65.2%	72.6%	
VOC Content	LB/Gal	g/L	
Total	4.81	576	

Volatile Organic Compounds - Mexico

Se	6T30
LB/Gal	g/L
7.39	885
By wt	By vol
65.2%	72.6%
0.0%	0.0%
65.2%	72.6%
34.8%	27.4%
LB/Gal	g/L
4.81	576
4.81	576
17.55	2103
1.87 lb/lb	1.87 kg/kg
	LB/Gal 7.39 By wt 65.2% 0.0% 65.2% 34.8% LB/Gal 4.81 4.81 17.55

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	S66T30		
	LB/Gal	kg/L	
Volatile HAPS	0.13	0.015	
Of solids	0.48	0.057	
Of solids	0.05 lb/lb	0.05 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.63 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.