# **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

14 00 [2523]

Date of Preparation Jan 20, 2024

#### **PRODUCT NUMBER**

T60F64

#### **PRODUCT NAME**

SHER-WOOD® LOVOC Lacquer Sanding Sealer

#### MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

T60F64 = | Acute | Chronic | Fire |

Product Weight	Specific	c Gravity		FLASH PO	DINT	
7.30 lb/gal	0.88			4 °F PI	NCC	
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	6	7
Light Aliphatic Hydrocarbon 64742-47-8	N	N	N	N	3	3
Ethylbenzene 100-41-4	N	Y	Y	Y	0.7	< 1
Xylene 1330-20-7	N	Y	Υ	Y	4	4
Methanol 67-56-1	N	Y	Y	Y	3	3
2-Propanol 67-63-0	N	N	N	N	3	3
2-Methyl-1-propanol 78-83-1	N	Y	N	N	4	5
2-Butoxyethanol 111-76-2	N	N	Y - Glycol Ethers (SARA)	N	2	2
Acetone 67-64-1	N	Y	N	N	36	40
Methyl Isobutyl Ketone 108-10-1	N	Y	Y	Y	3	3
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	3	3
Isobutyl Isobutyrate 97-85-8	N	N	N	N	8	8

#### **Regulated Compounds**

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Glycol Ethers (SARA)	Ν	Ν	Y	Ν	2	

## Volatile Organic Compounds - U.S. EPA / Canada

	T60F64	
	LB/Gal	g/L
Coating Density	7.30	874
	By wt	By vol
Total Volatiles	75.1%	82.2%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	35.9%	39.8%
Organic Volatiles	39.2%	42.4%
Percent Non-Volatile	24.9%	17.8%
VOC Content	LB/Gal	g/L
Total	2.85	342
Less exempt solvents	4.75	569
Of solids	16.10	1929
Of solids	1.57 lb/lb	1.57 kg/kg
	By wt	
By wt LVP-VOC	38.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.04

## Volatile Organic Compounds - California

	T60F64		
	LB/Gal	g/L	
Coating Density	7.30	874	
	By wt	By vol	
Total Volatiles	75.1%	82.2%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	35.9%	39.8%	
Organic Volatiles	39.2%	42.4%	
Percent Non-Volatile	24.9%	17.8%	
VOC Content	LB/Gal	g/L	
Total	2.85	342	
Less exempt solvents	4.75	569	
Of solids	16.10	1929	
Of solids	1.57 lb/lb	1.57 kg/kg	
	By wt		
By wt LVP-VOC	38.9%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.00

## Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T60F64		
	LB/Gal	g/L	
Coating Density	7.30	874	
	By wt	By vol	
Total Volatiles	75.1%	82.2%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	35.9%	39.8%	
Organic Volatiles	39.2%	42.4%	
Percent Non-Volatile	24.9%	17.8%	
VOC Content	LB/Gal	g/L	
Total	2.85	342	
Less exempt solvents	4.75	569	
Of solids	16.10	1929	
Of solids	1.57 lb/lb	1.57 kg/kg	

# Volatile Organic Compounds - EU Directive 2004/42/EC

	T60F64		
	By wt	By vol	
<b>Total Volatiles</b>	75.1%	82.2%	
VOC Content	LB/Gal	g/L	
Total	5.48	656	

### Volatile Organic Compounds - EU Directive 2010/75/EU

	T60F64		
	By wt	By vol	
<b>Total Volatiles</b>	75.1%	82.2%	
VOC Content	LB/Gal	g/L	
Total	5.48	656	

## **Volatile Organic Compounds - Mexico**

	те	60F64
	LB/Gal	g/L
Coating Density	7.30	874
	By wt	By vol
Total Volatiles	75.1%	82.2%
Exempt solvents		
Water	0.0%	0.0%
Acetone	35.9%	39.8%
Organic Volatiles	39.2%	42.4%
Percent Non-Volatile	24.9%	17.8%
VOC Content	LB/Gal	g/L
Total	2.85	342
Less exempt solvents	4.75	569
Of solids	16.10	1929
Of solids	1.57 lb/lb	1.57 kg/kg

### Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T60F64		
	LB/Gal	kg/L	
Volatile HAPS	0.77	0.092	
Of solids	4.35	0.522	
Of solids	0.42 lb/lb	0.42 kg/kg	

### **Air Quality Data**

Density of Organic Solvent Blend 6.67 lb/gal Photochemically Reactive Yes

#### Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.