

# ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation  
Jan 20, 2024

37 00 [2833]

## PRODUCT NUMBER

T67F6

## PRODUCT NAME

SHER-WOOD® Fast Dry Vinyl Sealer, Clear

## MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

## Hazard Category (for SARA 311.312)

T67F6 = | Acute | Chronic | Fire |

## Product Weight

7.46 lb/gal

## Specific Gravity

0.90

## FLASH POINT

4 °F PMCC

## Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	N	N	4	5
2-Propanol 67-63-0	N	N	N	N	4	4
1-Butanol 71-36-3	N	Y	Y	N	1	1
2-Methyl-1-propanol 78-83-1	N	Y	N	N	1	2
Acetone 67-64-1	N	Y	N	N	52	59
n-Butyl Acetate 123-86-4	N	Y	N	N	7	7
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	7	6

**Volatile Organic Compounds - U.S. EPA / Canada**

	T67F6	
	LB/Gal	g/L
Coating Density	7.46	893
	By wt	By vol
Total Volatiles	77.2%	85.1%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	52.2%	59.1%
Organic Volatiles	25.0%	26.0%
Percent Non-Volatile	22.8%	14.9%
VOC Content	LB/Gal	g/L
Total	1.86	223
Less exempt solvents	4.55	545
Of solids	12.49	1496
Of solids	1.09 lb/lb	1.09 kg/kg
	By wt	
By wt LVP-VOC	24.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.59**

**Volatile Organic Compounds - California**

	T67F6	
	LB/Gal	g/L
Coating Density	7.46	893
	By wt	By vol
Total Volatiles	77.2%	85.1%
Exempt solvents		
Water	0.0%	0.0%
Acetone	52.2%	59.1%
Organic Volatiles	25.0%	26.0%
Percent Non-Volatile	22.8%	14.9%
VOC Content	LB/Gal	g/L
Total	1.86	223
Less exempt solvents	4.55	545
Of solids	12.49	1496
Of solids	1.09 lb/lb	1.09 kg/kg
	By wt	
By wt LVP-VOC	24.9%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.54**

**Volatile Organic Compounds - South Coast Air Quality Management District, California, US**

	T67F6	
	LB/Gal	g/L
Coating Density	7.46	893
	By wt	By vol
Total Volatiles	77.2%	85.1%
Exempt solvents		
Water	0.0%	0.0%
Acetone	52.2%	59.1%
Organic Volatiles	25.0%	26.0%
Percent Non-Volatile	22.8%	14.9%
VOC Content	LB/Gal	g/L
Total	1.86	223
Less exempt solvents	4.55	545
Of solids	12.49	1496
Of solids	1.09 lb/lb	1.09 kg/kg

**Volatile Organic Compounds - EU Directive 2004/42/EC**

	T67F6	
	By wt	By vol
Total Volatiles	77.2%	85.1%
VOC Content	LB/Gal	g/L
Total	5.75	689

**Volatile Organic Compounds - EU Directive 2010/75/EU**

	T67F6	
	By wt	By vol
Total Volatiles	77.2%	85.1%
VOC Content	LB/Gal	g/L
Total	5.75	689

**Volatile Organic Compounds - Mexico**

	T67F6	
	LB/Gal	g/L
Coating Density	7.46	893
	By wt	By vol
Total Volatiles	77.2%	85.1%
Exempt solvents		
Water	0.0%	0.0%
Acetone	52.2%	59.1%
Organic Volatiles	25.0%	26.0%
Percent Non-Volatile	22.8%	14.9%
VOC Content	LB/Gal	g/L
Total	1.86	223
Less exempt solvents	4.55	545
Of solids	12.49	1496
Of solids	1.09 lb/lb	1.09 kg/kg

**Hazardous Air Pollutants (Clean Air Act, Section 112(b))**

	T67F6	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

**Air Quality Data****Density of Organic Solvent Blend**

6.77 lb/gal

**Photochemically Reactive**

No

**Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.