ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation
Jan 20, 2024

21 00 [2523]

PRODUCT NUMBER

T70F23

PRODUCT NAME

SHER-WOOD® Moisture Resistant Lacquer, Dull Rubbed Effect

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 W. Prospect Avenue
Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T70F23 = | Acute | Chronic | Fire |

Product Weight	Specific Gravity	FLASH POINT
7.42 lb/gal	0.89	22 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent **64742-89-8**	N	N	N	N	19	23
Toluene **108-88-3**	N	Y	Y	Y	1	1
Ethylbenzene **100-41-4**	N	Y	Y	Y	0.7	< 1
Xylene **1330-20-7**	N	Y	Y	Y	4	4
2-Propanol **67-63-0**	N	N	N	N	10	11
2-Methyl-1-propanol **78-83-1**	N	Y	N	N	9	10
Methyl Ethyl Ketone **78-93-3**	N	Y	N	N	2	3
Methyl n-Amyl Ketone **110-43-0**	N	N	N	N	2	2
Isobutyl Acetate **110-19-0**	N	Y	N	N	27	27

Volatile Organic Compounds - U.S. EPA / Canada

	T70F23	
	LB/Gal	**g/L**
Coating Density	7.42	888
	By wt	**By vol**
Total Volatiles	75.9%	83.5%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	75.9%	83.5%
Percent Non-Volatile	24.1%	16.5%
VOC Content	**LB/Gal**	**g/L**
Total	5.63	674
Less exempt solvents	5.63	674
Of solids	34.15	4092
Of solids	3.15 lb/lb	3.15 kg/kg
	By wt	
By wt LVP-VOC	75.9%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.17**

Volatile Organic Compounds - California

	T70F23	
	LB/Gal	**g/L**
Coating Density	7.42	888
	By wt	**By vol**
Total Volatiles	75.9%	83.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	75.9%	83.5%
Percent Non-Volatile	24.1%	16.5%
VOC Content	**LB/Gal**	**g/L**
Total	5.63	674
Less exempt solvents	5.63	674
Of solids	34.15	4092
Of solids	3.15 lb/lb	3.15 kg/kg
	By wt	
By wt LVP-VOC	75.9%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.16**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T70F23	
	LB/Gal	g/L
Coating Density	7.42	888
	By wt	By vol
Total Volatiles	75.9%	83.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	75.9%	83.5%
Percent Non-Volatile	24.1%	16.5%
VOC Content	LB/Gal	g/L
Total	5.63	674
Less exempt solvents	5.63	674
Of solids	34.15	4092
Of solids	3.15 lb/lb	3.15 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	T70F23	
	By wt	By vol
Total Volatiles	75.9%	83.5%
VOC Content	LB/Gal	g/L
Total	5.63	674

Volatile Organic Compounds - EU Directive 2010/75/EU

	T70F23	
	By wt	By vol
Total Volatiles	75.9%	83.5%
VOC Content	LB/Gal	g/L
Total	5.63	674

Volatile Organic Compounds - Mexico

	T70F23	
	LB/Gal	g/L
Coating Density	7.42	888
	By wt	By vol
Total Volatiles	75.9%	83.5%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	75.9%	83.5%
Percent Non-Volatile	24.1%	16.5%
VOC Content	LB/Gal	g/L
Total	5.63	674
Less exempt solvents	5.63	674
Of solids	34.15	4092
Of solids	3.15 lb/lb	3.15 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T70F23	
	LB/Gal	kg/L
Volatile HAPS	0.47	0.056
Of solids	2.86	0.343
Of solids	0.26 lb/lb	0.26 kg/kg

Air Quality Data

Density of Organic Solvent Blend

6.74 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.