

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

39 00 [3223]

PRODUCT NUMBER

T70FT1

PRODUCT NAME

SHER-WOOD® Hi Build Lacquer, Medium Rubbed Effect

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T70FT1 = | Acute | Chronic | Fire |

Product Weight

7.33 lb/gal

Specific Gravity

0.88

FLASH POINT

23 °F PMCC

Volatile Ingredients

| Chemical / Compound | SARA 302 EHS | CERCLA | SARA 313 TC | HAPS 112 | % by Weight | % by Volume |
|-------------------------------------------------|--------------|--------|-------------|----------|-------------|-------------|
| Lt. Aliphatic Hydrocarbon Solvent 64742-89-8 | N | N | N | N | 19 | 23 |
| Toluene 108-88-3 | N | Y | Y | Y | 7 | 7 |
| Ethylbenzene 100-41-4 | N | Y | Y | Y | 0.1 | 0.1 |
| 2-Propanol 67-63-0 | N | N | N | N | 4 | 4 |
| 2-Methyl-1-propanol 78-83-1 | N | Y | N | N | 16 | 18 |
| Acetone 67-64-1 | N | Y | N | N | 4 | 5 |
| Methyl Ethyl Ketone 78-93-3 | N | Y | N | N | 5 | 5 |
| Isopropyl Acetate 108-21-4 | N | N | N | N | 5 | 5 |
| Isobutyl Acetate 110-19-0 | N | Y | N | N | 16 | 16 |

Regulated Compounds

| | SARA 302 EHS | CERCLA | SARA 313 TC | HAPS 112 | % by Weight | % by Volume |
|-----------------|--------------|--------|-------------|----------|-------------|-------------|
| Mercury (as Hg) | N | N | Y | N | 0.000001 | |
| Lead (as Pb) | N | N | Y | N | 0.000002 | |

Volatile Organic Compounds - U.S. EPA / Canada

| | T70FT1 | |
|---------------------------|------------|------------|
| | LB/Gal | g/L |
| Coating Density | 7.33 | 878 |
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| Federally exempt solvents | | |
| Water | 0.0% | 0.0% |
| Acetone | 4.4% | 4.9% |
| Organic Volatiles | 73.6% | 79.9% |
| Percent Non-Volatile | 22.0% | 15.3% |
| VOC Content | LB/Gal | g/L |
| Total | 5.39 | 646 |
| Less exempt solvents | 5.67 | 679 |
| Of solids | 35.28 | 4227 |
| Of solids | 3.34 lb/lb | 3.34 kg/kg |
| | By wt | |
| By wt LVP-VOC | 73.6% | |

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.21**

Volatile Organic Compounds - California

| | T70FT1 | |
|----------------------|------------|------------|
| | LB/Gal | g/L |
| Coating Density | 7.33 | 878 |
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| Exempt solvents | | |
| Water | 0.0% | 0.0% |
| Acetone | 4.4% | 4.9% |
| Organic Volatiles | 73.6% | 79.9% |
| Percent Non-Volatile | 22.0% | 15.3% |
| VOC Content | LB/Gal | g/L |
| Total | 5.39 | 646 |
| Less exempt solvents | 5.67 | 679 |
| Of solids | 35.28 | 4227 |
| Of solids | 3.34 lb/lb | 3.34 kg/kg |
| | By wt | |
| By wt LVP-VOC | 73.6% | |

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **1.24**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

| | T70FT1 | |
|----------------------|------------|------------|
| | LB/Gal | g/L |
| Coating Density | 7.33 | 878 |
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| Exempt solvents | | |
| Water | 0.0% | 0.0% |
| Acetone | 4.4% | 4.9% |
| Organic Volatiles | 73.6% | 79.9% |
| Percent Non-Volatile | 22.0% | 15.3% |
| VOC Content | LB/Gal | g/L |
| Total | 5.39 | 646 |
| Less exempt solvents | 5.67 | 679 |
| Of solids | 35.28 | 4227 |
| Of solids | 3.34 lb/lb | 3.34 kg/kg |

Volatile Organic Compounds - EU Directive 2004/42/EC

| | T70FT1 | |
|-----------------|--------|--------|
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| VOC Content | LB/Gal | g/L |
| Total | 5.71 | 684 |

Volatile Organic Compounds - EU Directive 2010/75/EU

| | T70FT1 | |
|-----------------|--------|--------|
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| VOC Content | LB/Gal | g/L |
| Total | 5.71 | 684 |

Volatile Organic Compounds - Mexico

| | T70FT1 | |
|----------------------|------------|------------|
| | LB/Gal | g/L |
| Coating Density | 7.33 | 878 |
| | By wt | By vol |
| Total Volatiles | 78.0% | 84.7% |
| Exempt solvents | | |
| Water | 0.0% | 0.0% |
| Acetone | 4.4% | 4.9% |
| Organic Volatiles | 73.6% | 79.9% |
| Percent Non-Volatile | 22.0% | 15.3% |
| VOC Content | LB/Gal | g/L |
| Total | 5.39 | 646 |
| Less exempt solvents | 5.67 | 679 |
| Of solids | 35.28 | 4227 |
| Of solids | 3.34 lb/lb | 3.34 kg/kg |

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

| | T70FT1 | |
|---------------|------------|------------|
| | LB/Gal | kg/L |
| Volatile HAPS | 0.53 | 0.064 |
| Of solids | 3.50 | 0.420 |
| Of solids | 0.33 lb/lb | 0.33 kg/kg |

Air Quality Data**Density of Organic Solvent Blend**

6.75 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.