#### **ENVIRONMENTAL DATA SHEET**

(Certified Product Data Sheet)

**Date of Preparation** 

Jan 20, 2024

08 00 [2523]

### **PRODUCT NUMBER**

T73F10

#### **PRODUCT NAME**

PROCRAFT™ 9310 Clear Polyurethane, Matte

#### **MANUFACTURER'S NAME**

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

#### Hazard Category (for SARA 311.312)

T73F10 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT8.17 lb/gal0.9825 °F PMCC

#### **Volatile Ingredients**

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	<b>HAPS 112</b>	% by Weight	% by Volume
2-Propanol	N	N	N	N	4	4
67-63-0					<b>T</b>	<b>T</b>
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	3	4
Ethyl Acetate 141-78-6	N	Υ	N	N	15	16
n-Butyl Acetate 123-86-4	N	Υ	N	N	43	48
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	5	5

### Volatile Organic Compounds - U.S. EPA / Canada

	T73F10		
	LB/Gal	g/L	
Coating Density	8.17	979	
	By wt	By vol	
Total Volatiles	70.9%	78.7%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	70.9%	78.7%	
Percent Non-Volatile	29.1%	21.3%	
VOC Content	LB/Gal	g/L	
Total	5.79	694	
Less exempt solvents	5.79	694	
Of solids	27.20	3260	
Of solids	2.44 lb/lb	2.44 kg/kg	
	By wt		
By wt LVP-VOC	70.9%	•	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.71

# **Volatile Organic Compounds - California**

	T73F10		
	LB/Gal	g/L	
Coating Density	8.17	979	
	By wt	By vol	
Total Volatiles	70.9%	78.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	70.9%	78.7%	
Percent Non-Volatile	29.1%	21.3%	
VOC Content	LB/Gal	g/L	
Total	5.79	694	
Less exempt solvents	5.79	694	
Of solids	27.20	3260	
Of solids	2.44 lb/lb	2.44 kg/kg	
	By wt		
By wt LVP-VOC	70.9%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.69

## Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T73F10		
	LB/Gal	g/L	
Coating Density	8.17	979	
	By wt	By vol	
Total Volatiles	70.9%	78.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	70.9%	78.7%	
Percent Non-Volatile	29.1%	21.3%	
VOC Content	LB/Gal	g/L	
Total	5.79	694	
Less exempt solvents	5.79	694	
Of solids	27.20	3260	
Of solids	2.44 lb/lb	2.44 kg/kg	

## Volatile Organic Compounds - EU Directive 2004/42/EC

	T73F10	
	By wt	By vol
Total Volatiles	70.9%	78.7%
VOC Content	LB/Gal	g/L
Total	5.79	694

## Volatile Organic Compounds - EU Directive 2010/75/EU

	T73F10		
	By wt	By vol	
Total Volatiles	70.9%	78.7%	
VOC Content	LB/Gal	g/L	
Total	5.79	694	

## **Volatile Organic Compounds - Mexico**

	T73F10		
	LB/Gal	g/L	
Coating Density	8.17	979	
	By wt	By vol	
Total Volatiles	70.9%	78.7%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	70.9%	78.7%	
Percent Non-Volatile	29.1%	21.3%	
VOC Content	LB/Gal	g/L	
Total	5.79	694	
Less exempt solvents	5.79	694	
Of solids	27.20	3260	
Of solids	2.44 lb/lb	2.44 kg/kg	

## Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T73F10		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

## **Air Quality Data**

**Density of Organic Solvent Blend** 

7.37 lb/gal

**Photochemically Reactive** 

No

### **Waste Disposal**

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.