ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 31, 2023

PRODUCT NUMBER

24 00 [2523]

T77C60

PRODUCT NAME

SHER-WOOD® Acrylic Conversion Coating, Gloss

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T77C60 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.37 lb/gal0.894 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	8	9
Ethanol 64-17-5	N	N	N	N	15	17
1-Butanol 71-36-3	N	Υ	Υ	N	8	8
Acetone 67-64-1	N	Υ	N	N	4	4
Methyl Isoamyl Ketone 110-12-3	N	N	N	N	6	7
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	7	7
Isopropyl Acetate 108-21-4	N	N	N	N	5	5
n-Butyl Acetate 123-86-4	N	Υ	N	N	22	22

Volatile Organic Compounds - U.S. EPA / Canada

	T77C60	
	LB/Gal	g/L
Coating Density	7.37	883
	By wt	By vol
Total Volatiles	76.0%	81.8%
Federally exempt solvents		
Water	0.0%	0.0%
Acetone	4.0%	4.5%
Organic Volatiles	72.0%	77.4%
Percent Non-Volatile	24.0%	18.2%
VOC Content	LB/Gal	g/L
Total	5.30	635
Less exempt solvents	5.55	665
Of solids	29.19	3498
Of solids	2.99 lb/lb	2.99 kg/kg
	By wt	
By wt LVP-VOC	72.0%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 1.19

Volatile Organic Compounds - California

	T77C60		
	LB/Gal	g/L	
Coating Density	7.37	883	
	By wt	By vol	
Total Volatiles	76.0%	81.8%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	4.0%	4.5%	
Organic Volatiles	72.0%	77.4%	
Percent Non-Volatile	24.0%	18.2%	
VOC Content	LB/Gal	g/L	
Total	5.30	635	
Less exempt solvents	5.55	665	
Of solids	29.19	3498	
Of solids	2.99 lb/lb	2.99 kg/kg	
	By wt		
By wt LVP-VOC	72.0%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 1.10

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T77C60	
	LB/Gal	g/L
Coating Density	7.37	883
	By wt	By vol
Total Volatiles	76.0%	81.8%
Exempt solvents		
Water	0.0%	0.0%
Acetone	4.0%	4.5%
Organic Volatiles	72.0%	77.4%
Percent Non-Volatile	24.0%	18.2%
VOC Content	LB/Gal	g/L
Total	5.30	635
Less exempt solvents	5.55	665
Of solids	29.19	3498
Of solids	2.99 lb/lb	2.99 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	T77C60	
	By wt	By vol
Total Volatiles	76.0%	81.8%
VOC Content	LB/Gal	g/L
Total	5.60	671

Volatile Organic Compounds - EU Directive 2010/75/EU

	T77C60	
	By wt	By vol
Total Volatiles	76.0%	81.8%
VOC Content	LB/Gal	g/L
Total	5.60	671

Volatile Organic Compounds - Mexico

	T77C60		
	LB/Gal	g/L	
Coating Density	7.37	883	
	By wt	By vol	
Total Volatiles	76.0%	81.8%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	4.0%	4.5%	
Organic Volatiles	72.0%	77.4%	
Percent Non-Volatile	24.0%	18.2%	
VOC Content	LB/Gal	g/L	
Total	5.30	635	
Less exempt solvents	5.55	665	
Of solids	29.19	3498	
Of solids	2.99 lb/lb	2.99 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T77C60		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

6.84 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.