ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

26 00 [3613]

Date of Preparation Dec 27, 2023

PRODUCT NUMBER

T77F56

PRODUCT NAME

SHER-WOOD® Hi-Bild™ Precat Lacquer, Bright Rubbed Effect

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T77F56 = | Acute | Chronic | Fire |

Product Weight 7.92 lb/gal	Specific 0 0.95	Specific Gravity 0.95		FLASH POINT 4 °F PMCC		
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	Ν	N	7	9
2-Propanol 67-63-0	N	N	N	N	4	5
1-Butanol 71-36-3	N	Y	Y	N	4	5
2-Methyl-1-propanol 78-83-1	N	Y	Ν	N	8	9
Acetone 67-64-1	N	Y	N	N	7	8
n-Butyl Acetate 123-86-4	N	Y	Ν	N	31	33
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	5	5

Volatile Organic Compounds - U.S. EPA / Canada

	T77F56		
	LB/Gal	g/L	
Coating Density	7.92	948	
	By wt	By vol	
Total Volatiles	67.2%	75.4%	
Federally exempt solvents			
Water	0.0%	0.0%	
Acetone	6.9%	8.3%	
Organic Volatiles	60.3%	67.1%	
Percent Non-Volatile	32.8%	24.6%	
VOC Content	LB/Gal	g/L	
Total	4.77	571	
Less exempt solvents	5.20	623	
Of solids	19.37	2321	
Of solids	1.83 lb/lb	1.83 kg/kg	
	By wt		
By wt LVP-VOC	60.3%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.89

Volatile Organic Compounds - California

	T77F56	
	LB/Gal	g/L
Coating Density	7.92	948
	By wt	By vol
Total Volatiles	67.2%	75.4%
Exempt solvents		
Water	0.0%	0.0%
Acetone	6.9%	8.3%
Organic Volatiles	60.3%	67.1%
Percent Non-Volatile	32.8%	24.6%
VOC Content	LB/Gal	g/L
Total	4.77	571
Less exempt solvents	5.20	623
Of solids	19.37	2321
Of solids	1.83 lb/lb	1.83 kg/kg
	By wt	
By wt LVP-VOC	60.3%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.85

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T77F56		
	LB/Gal	g/L	
Coating Density	7.92	948	
	By wt	By vol	
Total Volatiles	67.2%	75.4%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	6.9%	8.3%	
Organic Volatiles	60.3%	67.1%	
Percent Non-Volatile	32.8%	24.6%	
VOC Content	LB/Gal	g/L	
Total	4.77	571	
Less exempt solvents	5.20	623	
Of solids	19.37	2321	
Of solids	1.83 lb/lb	1.83 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	T77F56	
	By wt	By vol
Total Volatiles	67.2%	75.4%
VOC Content	LB/Gal	g/L
Total	5.31	637

Volatile Organic Compounds - EU Directive 2010/75/EU

	T77F56	
	By wt	By vol
Total Volatiles	67.2%	75.4%
VOC Content	LB/Gal	g/L
Total	5.31	637

Volatile Organic Compounds - Mexico

	T77F56	
	LB/Gal	g/L
Coating Density	7.92	948
	By wt	By vol
Total Volatiles	67.2%	75.4%
Exempt solvents		
Water	0.0%	0.0%
Acetone	6.9%	8.3%
Organic Volatiles	60.3%	67.1%
Percent Non-Volatile	32.8%	24.6%
VOC Content	LB/Gal	g/L
Total	4.77	571
Less exempt solvents	5.20	623
Of solids	19.37	2321
Of solids	1.83 lb/lb	1.83 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T77F56		
	LB/Gal	kg/L	
Volatile HAPS	0.00	0.000	
Of solids	0.00	0.000	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend 7.06 lb/gal Photochemically Reactive No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.