ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Feb 21, 2024

38 00 [0524]

T77F58

PRODUCT NAME

PRODUCT NUMBER

SHER-WOOD® Hi-Bild™ Precat Lacquer, Dull Rubbed Effect

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T77F58 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT7.90 lb/gal0.954 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	N	N	7	8
2-Propanol 67-63-0	N	N	N	N	4	5
1-Butanol 71-36-3	N	Υ	Υ	N	4	5
2-Methyl-1-propanol 78-83-1	N	Υ	N	N	8	9
Acetone 67-64-1	N	Υ	N	N	8	10
n-Butyl Acetate 123-86-4	N	Υ	N	N	30	32
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	5	5

Volatile Organic Compounds - U.S. EPA / Canada

	T77F58		
	LB/Gal	g/L	
Coating Density	7.90	946	
	By wt	By vol	
Total Volatiles	67.3%	75.5%	
Federally exempt solvents			
Water	0.0%	0.0%	
Acetone	8.4%	10.0%	
Organic Volatiles	58.9%	65.4%	
Percent Non-Volatile	32.7%	24.5%	
VOC Content	LB/Gal	g/L	
Total	4.65	558	
Less exempt solvents	5.17	620	
Of solids	18.99	2275	
Of solids	1.80 lb/lb	1.80 kg/kg	
	By wt		
By wt LVP-VOC	58.7%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.88

Volatile Organic Compounds - California

	T77F58		
	LB/Gal	g/L	
Coating Density	7.90	946	
	By wt	By vol	
Total Volatiles	67.3%	75.5%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	8.4%	10.0%	
Organic Volatiles	58.9%	65.4%	
Percent Non-Volatile	32.7%	24.5%	
VOC Content	LB/Gal	g/L	
Total	4.65	558	
Less exempt solvents	5.17	620	
Of solids	18.99	2275	
Of solids	1.80 lb/lb	1.80 kg/kg	
	By wt		
By wt LVP-VOC	58.7%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.84

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T77F58		
	LB/Gal	g/L	
Coating Density	7.90	946	
	By wt	By vol	
Total Volatiles	67.3%	75.5%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	8.4%	10.0%	
Organic Volatiles	58.9%	65.4%	
Percent Non-Volatile	32.7%	24.5%	
VOC Content	LB/Gal	g/L	
Total	4.65	558	
Less exempt solvents	5.17	620	
Of solids	18.99	2275	
Of solids	1.80 lb/lb	1.80 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	T77F58	
	By wt	By vol
Total Volatiles	67.3%	75.5%
VOC Content	LB/Gal	g/L
Total	5.31	637

Volatile Organic Compounds - EU Directive 2010/75/EU

	T77F58	
	By wt	By vol
Total Volatiles	67.3%	75.5%
VOC Content	LB/Gal	g/L
Total	5.31	637

Volatile Organic Compounds - Mexico

	T77F58		
	LB/Gal	g/L	
Coating Density	7.90	946	
	By wt	By vol	
Total Volatiles	67.3%	75.5%	
Exempt solvents			
Water	0.0%	0.0%	
Acetone	8.4%	10.0%	
Organic Volatiles	58.9%	65.4%	
Percent Non-Volatile	32.7%	24.5%	
VOC Content	LB/Gal	g/L	
Total	4.65	558	
Less exempt solvents	5.17	620	
Of solids	18.99	2275	
Of solids	1.80 lb/lb	1.80 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T77F58	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

7.05 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.