

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Oct 31, 2023

20 00 [2523]

PRODUCT NUMBER

T85W320

PRODUCT NAME

SHER-WOOD® F3 Hi-Bild™ Precat Lacquer White, Low Gloss

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

T85W320 = | Acute | Chronic | Fire |

Product Weight

8.77 lb/gal

Specific Gravity

1.06

FLASH POINT

22 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethanol 64-17-5	N	N	N	N	13	17
2-Propanol 67-63-0	N	N	N	N	3	4
1-Butanol 71-36-3	N	Y	Y	N	3	4
2-Methyl-1-propanol 78-83-1	N	Y	N	N	2	2
Methyl Acetate 79-20-9	N	N	N	N	11	12
n-Butyl Acetate 123-86-4	N	Y	N	N	18	22
1-Methoxy-2-Propanol Acetate 108-65-6	N	N	N	N	7	8

Volatile Organic Compounds - U.S. EPA / Canada

	T85W320	
	LB/Gal	g/L
Coating Density	8.77	1050
	By wt	By vol
Total Volatiles	59.1%	72.1%
Federally exempt solvents		
Water	0.0%	0.0%
Methyl Acetate	10.5%	12.0%
Organic Volatiles	48.6%	60.1%
Percent Non-Volatile	40.9%	27.9%
VOC Content	LB/Gal	g/L
Total	4.26	510
Less exempt solvents	4.84	580
Of solids	15.24	1827
Of solids	1.18 lb/lb	1.18 kg/kg
	By wt	
By wt LVP-VOC	48.6%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.75**

Volatile Organic Compounds - California

	T85W320	
	LB/Gal	g/L
Coating Density	8.77	1050
	By wt	By vol
Total Volatiles	59.1%	72.1%
Exempt solvents		
Water	0.0%	0.0%
Methyl Acetate	10.5%	12.0%
Organic Volatiles	48.6%	60.1%
Percent Non-Volatile	40.9%	27.9%
VOC Content	LB/Gal	g/L
Total	4.26	510
Less exempt solvents	4.84	580
Of solids	15.24	1827
Of solids	1.18 lb/lb	1.18 kg/kg
	By wt	
By wt LVP-VOC	48.6%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.70**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	T85W320	
	LB/Gal	g/L
Coating Density	8.77	1050
	By wt	By vol
Total Volatiles	59.1%	72.1%
Exempt solvents		
Water	0.0%	0.0%
Methyl Acetate	10.5%	12.0%
Organic Volatiles	48.6%	60.1%
Percent Non-Volatile	40.9%	27.9%
VOC Content	LB/Gal	g/L
Total	4.26	510
Less exempt solvents	4.84	580
Of solids	15.24	1827
Of solids	1.18 lb/lb	1.18 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	T85W320	
	By wt	By vol
Total Volatiles	59.2%	72.1%
VOC Content	LB/Gal	g/L
Total	5.18	621

Volatile Organic Compounds - EU Directive 2010/75/EU

	T85W320	
	By wt	By vol
Total Volatiles	59.1%	72.1%
VOC Content	LB/Gal	g/L
Total	5.18	621

Volatile Organic Compounds - Mexico

	T85W320	
	LB/Gal	g/L
Coating Density	8.77	1050
	By wt	By vol
Total Volatiles	59.1%	72.1%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	59.1%	72.1%
Percent Non-Volatile	40.9%	27.9%
VOC Content	LB/Gal	g/L
Total	5.18	621
Less exempt solvents	5.18	621
Of solids	18.55	2223
Of solids	1.44 lb/lb	1.44 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	T85W320	
	LB/Gal	kg/L
Volatile HAPS	0.00	0.000
Of solids	0.00	0.000
Of solids	0.00 lb/lb	0.00 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

7.20 lb/gal

Photochemically Reactive

No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.