ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Aug 1, 2023

14 00 [2133]

PRODUCT NUMBER

V66V55

PRODUCT NAME

POLANE® Exterior Catalyst

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

V66V55 = | Acute | Chronic | Fire |

Product WeightSpecific GravityFLASH POINT9.44 lb/gal1.14117 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Light Aromatic Hydrocarbons 64742-95-6	N	N	N	N	2	3
Cumene 98-82-8	N	Υ	Υ	Υ	0.1	< 1
Trimethylbenzene 25551-13-7	N	N	N	N	1	2
n-Butyl Acetate 123-86-4	N	Y	N	N	5	6

Volatile Organic Compounds - U.S. EPA / Canada

	V66V55		
	LB/Gal	g/L	
Coating Density	9.44	1131	
	By wt	By vol	
Total Volatiles	10.0%	12.9%	
Federally exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	10.0%	12.9%	
Percent Non-Volatile	90.0%	87.1%	
VOC Content	LB/Gal	g/L	
Total	0.94	113	
Less exempt solvents	0.94	113	
Of solids	1.08	129	
Of solids	0.11 lb/lb	0.11 kg/kg	
	By wt		
By wt LVP-VOC	10.0%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.42

Volatile Organic Compounds - California

	V66V55		
	LB/Gal	g/L	
Coating Density	9.44	1131	
	By wt	By vol	
Total Volatiles	10.0%	12.9%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	10.0%	12.9%	
Percent Non-Volatile	90.0%	87.1%	
VOC Content	LB/Gal	g/L	
Total	0.94	113	
Less exempt solvents	0.94	113	
Of solids	1.08	129	
Of solids	0.11 lb/lb	0.11 kg/kg	
	By wt		
By wt LVP-VOC	10.0%	_	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.43

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	V66V55		
	LB/Gal	g/L	
Coating Density	9.44	1131	
	By wt	By vol	
Total Volatiles	10.0%	12.9%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	10.0%	12.9%	
Percent Non-Volatile	90.0%	87.1%	
VOC Content	LB/Gal	g/L	
Total	0.94	113	
Less exempt solvents	0.94	113	
Of solids	1.08	129	
Of solids	0.11 lb/lb	0.11 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	V66V55		
	By wt	By vol	
Total Volatiles	10.0%	12.9%	
VOC Content	LB/Gal	g/L	
Total	0.94	113	

Volatile Organic Compounds - EU Directive 2010/75/EU

	V66V55	
	By wt	By vol
Total Volatiles	10.0%	12.9%
VOC Content	LB/Gal	g/L
Total	0.94	113

Volatile Organic Compounds - Mexico

	V66V55		
	LB/Gal	g/L	
Coating Density	9.44	1131	
	By wt	By vol	
Total Volatiles	10.0%	12.9%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	10.0%	12.9%	
Percent Non-Volatile	90.0%	87.1%	
VOC Content	LB/Gal	g/L	
Total	0.94	113	
Less exempt solvents	0.94	113	
Of solids	1.08	129	
Of solids	0.11 lb/lb	0.11 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	V66V55		
	LB/Gal	kg/L	
Volatile HAPS	0.01	0.001	
Of solids	0.01	0.001	
Of solids	0.00 lb/lb	0.00 kg/kg	

Air Quality Data

Density of Organic Solvent Blend

7.29 lb/gal

Photochemically Reactive

Yes

Additional Regulatory Information

US EPA TSCA:

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against:

Not Applicable

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.