

ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Apr 20, 2024

42 00 [3223]

PRODUCT NUMBER

V84F83

PRODUCT NAME

SHER-WOOD® Water White Conversion Varnish, Dull Rubbed Effect

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY

101 W. Prospect Avenue

Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

V84F83 = | Acute | Chronic | Fire |

Product Weight

7.95 lb/gal

Specific Gravity

0.96

FLASH POINT

40 °F PMCC

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Lt. Aliphatic Hydrocarbon Solvent 64742-89-8	N	N	N	N	6	8
Ethylbenzene 100-41-4	N	Y	Y	Y	4	4
Xylene 1330-20-7	N	Y	Y	Y	21	23
Ethanol 64-17-5	N	N	N	N	7	9
2-Methyl-1-propanol 78-83-1	N	Y	N	N	11	13
Formaldehyde (max.) 50-00-0	Y	Y	Y	Y	0.2	0.2
n-Butyl Acetate 123-86-4	N	Y	N	N	5	5

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Mercury (as Hg)	N	N	Y	N	0.000002	

Volatile Organic Compounds - U.S. EPA / Canada

	V84F83	
	LB/Gal	g/L
Coating Density	7.95	953
	By wt	By vol
Total Volatiles	55.3%	63.9%
Federally exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	55.3%	63.9%
Percent Non-Volatile	44.7%	36.1%
VOC Content	LB/Gal	g/L
Total	4.39	526
Less exempt solvents	4.39	526
Of solids	12.17	1459
Of solids	1.23 lb/lb	1.23 kg/kg
	By wt	
By wt LVP-VOC	55.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **2.23**

Volatile Organic Compounds - California

	V84F83	
	LB/Gal	g/L
Coating Density	7.95	953
	By wt	By vol
Total Volatiles	55.3%	63.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	55.3%	63.9%
Percent Non-Volatile	44.7%	36.1%
VOC Content	LB/Gal	g/L
Total	4.39	526
Less exempt solvents	4.39	526
Of solids	12.17	1459
Of solids	1.23 lb/lb	1.23 kg/kg
	By wt	
By wt LVP-VOC	55.3%	

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **2.25**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	V84F83	
	LB/Gal	g/L
Coating Density	7.95	953
	By wt	By vol
Total Volatiles	55.3%	63.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	55.3%	63.9%
Percent Non-Volatile	44.7%	36.1%
VOC Content	LB/Gal	g/L
Total	4.39	526
Less exempt solvents	4.39	526
Of solids	12.17	1459
Of solids	1.23 lb/lb	1.23 kg/kg

Volatile Organic Compounds - EU Directive 2004/42/EC

	V84F83	
	By wt	By vol
Total Volatiles	55.3%	63.9%
VOC Content	LB/Gal	g/L
Total	4.39	526

Volatile Organic Compounds - EU Directive 2010/75/EU

	V84F83	
	By wt	By vol
Total Volatiles	55.3%	63.9%
VOC Content	LB/Gal	g/L
Total	4.39	526

Volatile Organic Compounds - Mexico

	V84F83	
	LB/Gal	g/L
Coating Density	7.95	953
	By wt	By vol
Total Volatiles	55.3%	63.9%
Exempt solvents		
Water	0.0%	0.0%
Organic Volatiles	55.3%	63.9%
Percent Non-Volatile	44.7%	36.1%
VOC Content	LB/Gal	g/L
Total	4.39	526
Less exempt solvents	4.39	527
Of solids	12.17	1459
Of solids	1.23 lb/lb	1.23 kg/kg

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	V84F83	
	LB/Gal	kg/L
Volatile HAPS	1.94	0.232
Of solids	5.38	0.645
Of solids	0.54 lb/lb	0.54 kg/kg

Air Quality Data**Density of Organic Solvent Blend**

6.88 lb/gal

Photochemically Reactive

Yes

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.