



**SHERWIN
WILLIAMS.**

CC-F61

SHER-WOOD® KEMVAR® Glaze

Van Dyke Brown S66N31
Natural..... S66T30
Custom Blend..... S66SG Series

DESCRIPTION	CHARACTERISTICS	SPECIFICATIONS
<p>SHER-WOOD® KEMVAR® Glaze is an alkyd type glaze formulated for use with a wide variety of Sher-Wood finishes to provide color and accents to interior wood products.</p> <p>Advantages:</p> <ul style="list-style-type: none"> • Ready-to-use • Clean color attains rich wood tones • No color fade or bleeding • Excellent clarity-highlights wood grain • Good workability - 10 minute open working time • Excellent rewetting of glaze even after 24 hours drying • Excellent adhesion on unsanded catalyzed materials such as conversion varnish and catalyzed lacquers • Apply by spray, brush, dip or cloth • May be used with all Sher-Wood solvent borne Sealer and Topcoat systems <p>Not Stocked - Special Order Only: White..... S66W32</p>	<p>Volume Solids: 27 - 30 ± 1% Varies by color</p> <p>Weight Solids: 34 - 40 ± 1% Varies by color</p> <p>Viscosity: 53 - 63 KU Stormer</p> <p>Recommended film thickness: NA Apply full wet coat and wipe clean</p> <p>Drying: (77°F, 50% RH): To Handle: 15 minutes To Recoat: 30 minutes Force Dry: 5-15 minutes at 120°F or 10 minutes at 140°F</p> <p>Good air movement is necessary for adequate drying.</p> <p>Flash Point: 40°F PMCC</p> <p>Package Life: 24 months unopened</p> <p>Air Quality Data:</p> <ul style="list-style-type: none"> • Non-photochemically reactive • Volatile Organic Compounds (VOC) theoretical as packaged, maximum, less exempt solvents: 4.83 lb/gal, 579 g/L • Volatile Hazardous Air Pollutants (VHAPS) as packaged, maximum: < 0.8 lb/lb solids <p>An Environmental Data Sheet is available from your local Sherwin-Williams facility, or at www.paintdocs.com.</p>	<p>General: Surface should be free of grease, oil, dirt, fingerprints, and any contamination to ensure optimum adhesion and coating performance properties. Sealer, basecoat or topcoat should be thoroughly dried, sanded and dust free prior to glazing.</p> <p>Testing: The information, data, and recommendations set forth in this Product Data Sheet are based upon test results believed to be reliable. However, due to the wide variety of substrates, substrate properties, surface preparation methods, equipment and tools, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.</p>

APPLICATION	ADDITIONAL INFORMATION	CAUTIONS
<p>Product must be used under agitation.</p> <ul style="list-style-type: none"> Wipe off excess glaze. Heavy glaze films may cause adhesion problems. Reduce as required to adjust strength or modify drying characteristics. Use mineral spirits to reduce, use R1K140 to retard. Dry 30 minutes air dry. Force dry 5- 15 minutes at 120F. If wiping becomes difficult due to dryness of stain, rewet with a cloth dipped in glaze and then re-wipe. <p>Sher-Wood Natural Filler D70T1 can be added to the S66 glaze to increase the filling properties of the glaze. Penetrating Oil V82V50 can be added to the S66 glaze to provide the glaze with higher vehicle content. This will provide an oilier glaze at application that could improve open time and wiping characteristics.</p> <p>May be applied by: Conventional Spray Airless Spray Air Assisted Airless HVLP Dip</p> <p>Cleanup: Clean tools/equipment immediately after use with mineral spirits.</p> <p>Flush equipment with solvent to prevent rusting.</p> <p>Follow manufacturer's safety recommendations when using any solvent.</p> <p>All trademarks are the property of their respective owners.</p>	<ul style="list-style-type: none"> For interior use only. Do not use under ULTRA-CURE® UV products. Agitation is recommended to maintain uniform color. Final color is influenced by wood type and substrate variations. Solvent based glaze may appear very strong in color on soft wood. If color is too deep, reduce glaze with solvent or allow less drying time before wiping. Not recommended for exterior use. Customer should pretest glaze on substrate and under coating system. Do not exceed 10% SHER-WOOD® SB Colorants (D59B70 series) in S66N31 and S66W32. Do not exceed 25% SHER-WOOD® SB Colorants in S66T30. Excessive tinting may affect adhesion. Sealed or finished surfaces must be glazed and top coated within 16 hours, otherwise the surface must be sanded prior to glazing. <p>Performance Tests: Cross Hatch Adhesion: 3B to 5B depending on coating system and amount of glaze left on the surface.</p>	<p>FOR INDUSTRIAL SHOP APPLICATION ONLY</p> <p>Thoroughly review product label and Safety Data Sheet (SDS) for safety information and cautions prior to using this product.</p> <p>To obtain the most current version of the Environmental Data Sheet (EDS), Product Data Sheet (PDS), or Safety Data Sheet (SDS) please visit your local Sherwin-Williams facility or www.paintdocs.com.</p> <p>Please direct any questions or comments to your local Sherwin-Williams facility.</p> <p>Note: All purchases of products from Sherwin-Williams are exclusively subject to Sherwin-Williams' terms and conditions of sale which can be found by following this link (click here) Please review these terms and conditions prior to the purchase of the products.</p> <p>Sherwin-Williams warrants the product to be free of manufacturing defect in accordance with Sherwin-Williams' quality control procedures. Except for the preceding sentence, due to factors that are outside of Sherwin-Williams' control, including substrate selection, and customer handling, preparation, and application, Sherwin-Williams cannot make any other warranties related to the product or the performance of the product. SHERWIN-WILLIAMS DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.</p> <p>Liability for products proven to be defectively manufactured will be limited solely to replacement of the defective product or the refund of the purchase price paid for the defective product, as determined by Sherwin- Williams. Under no circumstances shall Sherwin-Williams be liable for indirect, special, incidental or consequential damages, lost profits or punitive damages arising from any cause whatsoever</p>