SAFETY DATA SHEET

D64B520

Section 1. Identification

Product name	: SHER-WOOD® Waterborne Stain Dispersion Black
Product code	: D64B520
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	the substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: 866-722-9710 Mexico: Not Available
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 10% (dermal), 10% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer.
Due a sufficiencia statementa	

Precautionary statements

Date of issue/Date	of revision	: 9/8/2023	Date of previous issue	: 6/10/2023	Version	:15	1/13
D64B520	SHER-WOOD® Water Black	borne Stain Dis	persion		SHW-85-	NA-GHS-US	

Section 2. Hazards identification

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
: Store locked up.
 Dispose of contents and container in accordance with all local, regional, national and international regulations.
WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

D64B520

Black

Ingredient name	% by weight	CAS number
Carbon Black	≥25 - ≤50	1333-86-4
Octylphenoxypoly(ethoxy)ethanol	≥10 - ≤25	9002-93-1
Triethanolamine	≤3	102-71-6
1,2-Benzisothiazolone	≤0.3	2634-33-5
2-Methyl-4-isothiazolin-3-one	≤0.3	2682-20-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SHER-WOOD® Waterborne Stain Dispersion

Section 4. First aid measures

Description of necessary fi	<u>rst ai</u>	d measures	<u>S</u>				
Eye contact	:	eyes with p remove any	al attention immediately. lenty of water, occasiona y contact lenses. Contin ated promptly by a phys	ally lifting the upper and ue to rinse for at least	d lower eyelids	s. Check	for and
Inhalation	:	fresh air an fumes are s breathing a occurs, pro dangerous unconsciou an open air inhalation c	al attention immediately. Id keep at rest in a positi still present, the rescuer pparatus. If not breathir vide artificial respiration to the person providing is, place in recovery pos way. Loosen tight clothi of decomposition product y need to be kept under	on comfortable for bre should wear an approp ng, if breathing is irregu or oxygen by trained p aid to give mouth-to-m ition and get medical a ng such as a collar, tie ts in a fire, symptoms r	athing. If it is priate mask or ilar or if respir ersonnel. It m outh resuscita ttention imme , belt or waist nay be delaye	suspected self-conta atory arre nay be tion. If diately. M band. In d	d that ained st Aaintain case of
Date of issue/Date of revision		: 9/8/2023	Date of previous issue	: 6/10/2023	Version	:15	2/13

SHW-85-NA-GHS-US

Section 4. First aid measures

Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for co	ont	ainment and cleaning up	
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.	

Section 7. Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020).TWA: 3.5 mg/m³ 10 hours.OSHA PEL (United States, 5/2018).TWA: 3.5 mg/m³ 8 hours.ACGIH TLV (United States, 1/2023).TWA: 3 mg/m³ 8 hours. Form: Inhalablefraction
Octylphenoxypoly(ethoxy)ethanol Triethanolamine	9002-93-1 102-71-6	None. ACGIH TLV (United States, 1/2023). TWA: 5 mg/m ³ 8 hours.
1,2-Benzisothiazolone 2-Methyl-4-isothiazolin-3-one	2634-33-5 2682-20-4	None. None.

Occupational exposure limits (Canada)

Ingredien	it name		CAS #	Exposure limits			
Carbon bl	ack		1333-86-4	6/2022). TWA: 3 mg/m CA Ontario Pro TWA: 3 mg/m particulate matt CA Quebec Pr TWAEV: 3 mg dust CA Alberta Pro	umbia Provincial (Can ³ 8 hours. Form: Inhalab ovincial (Canada, 6/207 ³ 8 hours. Form: Inhalab ter. ovincial (Canada, 6/201 g/m ³ 8 hours. Form: inha ovincial (Canada, 6/201 5 mg/m ³ 8 hours.	ole 19). ole 22). Ilable	
ate of issue/	Date of revision	: 9/8/2023	Date of previous issue	: 6/10/2023	Version : 15	5/13	
64B520	SHER-WOOD® Black	Waterborne Stain Di	spersion		SHW-85-NA-GHS-U	IS	

Section 8. Exposure controls/personal protection

			CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m ³ 15 minutes. TWA: 3.5 mg/m ³ 8 hours.
Occupational exposure lim	nits (Mexico)	I	1
		CAS #	Exposure limits
None.			
Biological exposure indice	es (United States)		
No exposure indices known	•		
Biological exposure indice	es (Canada)		
No exposure indices known			
Biological exposure indice	as (Mexico)		
No exposure indices known			
,			
Appropriate engineering controls	local exhaust ventila	ation or other engir	es, gas, vapor or mist, use process enclosures, neering controls to keep worker exposure to mmended or statutory limits.
Environmental exposure controls	: Emissions from ven they comply with the cases, fume scrubb	tilation or work pro e requirements of e ers, filters or engin	beering modifications to the process equipment to acceptable levels.
Individual protection meas	ures		
Hygiene measures	eating, smoking and Appropriate techniq Contaminated work	d using the lavatory ues should be use clothing should no ng before reusing.	ughly after handling chemical products, before / and at the end of the working period. d to remove potentially contaminated clothing. t be allowed out of the workplace. Wash Ensure that eyewash stations and safety ocation.
Eye/face protection	assessment indicate gases or dusts. If c the assessment ind	es this is necessar ontact is possible, icates a higher deg	proved standard should be used when a risk y to avoid exposure to liquid splashes, mists, the following protection should be worn, unless gree of protection: chemical splash goggles and/ kist, a full-face respirator may be required instead.
Skin protection			
Hand protection	worn at all times wh necessary. Conside during use that the g noted that the time t glove manufacturers	en handling chemi ering the paramete gloves are still reta to breakthrough for s. In the case of m	complying with an approved standard should be ical products if a risk assessment indicates this is its specified by the glove manufacturer, check ining their protective properties. It should be r any glove material may be different for different nixtures, consisting of several substances, the e accurately estimated.
Body protection		isks involved and	body should be selected based on the task being should be approved by a specialist before
Other skin protection		eing performed an	al skin protection measures should be selected d the risks involved and should be approved by a

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>					
Physical state		Liquid.			
Color		Not available.			
Odor		Not available.			
Odor threshold		Not available.			
pH	÷				
•		9 Not available.			
Melting point/freezing point					
Boiling point, initial boiling point, and boiling range	÷	100°C (212°F)			
Flash point	1	Closed cup: Not applicable.			
Evaporation rate	:	0.09 (butyl acetate = 1)			
Flammability	1	Not available.			
Lower and upper explosion limit/flammability limit	:	: Not available.			
Vapor pressure	:	: 2.3 kPa (17.5 mm Hg)			
Relative vapor density	1	: 1 [Air = 1]			
Relative density	1	: 1.09			
Solubility(ies)	:				
Media		Result			
cold water		Partially soluble			
Partition coefficient: n- octanol/water	:	Not applicable.			
Auto-ignition temperature	1	Not available.			
Decomposition temperature	1	Not available.			
Viscosity	:	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	:	Not applicable.			
Heat of combustion	:	5.353 kJ/g			

Section 10. Stability and reactivity

Reactivity		: No specific	test data related to react	ivity available for this	s product or its ingredients.	
Chemical st	ability	: The produc	t is stable.			
Possibility or reactions	of hazardous	: Under norm	nal conditions of storage	and use, hazardous	reactions will not occur.	
Conditions	to avoid	: No specific	data.			
Incompatibl	e materials	: No specific	data.			
Date of issue/D	Date of revision	: 9/8/2023	Date of previous issue	: 6/10/2023	Version : 15	7/13
D64B520	SHER-WOOD® Black	Waterborne Stain Di	spersion		SHW-85-NA-GHS-US	

Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon Black Octylphenoxypoly(ethoxy) ethanol	LD50 Oral LD50 Oral		>15400 mg/kg 1800 mg/kg	-
Triethanolamine 1,2-Benzisothiazolone	LD50 Oral LD50 Oral		7.39 g/kg 1020 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Octylphenoxypoly(ethoxy) ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 10 uL	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 uL	-
Triethanolamine	Eyes - Mild irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Human	-	72 hours 15 mg I	-
	Skin - Mild irritant	Rabbit	-	24 hours 560 mg	-
	Skin - Severe irritant	Mouse	-	50 %	-
1,2-Benzisothiazolone	Skin - Mild irritant	Human	-	48 hours 5 %	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Carbon Black Triethanolamine	-	2B 3	-

Date of previous issue

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

D64B520

Aspiration hazard

: 9/8/2023

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure	: Not available.
Potential acute health effe	ects
Eye contact	: Causes serious eye damage.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: Adverse symptoms may include the following: pain watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur
Ingestion	: Adverse symptoms may include the following: stomach pains
Delayed and immediate of	fects and also chronic effects from short and long term exposure
Short term exposure	teres and also smolle checks non-short and long term exposure
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of to	

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	18000 mg/kg

Date of issue/Date of revision		: 9/8/2023	Date of previous issue	: 6/10/2023	Version	:15	9/13
D64B520				SHW-85-1	NA-GHS-US		

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Octylphenoxypoly(ethoxy) ethanol	Acute LC50 5.85 mg/l Fresh water	Crustaceans - Ceriodaphnia rigaudi - Neonate	48 hours 🥄
	Acute LC50 11.2 mg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate	48 hours
	Acute LC50 4500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 0.004 mg/l Fresh water	Fish - Gambusia holbrooki	28 days
Triethanolamine	Acute EC50 609.98 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 11800000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic NOEC 16 mg/l Fresh water	Daphnia - Daphnia magna	21 days
1,2-Benzisothiazolone	Acute EC50 97 ppb Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10 to 20 mg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 167 ppb Fresh water	Fish - Oncorhynchus mykiss	96 hours
2-Methyl-4-isothiazolin-3-one	Acute EC50 0.18 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 0.07 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Triethanolamine	-	<3.9	Low

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 9/8/2023	Date of previous issue	: 6/10/2023	Version	:15	10/13
D64B520	SHER-WOOD® Water Black	rborne Stain Di	spersion		SHW-85-N	IA-GHS-US	

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG	
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	-	-	
Transport hazard class(es)	-	-	-	-	-	
Packing group	-	-	-	-	-	
Environmental hazards	No.	No.	No.	No.	No.	
Additional information	-	-	-	-	-	
pecial precautions	conside mode o suitably to shipn of the p dangero and on	odal shipping descript odal shipping descript r container sizes. The f transport (sea, air, for that mode of transformed of transformed nent, and compliance erson offering the propus goods must be the all actions in case of	e presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	a particular is packaged for suitability prior ole responsibility unloading	
ansport in bulk ac IMO instruments	cording : Not avail	able.				

Proper shipping name : Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one

<u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification	
SERIOUS EYE DAMAGE/ SKIN SENSITIZATION - C CARCINOGENICITY - Cat	Calculation method Calculation method Calculation method		
History			
Date of printing	: 9/8/2023		
Date of issue/Date of revision	: 9/8/2023		
Date of previous issue	: 6/10/2023		
Version	: 15		
Key to abbreviations			

Indicates information that has changed from previously issued version.
<u>Notice to reader</u>

Date of issue/Date	of revision	: 9/8/2023	Date of previous issue	: 6/10/2023	Version	:15	12/13
D64B520	SHER-WOOD® Water Black	borne Stain Dis	persion		SHW-85-	NA-GHS-US	

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.