

# SAFETY DATA SHEET

F88W160

## Section 1. Identification

**Product name** : KEM ACRYL® HS 100 Enamel  
Gloss White

**Product code** : F88W160

**Other means of identification** : Not available.

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Paint or paint related material.

**Manufacturer** : THE SHERWIN-WILLIAMS COMPANY  
101 W. Prospect Avenue  
Cleveland, OH 44115

**National contact** : Sherwin-Williams Canada Inc.  
180 Brunel Road  
Mississauga, Ontario L4Z 1T5 Canada

**Emergency telephone number of the company** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

**Product Information Telephone Number** : US / Canada: 866-722-9710  
Mexico: Not Available

**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1  
CARCINOGENICITY - Category 1B  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
ASPIRATION HAZARD - Category 1  
Percentage of the mixture consisting of ingredient(s) of unknown acute dermal toxicity: 4.8%

### GHS label elements

#### Hazard pictograms



**Signal word** : Danger

**Date of issue/Date of revision** : 4/18/2024

**Date of previous issue** : 1/23/2024

**Version** : 23

1/24

F88W160

KEM ACRYL® HS 100 Enamel  
Gloss White

SHW-85-NA-GHS-CA

## Section 2. Hazards identification

<b>Hazard statements</b>	: Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. (hearing organs)
<b>Precautionary statements</b>	
<b>Prevention</b>	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
<b>Response</b>	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
<b>Storage</b>	: Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
<b>Disposal</b>	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Supplemental label elements</b>	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.  Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
<b>Hazards not otherwise classified</b>	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

## Section 3. Composition/information on ingredients

<b>Substance/mixture</b>	: Mixture
<b>Other means of identification</b>	: Not available.
<b>CAS number/other identifiers</b>	

## Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
Titanium Dioxide	37.14	13463-67-7
Methyl n-Amyl Ketone	12.36	110-43-0
Light Aromatic Hydrocarbons	5.76	64742-95-6
trimethylbenzene	3.01	25551-13-7
Styrene	1.83	100-42-5
1,3,5-Trimethylbenzene	1.25	108-67-8
1,2,4-Trimethylbenzene	1.25	95-63-6
Aluminum Hydroxide	1.17	21645-51-2
Methyl Methacrylate	0.46	80-62-6
Xylene, mixed isomers	0.38	1330-20-7
1,2,3-Trimethylbenzene	0.38	526-73-8
Cumene	0.38	98-82-8
Kerosine, petroleum	0.23	64742-81-0
Med. Aliphatic Hydrocarbon Solvent	0.21	64742-88-7
Methyl Ethyl Ketoxime	0.19	96-29-7
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	0.15	77-99-6
Zirconium 2-Ethylhexanoate	0.14	22464-99-9
Ethylbenzene	0.13	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

<b>Date of issue/Date of revision</b> : 4/18/2024	<b>Date of previous issue</b> : 1/23/2024	<b>Version</b> : 23	3/24
F88W160	KEM ACRYL® HS 100 Enamel Gloss White	SHW-85-NA-GHS-CA	

## Section 4. First aid measures

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : May be fatal if swallowed and enters airways.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

## Section 5. Fire-fighting measures

<b>Hazardous thermal decomposition products</b>	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
<b>Special protective actions for fire-fighters</b>	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
<b>Special protective equipment for fire-fighters</b>	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
<b>Remark</b>	: Flammable liquid.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>For non-emergency personnel</b>	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
<b>For emergency responders</b>	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
<b>Environmental precautions</b>	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

<b>Small spill</b>	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
<b>Large spill</b>	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

<b>Protective measures</b>	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made
----------------------------	---

<b>Date of issue/Date of revision</b>	: 4/18/2024	<b>Date of previous issue</b>	: 1/23/2024	<b>Version</b>	: 23	5/24
F88W160	KEM ACRYL® HS 100 Enamel Gloss White			SHW-85-NA-GHS-CA		

## Section 7. Handling and storage

from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	<b>OSHA PEL (United States, 5/2018).</b> TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Methyl n-Amyl Ketone	110-43-0	<b>ACGIH TLV (United States, 1/2023).</b> TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles
Light Aromatic Hydrocarbons trimethylbenzene	64742-95-6 25551-13-7	<b>ACGIH TLV (United States, 1/2023).</b> TWA: 50 ppm 8 hours. TWA: 233 mg/m <sup>3</sup> 8 hours. <b>NIOSH REL (United States, 10/2020).</b> TWA: 100 ppm 10 hours. TWA: 465 mg/m <sup>3</sup> 10 hours. <b>OSHA PEL (United States, 5/2018).</b> TWA: 100 ppm 8 hours. TWA: 465 mg/m <sup>3</sup> 8 hours.
Styrene	100-42-5	None. <b>ACGIH TLV (United States, 1/2023).</b> [trimethyl benzene, isomers] TWA: 10 ppm 8 hours. <b>ACGIH TLV (United States, 1/2023).</b> <b>Ototoxicant.</b> TWA: 10 ppm 8 hours. STEL: 20 ppm 15 minutes. <b>OSHA PEL Z2 (United States, 2/2013).</b> TWA: 100 ppm 8 hours. CEIL: 200 ppm AMP: 600 ppm 5 minutes. <b>NIOSH REL (United States, 10/2020).</b> TWA: 50 ppm 10 hours. TWA: 215 mg/m <sup>3</sup> 10 hours. STEL: 100 ppm 15 minutes. STEL: 425 mg/m <sup>3</sup> 15 minutes.



## Section 8. Exposure controls/personal protection

1,3,5-Trimethylbenzene	108-67-8	<p><b>ACGIH TLV (United States, 1/2023).</b>  <b>[trimethyl benzene, isomers]</b>  TWA: 10 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b>  TWA: 25 ppm 10 hours.  TWA: 125 mg/m<sup>3</sup> 10 hours.</p>
1,2,4-Trimethylbenzene	95-63-6	<p><b>NIOSH REL (United States, 10/2020).</b>  TWA: 25 ppm 10 hours.  TWA: 125 mg/m<sup>3</sup> 10 hours.</p> <p><b>ACGIH TLV (United States, 1/2023).</b>  TWA: 10 ppm 8 hours.</p>
Aluminum Hydroxide	21645-51-2	<p><b>ACGIH TLV (United States, 1/2023).</b>  <b>[Aluminum, metal and insoluble compounds]</b>  TWA: 1 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p>
Methyl Methacrylate	80-62-6	<p><b>ACGIH TLV (United States, 1/2023). Skin sensitizer.</b>  TWA: 50 ppm 8 hours.  STEL: 100 ppm 15 minutes.</p> <p><b>NIOSH REL (United States, 10/2020).</b>  TWA: 100 ppm 10 hours.  TWA: 410 mg/m<sup>3</sup> 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b>  TWA: 100 ppm 8 hours.  TWA: 410 mg/m<sup>3</sup> 8 hours.</p>
Xylene, mixed isomers	1330-20-7	<p><b>OSHA PEL (United States, 5/2018).</b>  <b>[Xylenes (o-, m-, p-isomers)]</b>  TWA: 100 ppm 8 hours.  TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023). [p-xylene and mixtures containing p-xylene] Ototoxicant.</b>  TWA: 20 ppm 8 hours.</p>
1,2,3-Trimethylbenzene	526-73-8	<p><b>ACGIH TLV (United States, 1/2023).</b>  <b>[trimethyl benzene, isomers]</b>  TWA: 10 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b>  TWA: 25 ppm 10 hours.  TWA: 125 mg/m<sup>3</sup> 10 hours.</p>
Cumene	98-82-8	<p><b>ACGIH TLV (United States, 1/2023).</b>  TWA: 5 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b>  <b>Absorbed through skin.</b>  TWA: 50 ppm 10 hours.  TWA: 245 mg/m<sup>3</sup> 10 hours.</p> <p><b>OSHA PEL (United States, 5/2018).</b>  <b>Absorbed through skin.</b>  TWA: 50 ppm 8 hours.  TWA: 245 mg/m<sup>3</sup> 8 hours.</p>
Kerosine, petroleum	64742-81-0	<p><b>ACGIH TLV (United States, 1/2023).</b>  <b>[Kerosene as total hydrocarbon vapor]</b>  <b>Absorbed through skin.</b>  TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapor) 8 hours.</p>
Med. Aliphatic Hydrocarbon Solvent	64742-88-7	<p><b>OSHA PEL (United States, 5/2018).</b>  <b>[Naphtha (Coal tar)]</b></p>

## Section 8. Exposure controls/personal protection

Methyl Ethyl Ketoxime	96-29-7	<p>TWA: 100 ppm 8 hours. TWA: 400 mg/m<sup>3</sup> 8 hours.</p> <p><b>OARS WEEL (United States, 4/2022). Skin sensitizer.</b></p> <p>TWA: 10 ppm 8 hours. None.</p>
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	77-99-6	<p><b>ACGIH TLV (United States, 1/2023). [Zirconium and compounds as Zr]</b></p> <p>TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours. STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.</p>
Zirconium 2-Ethylhexanoate	22464-99-9	<p><b>NIOSH REL (United States, 10/2020). [zirconium compounds as Zr]</b></p> <p>TWA: 5 mg/m<sup>3</sup>, (as Zr) 10 hours. STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.</p>
Ethylbenzene	100-41-4	<p><b>OSHA PEL (United States, 5/2018). [Zirconium compounds (as Zr)]</b></p> <p>TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2023). Ototoxicant.</b></p> <p>TWA: 20 ppm 8 hours. <b>NIOSH REL (United States, 10/2020).</b></p> <p>TWA: 100 ppm 10 hours. TWA: 435 mg/m<sup>3</sup> 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b></p> <p>TWA: 100 ppm 8 hours. TWA: 435 mg/m<sup>3</sup> 8 hours.</p>

### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Methyl n-amyl ketone	110-43-0	<p><b>CA Alberta Provincial (Canada, 6/2018).</b></p> <p>8 hrs OEL: 233 mg/m<sup>3</sup> 8 hours. 8 hrs OEL: 50 ppm 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 6/2022).</b></p> <p>TWA: 50 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b></p> <p>TWA: 25 ppm 8 hours. TWA: 115 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b></p> <p>TWAEV: 50 ppm 8 hours. TWAEV: 233 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b></p> <p>STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Trimethylbenzene	25551-13-7	<p><b>CA Alberta Provincial (Canada, 6/2018). [Trimethyl benzene (mixed isomers)]</b></p> <p>8 hrs OEL: 123 mg/m<sup>3</sup> 8 hours. 8 hrs OEL: 25 ppm 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 6/2022). [Trimethyl benzene (mixed isomers)]</b></p> <p>TWA: 25 ppm 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b></p>



## Section 8. Exposure controls/personal protection

Vinyl benzene	100-42-5	<p><b>[Trimethyl benzene (mixture of isomers)]</b>  <b>Skin sensitizer. Inhalation sensitizer.</b>  TWA: 25 ppm 8 hours.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  <b>[Trimethyl benzene (mixed isomers)]</b>  TWA: 25 ppm 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> <b>[Trimethyl benzene mixed isomer]</b>  STEL: 30 ppm 15 minutes.  TWA: 25 ppm 8 hours.  <b>CA Alberta Provincial (Canada, 6/2018).</b>  15 min OEL: 40 ppm 15 minutes.  15 min OEL: 170 mg/m<sup>3</sup> 15 minutes.  8 hrs OEL: 85 mg/m<sup>3</sup> 8 hours.  8 hrs OEL: 20 ppm 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b>  TWA: 20 ppm 8 hours.  STEL: 40 ppm 15 minutes.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  TWA: 35 ppm 8 hours.  STEL: 100 ppm 15 minutes.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  TWA: 50 ppm 8 hours.  STEL: 75 ppm 15 minutes.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b>  STEL: 40 ppm 15 minutes.  TWA: 20 ppm 8 hours.</p>
Mesitylene	108-67-8	<p><b>CA Alberta Provincial (Canada, 6/2018).</b>  <b>[Trimethyl benzene (mixed isomers)]</b>  8 hrs OEL: 123 mg/m<sup>3</sup> 8 hours.  8 hrs OEL: 25 ppm 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b> <b>[Trimethyl benzene (mixed isomers)]</b>  TWA: 25 ppm 8 hours.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  <b>[Trimethyl benzene (mixture of isomers)]</b>  <b>Skin sensitizer. Inhalation sensitizer.</b>  TWA: 25 ppm 8 hours.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  <b>[Trimethyl benzene (mixed isomers)]</b>  TWA: 25 ppm 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> <b>[Trimethyl benzene mixed isomer]</b>  STEL: 30 ppm 15 minutes.  TWA: 25 ppm 8 hours.</p>
1,2,4-Trimethylbenzene	95-63-6	<p><b>CA Alberta Provincial (Canada, 6/2018).</b>  <b>[Trimethyl benzene (mixed isomers)]</b>  8 hrs OEL: 123 mg/m<sup>3</sup> 8 hours.  8 hrs OEL: 25 ppm 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b> <b>[Trimethyl benzene (mixed isomers)]</b>  TWA: 25 ppm 8 hours.  <b>CA Quebec Provincial (Canada, 6/2022).</b></p>

## Section 8. Exposure controls/personal protection

Methyl methacrylate	80-62-6	<p><b>[Trimethyl benzene (mixture of isomers)]</b>  <b>Skin sensitizer. Inhalation sensitizer.</b>  TWA: 25 ppm 8 hours.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  <b>[Trimethyl benzene (mixed isomers)]</b>  TWA: 25 ppm 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> <b>[Trimethyl benzene mixed isomer]</b>  STEL: 30 ppm 15 minutes.  TWA: 25 ppm 8 hours.  <b>CA Alberta Provincial (Canada, 6/2018).</b>  8 hrs OEL: 205 mg/m<sup>3</sup> 8 hours.  8 hrs OEL: 50 ppm 8 hours.  15 min OEL: 410 mg/m<sup>3</sup> 15 minutes.  15 min OEL: 100 ppm 15 minutes.  <b>CA British Columbia Provincial (Canada, 6/2022).</b> <b>Skin sensitizer.</b>  TWA: 50 ppm 8 hours.  STEL: 100 ppm 15 minutes.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  <b>Skin sensitizer.</b>  TWA: 50 ppm 8 hours.  STEL: 100 ppm 15 minutes.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  <b>Skin sensitizer.</b>  TWA: 50 ppm 8 hours.  STEL: 100 ppm 15 minutes.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> <b>Skin sensitizer.</b>  STEL: 100 ppm 15 minutes.  TWA: 50 ppm 8 hours.</p>
Xylene	1330-20-7	<p><b>CA Alberta Provincial (Canada, 6/2018).</b>  <b>[Dimethylbenzene (o,m &amp; p isomers)]</b>  8 hrs OEL: 100 ppm 8 hours.  15 min OEL: 651 mg/m<sup>3</sup> 15 minutes.  15 min OEL: 150 ppm 15 minutes.  8 hrs OEL: 434 mg/m<sup>3</sup> 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b> <b>[Xylene (o, m &amp; p isomers)]</b>  TWA: 100 ppm 8 hours.  STEL: 150 ppm 15 minutes.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  <b>[Xylene (o-,m-,p- isomers)]</b>  TWA: 100 ppm 8 hours.  TWA: 434 mg/m<sup>3</sup> 8 hours.  STEL: 150 ppm 15 minutes.  STEL: 651 mg/m<sup>3</sup> 15 minutes.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  <b>[Xylene (o-, m-, p-isomers)]</b>  STEL: 150 ppm 15 minutes.  TWA: 100 ppm 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> <b>[Xylene (o, m-, p-isomers)]</b>  STEL: 150 ppm 15 minutes.  TWA: 100 ppm 8 hours.</p>
Cumene	98-82-8	<p><b>CA Alberta Provincial (Canada, 6/2018).</b>  8 hrs OEL: 50 ppm 8 hours.</p>

## Section 8. Exposure controls/personal protection

		<p>8 hrs OEL: 246 mg/m<sup>3</sup> 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b>  TWA: 25 ppm 8 hours.  STEL: 75 ppm 15 minutes.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  TWA: 50 ppm 8 hours.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  TWAEV: 50 ppm 8 hours.  TWAEV: 246 mg/m<sup>3</sup> 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b>  STEL: 74 ppm 15 minutes.  TWA: 50 ppm 8 hours.</p>
Kerosine (petroleum), hydrosulfurized	64742-81-0	<p><b>CA British Columbia Provincial (Canada, 6/2022).</b> [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin. Notes: Application restricted to conditions in which there are negligible aerosol exposures.  TWA: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours.  <b>CA Alberta Provincial (Canada, 6/2018).</b> [Kerosene/Jet fuels as total hydrocarbon vapour] Absorbed through skin.  8 hrs OEL: 200 mg/m<sup>3</sup>, (as total hydrocarbon vapour) 8 hours.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b> Absorbed through skin.  STEL: 250 mg/m<sup>3</sup>, (measured as total hydrocarbon vapour) 15 minutes.  TWA: 200 mg/m<sup>3</sup>, (measured as total hydrocarbon vapour) 8 hours.  <b>CA Quebec Provincial (Canada, 6/2022).</b> [kerosene] Absorbed through skin.  TWAEV: 200 mg/m<sup>3</sup> 8 hours.</p>
Methyl Ethyl Ketoxime	96-29-7	<p><b>OARS WEEL (United States, 4/2022).</b> Skin sensitizer.  TWA: 10 ppm 8 hours.</p>
Ethyl alcohol	64-17-5	<p><b>CA Alberta Provincial (Canada, 6/2018).</b>  8 hrs OEL: 1000 ppm 8 hours.  8 hrs OEL: 1880 mg/m<sup>3</sup> 8 hours.  <b>CA British Columbia Provincial (Canada, 6/2022).</b>  STEL: 1000 ppm 15 minutes.  <b>CA Ontario Provincial (Canada, 6/2019).</b>  STEL: 1000 ppm 15 minutes.  <b>CA Saskatchewan Provincial (Canada, 7/2013).</b>  STEL: 1250 ppm 15 minutes.  TWA: 1000 ppm 8 hours.  <b>CA Quebec Provincial (Canada, 6/2022).</b>  STEV: 1000 ppm 15 minutes.</p>
Zirconium 2-Ethylhexanoate	22464-99-9	<p><b>CA Alberta Provincial (Canada, 6/2018).</b> [Zirconium and compounds as Zr]  8 hrs OEL: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.  15 min OEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.</p>

## Section 8. Exposure controls/personal protection

Ethylbenzene	100-41-4	<p><b>CA British Columbia Provincial (Canada, 6/2022). [Zirconium and compounds as Zr]</b> TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours. STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.</p> <p><b>CA Quebec Provincial (Canada, 6/2022). [Zirconium and compounds]</b> TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours. STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes.</p> <p><b>CA Ontario Provincial (Canada, 6/2019). [Zirconium and compounds as Z]</b> STEL: 10 mg/m<sup>3</sup>, (as Zr) 15 minutes. TWA: 5 mg/m<sup>3</sup>, (as Zr) 8 hours.</p> <p><b>CA Alberta Provincial (Canada, 6/2018).</b> 8 hrs OEL: 100 ppm 8 hours. 8 hrs OEL: 434 mg/m<sup>3</sup> 8 hours. 15 min OEL: 543 mg/m<sup>3</sup> 15 minutes. 15 min OEL: 125 ppm 15 minutes.</p> <p><b>CA British Columbia Provincial (Canada, 6/2022).</b> TWA: 20 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 20 ppm 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 6/2022).</b> TWA: 20 ppm 8 hours.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b> STEL: 125 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>
--------------	----------	---

### Occupational exposure limits (Mexico)

Ingredient name	CAS #	Exposure limits
Methyl n-Amyl Ketone	110-43-0	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 50 ppm 8 hours.
trimethylbenzene	25551-13-7	<b>NOM-010-STPS-2014 (Mexico, 4/2016). [Trimethyl benzene, mixed isomers]</b> TWA: 25 ppm 8 hours.
Styrene	100-42-5	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 20 ppm 8 hours. STEL: 40 ppm 15 minutes.
1,3,5-Trimethylbenzene	108-67-8	<b>NOM-010-STPS-2014 (Mexico, 4/2016). [Trimethyl benzene, mixed isomers]</b> TWA: 25 ppm 8 hours.
1,2,4-Trimethylbenzene	95-63-6	<b>NOM-010-STPS-2014 (Mexico, 4/2016). [Trimethyl benzene, mixed isomers]</b> TWA: 25 ppm 8 hours.
Cumene	98-82-8	<b>NOM-010-STPS-2014 (Mexico, 4/2016).</b> TWA: 50 ppm 8 hours.
Zirconium 2-Ethylhexanoate	22464-99-9	<b>NOM-010-STPS-2014 (Mexico, 4/2016). [Zirconium compounds]</b> TWA: 5 mg/m <sup>3</sup> , (as Zr) 8 hours. STEL: 10 mg/m <sup>3</sup> , (as Zr) 15 minutes.

### Biological exposure indices (United States)

## Section 8. Exposure controls/personal protection

Ingredient name	Exposure indices
Styrene	<b>ACGIH BEI (United States, 1/2023)</b> BEI: 150 mg/g creatinine, mandelic acid plus phenylglyoxylic acid [in urine]. Sampling time: end of shift. BEI: 20 µg/l, styrene [in urine]. Sampling time: end of shift.
Xylene, mixed isomers	<b>ACGIH BEI (United States, 1/2023) [xylenes (technical or commercial grade)]</b> BEI: 1.5 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift.
Ethylbenzene	<b>ACGIH BEI (United States, 1/2023)</b> BEI: 0.15 g/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine]. Sampling time: end of shift.

### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

Ingredient name	Exposure indices
Styrene	<b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012)</b> BEI: 0.2 mg/L [semi-quantitative. The biological determinant is an indicator of chemical exposure, but the quantitative interpretation of the measure is ambiguous. These biological determinants should be used as a screening test if a quantitative test is not possible.], styrene [in venous blood]. Sampling time: at the end of the work shift. BEI: 400 mg/g creatinine [non-specific. The determinant is nonspecific, since it can be found after exposure to other chemicals.], mandelic Acid plus Phenylglyoxylic Acid [in urine]. Sampling time: at the end of the work shift.

### Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

### Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

<b>Date of issue/Date of revision</b>	: 4/18/2024	<b>Date of previous issue</b>	: 1/23/2024	<b>Version</b> : 23	13/24
F88W160	KEM ACRYL® HS 100 Enamel Gloss White	SHW-85-NA-GHS-CA			

## Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : White.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 145°C (293°F)
- Flash point** : Closed cup: 39°C (102.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 0.49 (butyl acetate = 1)
- Flammability** : Flammable liquid.
- Lower and upper explosion limit/flammability limit** : Lower: 0.7%  
Upper: 7.9%
- Vapor pressure** : 0.57 kPa (4.3 mm Hg)
- Relative vapor density** : 3.6 [Air = 1]
- Relative density** : 1.35
- Solubility(ies)** :

**Date of issue/Date of revision** : 4/18/2024

**Date of previous issue** : 1/23/2024

**Version** : 23

14/24

F88W160

KEM ACRYL® HS 100 Enamel  
Gloss White

SHW-85-NA-GHS-CA



## Section 9. Physical and chemical properties

Media	Result
cold water	Not soluble

Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): <20.5 mm <sup>2</sup> /s (<20.5 cSt)
Molecular weight	: Not applicable.
Heat of combustion	: 11.252 kJ/g

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Methyl n-Amyl Ketone	LD50 Oral	Rat	1600 mg/kg	-
Light Aromatic Hydrocarbons	LD50 Oral	Rat	8400 mg/kg	-
trimethylbenzene	LD50 Oral	Rat	8970 mg/kg	-
Styrene	LC50 Inhalation Gas.	Rat	2770 ppm	4 hours
	LC50 Inhalation Vapor	Rat	11800 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	2650 mg/kg	-
1,3,5-Trimethylbenzene	LC50 Inhalation Vapor	Rat	24000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	5000 mg/kg	-
1,2,4-Trimethylbenzene	LC50 Inhalation Vapor	Rat	18000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	5 g/kg	-
Methyl Methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m <sup>3</sup>	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	7872 mg/kg	-
Xylene, mixed isomers	LC50 Inhalation Gas.	Rat	6700 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-
Cumene	LC50 Inhalation Vapor	Rat	39000 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	1400 mg/kg	-
Kerosine, petroleum	LD50 Oral	Rat	>5000 mg/kg	-

Date of issue/Date of revision	: 4/18/2024	Date of previous issue	: 1/23/2024	Version	: 23	15/24
F88W160	KEM ACRYL® HS 100 Enamel			SHW-85-NA-GHS-CA		
	Gloss White					

## Section 11. Toxicological information

Methyl Ethyl Ketoxime	LD50 Oral	Rat	930 mg/kg	-
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	LD50 Oral	Rat	14000 mg/kg	-
Zirconium 2-Ethylhexanoate	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	>5 g/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Methyl n-Amyl Ketone	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
Light Aromatic Hydrocarbons	Eyes - Mild irritant	Rabbit	-	24 hours 100 uL	-
trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Styrene	Eyes - Mild irritant	Human	-	50 ppm	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
1,3,5-Trimethylbenzene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Cumene	Eyes - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Eyes - Mild irritant	Rabbit	-	86 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 10 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 100 mg	-
Kerosine, petroleum	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Methyl Ethyl Ketoxime	Eyes - Severe irritant	Rabbit	-	100 uL	-
Ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 mg	-

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

## Section 11. Toxicological information

### Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-
Styrene	-	2A	Reasonably anticipated to be a human carcinogen.
Methyl Methacrylate	-	3	-
Xylene, mixed isomers	-	3	-
Cumene	-	2B	Reasonably anticipated to be a human carcinogen.
Ethylbenzene	-	2B	-

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Methyl n-Amyl Ketone	Category 3	-	Respiratory tract irritation
Light Aromatic Hydrocarbons	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Styrene	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
1,3,5-Trimethylbenzene	Category 3	-	Respiratory tract irritation
1,2,4-Trimethylbenzene	Category 3	-	Respiratory tract irritation
Methyl Methacrylate	Category 3	-	Respiratory tract irritation
Xylene, mixed isomers	Category 3	-	Respiratory tract irritation
1,2,3-Trimethylbenzene	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Cumene	Category 3	-	Narcotic effects
Kerosine, petroleum	Category 3	-	Respiratory tract irritation
Med. Aliphatic Hydrocarbon Solvent	Category 3 Category 3	-	Narcotic effects Respiratory tract irritation
Methyl Ethyl Ketoxime	Category 3 Category 1	-	Narcotic effects upper respiratory tract
Ethylbenzene	Category 3 Category 3	-	Narcotic effects Narcotic effects

### Specific target organ toxicity (repeated exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
Methyl n-Amyl Ketone	Category 2	-	-
Light Aromatic Hydrocarbons	Category 2	-	-
Styrene	Category 1	-	hearing organs
Xylene, mixed isomers	Category 2	-	-
Kerosine, petroleum	Category 2	-	-
Med. Aliphatic Hydrocarbon Solvent	Category 1	-	-
Methyl Ethyl Ketoxime	Category 2	-	blood system
Ethylbenzene	Category 2	-	-

### Aspiration hazard

Name	Result
Light Aromatic Hydrocarbons	ASPIRATION HAZARD - Category 1
trimethylbenzene	ASPIRATION HAZARD - Category 1
Styrene	ASPIRATION HAZARD - Category 1
1,3,5-Trimethylbenzene	ASPIRATION HAZARD - Category 1
1,2,4-Trimethylbenzene	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1
1,2,3-Trimethylbenzene	ASPIRATION HAZARD - Category 1
Cumene	ASPIRATION HAZARD - Category 1
Kerosine, petroleum	ASPIRATION HAZARD - Category 1
Med. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

**Inhalation** : May cause respiratory irritation.

**Skin contact** : May cause an allergic skin reaction.

**Ingestion** : May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

## Section 11. Toxicological information

**Ingestion** : Adverse symptoms may include the following:  
nausea or vomiting  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : Suspected of damaging the unborn child.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : Suspected of damaging fertility.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	6813.05 mg/kg
Inhalation (gases)	151260.04 ppm
Inhalation (vapors)	61.66 mg/l

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - <i>Fundulus heteroclitus</i>	96 hours
	Acute LC50 131000 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Acute LC50 5600 µg/l Marine water	Crustaceans - <i>Palaemonetes pugio</i>	48 hours
Styrene	Acute EC50 78000 µg/l Marine water	Algae - <i>Skeletonema costatum</i>	96 hours
	Acute EC50 4700 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 52 mg/l Marine water	Crustaceans - <i>Artemia salina</i>	48 hours
1,3,5-Trimethylbenzene	Acute LC50 4020 µg/l Fresh water	Fish - <i>Pimephales promelas</i>	96 hours
	Acute LC50 13000 µg/l Marine water	Crustaceans - <i>Cancer magister</i> - Zoea	48 hours
	Acute LC50 12520 µg/l Fresh water	Fish - <i>Carassius auratus</i>	96 hours
1,2,4-Trimethylbenzene	Chronic NOEC 0.4 mg/l Fresh water	Daphnia - <i>Daphnia magna</i>	21 days
	Acute LC50 4910 µg/l Marine water	Crustaceans - <i>Elasmopus</i>	48 hours

<b>Date of issue/Date of revision</b> : 4/18/2024	<b>Date of previous issue</b> : 1/23/2024	<b>Version</b> : 23	19/24
F88W160	KEM ACRYL® HS 100 Enamel Gloss White	SHW-85-NA-GHS-CA	

## Section 12. Ecological information

Methyl Methacrylate	Acute LC50 7720 µg/l Fresh water Acute LC50 130000 µg/l Fresh water	<i>pecteniscus</i> - Adult Fish - <i>Pimephales promelas</i> Fish - <i>Pimephales promelas</i> - Adult	96 hours 96 hours
Xylene, mixed isomers	Acute LC50 8500 µg/l Marine water	Crustaceans - <i>Palaemonetes pugio</i>	48 hours
Cumene	Acute LC50 13400 µg/l Fresh water Acute EC50 7.4 mg/l Marine water	Fish - <i>Pimephales promelas</i> Crustaceans - <i>Artemia</i> sp. - Nauplii	96 hours 48 hours
Methyl Ethyl Ketoxime 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	Acute EC50 10.6 mg/l Fresh water Acute LC50 2700 µg/l Fresh water Acute LC50 843000 µg/l Fresh water Acute EC50 13000000 µg/l Fresh water	Daphnia - <i>Daphnia magna</i> - Neonate Fish - <i>Oncorhynchus mykiss</i> Fish - <i>Pimephales promelas</i> Daphnia - <i>Daphnia magna</i>	48 hours 96 hours 96 hours 48 hours
Ethylbenzene	Acute LC50 14400000 µg/l Marine water Acute EC50 4900 µg/l Marine water Acute EC50 7700 µg/l Marine water Acute EC50 6.53 mg/l Marine water Acute EC50 2.93 mg/l Fresh water Acute LC50 4200 µg/l Fresh water	Fish - <i>Cyprinodon variegatus</i> Algae - <i>Skeletonema costatum</i> Algae - <i>Skeletonema costatum</i> Crustaceans - <i>Artemia</i> sp. - Nauplii Daphnia - <i>Daphnia magna</i> - Neonate Fish - <i>Oncorhynchus mykiss</i>	96 hours 72 hours 96 hours 48 hours 48 hours 96 hours

### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Methyl n-Amyl Ketone	-	-	Readily
Light Aromatic Hydrocarbons	-	-	Readily
Xylene, mixed isomers	-	-	Readily
Ethylbenzene	-	-	Readily

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Light Aromatic Hydrocarbons	-	10 to 2500	High
Styrene	-	13.49	Low
1,3,5-Trimethylbenzene	-	161	Low
1,2,4-Trimethylbenzene	-	243	Low
Xylene, mixed isomers	-	8.1 to 25.9	Low
1,2,3-Trimethylbenzene	-	194.98	Low
Cumene	-	35.48	Low
Methyl Ethyl Ketoxime	-	2.5 to 5.8	Low
2-Ethyl-2-(hydroxymethyl)-1,3-propanediol	-	<1	Low
Zirconium 2-Ethylhexanoate	-	2.96	Low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.








## Section 13. Disposal considerations

### Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	III	III	III	III	III
Environmental hazards	No.	No.	No.	No.	No.
Additional information	This product may be re-classified as "Combustible Liquid," unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gal) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity. <b>ERG No.</b> 128	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). <b>ERG No.</b> 128	- <b>ERG No.</b> 128	-	<b>Emergency schedules</b> F-E, S-E

## Section 14. Transport information

--	--	--	--	--	--

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to IMO instruments** : Not available.

**Proper shipping name** : Not available.

## Section 15. Regulatory information

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

### International lists

: **Australia inventory (AIIIC)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Korea inventory (KECI)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
**Philippines inventory (PICCS)**: Not determined.  
**Taiwan Chemical Substances Inventory (TCSI)**: Not determined.  
**Thailand inventory**: Not determined.  
**Turkey inventory**: Not determined.  
**Vietnam inventory**: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		2
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

### Procedure used to derive the classification

<b>Date of issue/Date of revision</b>	: 4/18/2024	<b>Date of previous issue</b>	: 1/23/2024	<b>Version</b>	: 23	22/24
F88W160	KEM ACRYL® HS 100 Enamel				SHW-85-NA-GHS-CA	
	Gloss White					

## Section 16. Other information

Classification	Justification
FLAMMABLE LIQUIDS - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1B TOXIC TO REPRODUCTION - Category 2 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 ASPIRATION HAZARD - Category 1	On basis of test data Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method Calculation method

### History

**Date of printing** : 4/18/2024

**Date of issue/Date of revision** : 4/18/2024

**Date of previous issue** : 1/23/2024

**Version** : 23

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

<b>Date of issue/Date of revision</b> : 4/18/2024	<b>Date of previous issue</b> : 1/23/2024	<b>Version</b> : 23	23/24
F88W160	KEM ACRYL® HS 100 Enamel Gloss White	SHW-85-NA-GHS-CA	

