# **SAFETY DATA SHEET**

F93N505KL

## Section 1. Identification

Product name	: MIL-DTL-64159C Type III 2K Water Reducible Polyurethane Tru-Mix® Touch Up Cartridge 600mL Brown 383 30051 Q2081
Product code	: F93N505KL
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
National contact	: Sherwin-Williams Canada Inc. 180 Brunel Road Mississauga, Ontario L4Z 1T5 Canada
Emergency telephone number of the company Product Information Telephone Number	<ul> <li>US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year</li> <li>US / Canada: 1-844-290-6044 Mexico: Not Available</li> </ul>
Transportation Emergency Telephone Number	: US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 1B	
	Percentage of the mixture consisting of ingredient(s) of un (dermal), 6.4% (inhalation)	known acute toxicity: 2.4%
GHS label elements		
Hazard pictograms		
Signal word	: Danger	
Hazard statements	: May cause an allergic skin reaction. Suspected of causing cancer. May damage fertility or the unborn child.	
Precautionary statements		
Prevention	: Obtain special instructions before use. Do not handle until been read and understood. Wear protective gloves, protection. Avoid breathing vapor. Contaminated work clo of the workplace.	ctive clothing and eye or face
Date of issue/Date of revision	: 9/18/2023 Date of previous issue : 7/31/2023	Version : 21 1/1
F93N505KL MIL-DTL-64159	C Type III 2K Water Reducible Polyurethane	SHW-85-NA-GHS-CA

Tru-Mix® Touch Up Cartridge 600mL Brown 383 30051 Q2081

## Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### CAS number/other identifiers

Ingredient name	% by weight	CAS number
Chromium Oxide	7.72	1308-38-9
1-Methyl-2-Pyrrolidone	3.96	872-50-4
Mercaptopropyl Trimethoxysilane	2.44	4420-74-0
Iron Oxide	2.08	1309-37-1
Carbon Black	0.12	1333-86-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

#### Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	2/13
F93N505KL	MIL-DTL-64159C Type Tru-Mix® Touch Up Ca		educible Polyurethane 3rown 383 30051 Q2081		SHW-85-	NA-GHS-CA	

### Section 4. First aid measures

Section 4. First a	id measures
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	ects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/sym</u>	<u>ptoms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>In case of inhalation of decomposition products in a fire, symptoms may be delayed.</li> <li>The exposed person may need to be kept under medical surveillance for 48 hours.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	3/13
F93N505KL	MIL-DTL-64159C Type Tru-Mix® Touch Up Ca		educible Polyurethane Brown 383 30051 Q2081		SHW-85-	NA-GHS-CA	

## Section 5. Fire-fighting measures

•	-
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protect	<u>tiv:</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

#### Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	4/13
F93N505KL	MIL-DTL-64159C Type Tru-Mix® Touch Up Car		ducible Polyurethane Brown 383 30051 Q2081		SHW-85-	NA-GHS-CA	

## Section 7. Handling and storage

		closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Chromium Oxide	1308-38-9	NIOSH REL (United States, 10/2020). [chromium (III) compounds as Cr] TWA: 0.5 mg/m <sup>3</sup> , (as Cr) 8 hours. ACGIH TLV (United States, 1/2023). [inorganic chromium III compounds as Cr] TWA: 0.003 mg/m <sup>3</sup> , (measured as Cr) 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Chromium (III) compounds (as Cr)] TWA: 0.5 mg/m <sup>3</sup> , (as Cr) 8 hours.
1-Methyl-2-Pyrrolidone	872-50-4	OARS WEEL (United States, 4/2022). Absorbed through skin. TWA: 15 ppm 8 hours. STEL: 120 mg/m <sup>3</sup> 15 minutes. STEL: 30 ppm 15 minutes. TWA: 60 mg/m <sup>3</sup> 8 hours.
Mercaptopropyl Trimethoxysilane Iron Oxide	4420-74-0 1309-37-1	None. <b>NIOSH REL (United States, 10/2020).</b> TWA: 5 mg/m <sup>3</sup> , (as Fe) 10 hours. Form: Dust and fumes <b>ACGIH TLV (United States, 1/2023).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction <b>OSHA PEL (United States, 5/2018).</b> TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020). TWA: 3.5 mg/m <sup>3</sup> 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). TWA: 3 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	5/13
F93N505KL	MIL-DTL-64159C Type	III 2K Water Re	educible Polyurethane		SHW-85-	NA-GHS-CA	
	Tru-Mix® Touch Up Ca	rtridge 600mL E	Brown 383 30051 Q2081				

### Section 8. Exposure controls/personal protection

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
N-Methyl pyrrolidone	872-50-4	<b>CA Ontario Provincial (Canada, 6/2019).</b> TWA: 400 mg/m <sup>3</sup> 8 hours.
Carbon black	1333-86-4	<ul> <li>CA British Columbia Provincial (Canada, 6/2022).</li> <li>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable</li> <li>CA Ontario Provincial (Canada, 6/2019).</li> <li>TWA: 3 mg/m<sup>3</sup> 8 hours. Form: Inhalable particulate matter.</li> <li>CA Quebec Provincial (Canada, 6/2022).</li> <li>TWAEV: 3 mg/m<sup>3</sup> 8 hours. Form: inhalable dust</li> <li>CA Alberta Provincial (Canada, 6/2018).</li> <li>8 hrs OEL: 3.5 mg/m<sup>3</sup> 8 hours.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 7 mg/m<sup>3</sup> 15 minutes.</li> <li>TWA: 3.5 mg/m<sup>3</sup> 8 hours.</li> </ul>

#### **Occupational exposure limits (Mexico)**

Ingredient name	CAS #	Exposure limits
None.		

#### **Biological exposure indices (United States)**

Ingredient name	Exposure indices
	ACGIH BEI (United States, 1/2023) BEI: 100 mg/l, 5-hydroxy-N-methyl- 2-pyrrolidone [in urine]. Sampling time: end of shift.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

Ingredient name	Exposure indices
1-Methyl-2-Pyrrolidone	Official Mexican STANDARD NOM- 047-SSA1-2011, Environmental Health- Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) BEI: 100 mg/L, 5-hydroxy-n-methyl- 2-pyrrolidone [in urine]. Sampling time: at the end of the work shift.

## Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	6/13
F93N505KL	MIL-DTL-64159C Type Tru-Mix® Touch Up Ca		educible Polyurethane 3rown 383 30051 Q2081		SHW-85-	NA-GHS-CA	

## Section 8. Exposure controls/personal protection

	•
Individual protection measure	es
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Lower: 2.2% Upper: 12.3%
Vapor pressure	: 2.3 kPa (17.5 mm Hg)
Relative vapor density	: 1 [Air = 1]
Relative density	: 1.17

### Section 9. Physical and chemical properties

Solubility(ies) :						
Media		Result				
cold water		Partially soluble				
Partition coefficient: n- : Not octanol/water		applicable.				
Auto-ignition temperature :		Not available.				
Decomposition temperature : No		lot available.				
Viscosity : Kin		nematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight : Not		ot applicable.				
Heat of combustion : 1.72		22 kJ/g				

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

#### Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
, ,	LD50 Dermal LD50 Oral	Rat	8 g/kg 3914 mg/kg	-
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-Methyl-2-Pyrrolidone Mercaptopropyl Trimethoxysilane	Eyes - Moderate irritant Skin - Mild irritant	Rabbit Rabbit	-	100 mg 500 mg	-

#### **Sensitization**

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### **Classification**

Date of issue/Date	of revision	: 9/18/2023	Date of previous issue	: 7/31/2023
F93N505KL	MIL-DTL-64159C Type	III 2K Water Re	ducible Polyurethane	
	Tru-Mix® Touch Up Ca	artridge 600mL E	Brown 383 30051 Q2081	

## Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
Chromium Oxide	-	3	-
Iron Oxide	-	3	-
Carbon Black	-	2B	-

#### **Reproductive toxicity**

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Name		Route of exposure	Target organs
1-Methyl-2-Pyrrolidone	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

## Information on the likely : Not available. routes of exposure

Potential acute health effe	<u>ets</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.

- Skin contact : May cause an allergic skin reaction.
- Ingestion : No known significant effects or critical hazards.

Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	<ul> <li>Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations</li> </ul>
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	<ul> <li>Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations</li> </ul>

Delayed and immediate	effects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.

Date of issue/Date	e of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	9/13
F93N505KL			Reducible Polyurethane Brown 383 30051 Q2081		SHW-85-	NA-GHS-CA	4

## Section 11. Toxicological information

	-	
Potential delayed effects	Not available.	
<u>Long term exposure</u>		
Potential immediate effects	Not available.	
Potential delayed effects	Not available.	
Potential chronic health ef	<u>cts</u>	
Not available.		
General	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.	
Carcinogenicity	Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.	
Mutagenicity	No known significant effects or critical hazards.	
Teratogenicity	May damage the unborn child.	
Developmental effects	No known significant effects or critical hazards.	
Fertility effects	No known significant effects or critical hazards.	

#### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	16977.65 mg/kg

## Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
5		1 - 7 3 -	48 hours 96 hours

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

Date of issue/Date	e of revision	: 9/18/2023	Date of previous issue	: 7/31/2023	Version	: 21	10/13
F93N505KL	······································			SHW-85-	NA-GHS-C/	4	

## Section 13. Disposal considerations

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	_	-	-		-
Special precautions	conside mode o suitably to shipr of the p dangero and on	odal shipping descri er container sizes. Th f transport (sea, air, f for that mode of trainent, and complianc erson offering the propus goods must be t all actions in case of able.	he presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the produce g must be reviewed regulations is the People loading and isks deriving from t	or a particular t is packaged t for suitability pric sole responsibility t unloading

Proper shipping name : Not available.

### Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

## Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Justification		
SKIN SENSITIZATION - C CARCINOGENICITY - Cat TOXIC TO REPRODUCTI	Calculation method Calculation method Calculation method		
<u>History</u>			
Date of printing	: 9/18/2023		
Date of issue/Date of revision	: 9/18/2023		
Date of previous issue	: 7/31/2023		
Version	: 21		
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff		
Date of issue/Date of revision	: 9/18/2023 Date of previous issue : 7/31/2023	Version : 21 12/13	
F93N505KL MIL-DTL-6415 Tru-Mix® Touc	SHW-85-NA-GHS-CA		

### Section 16. Other information

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

**V** Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 7/31/2023