SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	: POWDURA® TGIC Polyester Powder Coating - Regal Red
Product code	: PRS8-C0008
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Material uses	: Paint or paint related material.
	: Industrial use only.
1.3 Details of the supplier of sheet	the safety data
Mfg. in U.S.A and exported by The Sherwin-Williams Compa 101 Prospect Avenue N.W. Cleveland, OH 44115	
EU Only Representative: Vals Zuiveringweg 89 8243 PE Lelystad P.O. Box 2139 The Netherlands Phone: +31 (0)320 29 22 00	par B.V.
e-mail address of person responsible for this SDS	: sds@sherwin.com
1.4 Emergency telephone nu	mber
National advisory body/Pois	son Center
Telephone number	: +431 406 43 43
<u>Supplier</u>	
Telephone number	: +1 703-741-5970
Hours of operation	: Emergency contact available 24 hours a day
SECTION 2: Hazards ide	ntification
2.1 Classification of the subs	tance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

SECTION 2: Hazards identification

...

.

Hazard pictograms	
Signal word	: Danger
Hazard statements	: May cause an allergic skin reaction. Causes serious eye damage. Harmful if inhaled. May cause genetic defects.
Precautionary statements	
Prevention	: Obtain special instructions before use. Wear protective gloves, protective clothing, eye protection, face protection, or hearing protection. Avoid breathing dust or mist.
Response	: IF exposed or concerned: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	 Triglycidyl Isocyanurate Rosin 2'-ethoxy-3-hydroxy-2-naphthanilide
Supplemental label elements	 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust. FOR INDUSTRIAL USE ONLY
Special packaging requiren	nents

Special	packagi	ing rea	uiremen

Not applicable.

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Other hazards which do not result in classification

SECTION 3: Composition/information on ingredients

:

3.2 Mixture

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Triglycidyl Isocyanurate	EC: 219-514-3 CAS: 2451-62-9 Index: 615-021-00-6	≤5	Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340 STOT RE 2, H373 Aquatic Chronic 3, H412	ATE [Oral] = 138 mg/kg ATE [Inhalation (vapours)] = 0.65 mg/l	[1]
Titanium Dioxide	REACH #: 01-2119489379-17 EC: 236-675-5 CAS: 13463-67-7	≤3	Not classified.	-	[2]
Rosin	EC: 232-475-7 CAS: 8050-09-7	≤0.3	Skin Sens. 1, H317	-	[1]
Date of issue/Date of revision	: 18, Apr, 2024	Date of previo	us issue : 15, Oct, 2023	Version : 3	2/14
				SHW-A4-EU-CLP44-A	۹T

: May form combustible dust concentrations in air.

POWDURA® TGIC Polyester Powder Coating - Regal Red

PRS8-C0008

SECTION 3: Composition/information on ingredients

•		0			
2'-ethoxy-3-hydroxy- 2-naphthanilide	Index: 650-015-00-7 REACH #: 01-2119473802-36 EC: 202-185-5 CAS: 92-74-0	<0.1	Skin Sens. 1A, H317 Aquatic Chronic 1, H410	M [Chronic] = 1	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Contains 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione, rosin. May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

Date of issue/Date of revision	: 18, Apr, 2024	Date of previous issue	: 15, Oct, 2023	Version : 3	3/14

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Recommended: alcohol-resistant foam, CO_2 blanket, water spray or mist.
Unsuitable extinguishing media	:	Do not use water jet. Do not use inert gas under high pressure (e.g. CO2).
5.2 Special hazards arising fr	on	n the substance or mixture
Hazards from the substance or mixture	:	Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
SECTION 6: Accidental r	el	ease measures
6.1 Personal precautions, pro	ote	ctive equipment and emergency procedures
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.
		Keep unnecessary and unprotected personnel from entering.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3 Methods and materials for containment and	:	Contain and collect spillage with an electrically protected vacuum cleaner or by wet- brushing and place in container for disposal according to local regulations (see

6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.
SECTION 7. Handling	and storage

section 13). Do not use a dry brush as dust clouds or static can be created.

SECTION 7: Handling and storage

cleaning up

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

7.1 Precautions for safe : handling	 Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame.
--	---

Date of issue/Date of revision	: 18, Apr, 2024	Date of previous issue	: 15, Oct, 2023	Version : 3	4/14
				SHW-A4-EU-CLP44-AT	

SECTION 7: Handling and storage

	 Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
7.2 Conditions for safe storage, including any incompatibilities	 Store in accordance with local regulations. Additional information on storage conditions Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorized access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
	Contaminated absorbent material may pose the same hazard as the spilled product.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Titanium Dioxide	Regulation on Limit Values - MAC (Austria, 4/2021). TWA: 5 mg/m ³ 8 hours. Form: respirable dust PEAK: 10 mg/m ³ , 2 times per shift, 60 minutes. Form: respirable dust

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
	 Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

POWDURA® TGIC Polyester Powder Coating - Regal Red PRS8-C0008

SECTION 8: Exposure controls/personal protection

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Rosin	DNEL	Long term Dermal	1.065 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Oral	1.065 mg/ kg bw/day	General population	Systemic
		Short term Inhalation	10 mg/m ³	Workers	Local
	DNEL		2.131 mg/ kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Rosin	Fresh water	0.0016 mg/l	-
	Marine water	0.00016 mg/l	-
	Fresh water sediment	0.007 mg/kg	-
	Marine water sediment	0.001 mg/kg	-
	Soil	0.00031 mg/kg dwt	-
	Sewage Treatment Plant	1000 mg/l	-

8.2 Exposure controls Appropriate engineering : Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not controls sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn. : Users are advised to consider national Occupational Exposure Limits or other equivalent values. Individual protection measures : Wash hands, forearms and face thoroughly after handling chemical products, before Hygiene measures eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. Eye/face protection : Safety eyewear should be used when there is a likelihood of exposure. Skin protection Hand protection : Wear suitable gloves tested to EN374. Gloves : Gloves for short term exposure or repeated or prolonged exposure (480 min): Wear any rubber glove such as Nitrile or Neoprene gloves. Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing. There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be

Date of issue/Date of revision	: 18, Apr, 2024	Date of previous issue	:15, Oct, 2023	Version : 3	6/14

POWDURA® TGIC Polyester Powder Coating - Regal Red

PRS8-C0008

SECTION 8: Exposure controls/personal protection

	applied once exposure has occurred.	
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.	
Body protection	Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.	
	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.	
Respiratory protection	Application methods: Brush or roller. Approved/certified respirator with organic vapor cartridge. Filter type: A2 P2 (EN14387). Manual spraying. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.	
Environmental exposure controls	Do not allow to enter drains or watercourses.	

Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: :	Solid.
Color	:	Red.
Odor	:	None
Odor threshold	:	Not applicable.
рН		Not relevant/applicable due to nature of the product. insoluble in water.
Melting point/freezing point	:	Not relevant/applicable due to nature of the product.
Initial boiling point and boiling range	:	Not relevant/applicable due to nature of the product.
Flash point	: (Closed cup: Not applicable.
Evaporation rate	:	Not relevant/applicable due to nature of the product.
Flammability	:	Not relevant/applicable due to nature of the product.
Lower and upper explosion limit	:	Not relevant/applicable due to nature of the product.
Vapor pressure	:	Not relevant/applicable due to nature of the product.
Relative vapor density	:	Not applicable.
Relative density	:	1.56
Solubility(ies)	:	
Media		Result
cold water		Not soluble

SECTION 9: Physical and chemical properties

-		
Partition coefficient: n-octan water	I/ ∶ Not relevant/applicable due to nature of the product.	
Auto-ignition temperature	: Not relevant/applicable due to nature of the product.	
Decomposition temperature	: Not relevant/applicable due to nature of the product.	
Viscosity	: Kinematic (40°C): >20.5 mm ² /s	
Explosive properties	: Under normal conditions of storage and use, hazardous reactions will not oc	cur.
Oxidizing properties	: Under normal conditions of storage and use, hazardous reactions will not oc	cur.
Particle characteristics		
Median particle size	: Not relevant/applicable due to nature of the product.	
9.2 Other information		
Heat of combustion	: 0.136 kJ/g	
SECTION 10: Stability an	reactivity	
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingredien	nts.
10.2 Chemical stability	Stable under recommended storage and handling conditions (see Section 7).	
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decomposition products.	
10.5 Incompatible materials	Not applicable.	
10.6 Hazardous decomposition products	Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localized skin irritation in folds of the skin or under tight clothing.

Contains 1,3,5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione, rosin. May produce an allergic reaction. **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Triglycidyl Isocyanurate	LC50 Inhalation Vapor	Rat	650 mg/m³	4 hours
	LD50 Oral	Rat	138 mg/kg	-
Rosin	LD50 Oral	Rat	7600 mg/kg	-

Acute toxicity estimates

: Not available.

POWDURA® TGIC Polyester Powder Coating - Regal Red

PRS8-C0008

SECTION 11: Toxicological information

Route	ATE value
Oral	3023.83 mg/kg
Inhalation (vapors)	14.24 mg/l

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Triglycidyl Isocyanurate	Eyes - Severe irritant	Rabbit	-	100 mg	-

Conclusion/Summary

Sensitization

No data available

Conclusion/Summary : Not available.

Mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Teratogenicity

No data available

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Triglycidyl Isocyanurate	Category 2	-	-

Aspiration hazard

No data available

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

12.2 Persistence and degradability

POWDURA® TGIC Polyester Powder Coating - Regal Red PRS8-C0008

SECTION 12: Ecological information

Product/ingredient name	Test	Result		Dose		Inoculum
No data available						
Conclusion/Summary	: Not available.			•		•
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
No data available						

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
No data available			

12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

considerations
ds
: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
: Yes.
 waste paint and varnish containing organic solvents or other hazardous substances 08 01 11*
 Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

POWDURA® TGIC Polyester Powder Coating - Regal Red PRS8-C0008

SECTION 13: Disposal considerations

Disposal considerations	:	Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
European waste catalogue (EWC)	:	packaging containing residues of or contaminated by hazardous substances 15 01 10*
Special precautions	:	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport Hazard Class(es)/ Label(s)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in	: Not applicable.
bulk according to IMO	
instruments	

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

Ingredient name	Intrinsic property		Reference number	Date of revision
Triglycidyl Isocyanurate	Mutagen	Candidate	ED/87/2012	6/18/2012

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]	
	WDURA® TGIC Polyester Powder Coating 5-tris(oxiranylmethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione		29 29	
Labeling <u>Other EU regulations</u> <i>VOC content (2010/75/EU)</i>	 Restricted to professional users. 0 w/w 0 g/l 			
Explosive precursors <u>Seveso Directive</u>	: Not applicable.			
This product is not controllec National regulations	under the Seveso Directive.			
5.2 Chemical Safety ssessment	: No Chemical Safety Assessment has bee	n carried out.		

SECTION 16: Other information

Indicates information that has changed from previously issued version.
--

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number vPvB = Very Persistent and Very Bioaccumulative N/A = Not available
Key literature references and sources for data	 Regulation (EC) No. 1272/2008 [CLP] ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 Directive 2012/18/EU, and relative amendments & additions Directive 2008/98/EC, and relative amendments & additions Directive 2009/161/EU, and relative amendments & additions CEPE Guidelines

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

12/14

POWDURA® TGIC Polyester Powder Coating - Regal Red PRS8-C0008 SECTION 16: Other information			
Acute Tox. 4, H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 1B, H340		Calculation method Calculation method Calculation method Calculation method	
Full text of abbreviated H statements	H317 May ca H318 Causes H330 Fatal if H332 Harmfu H340 May ca H373 May ca exposu H410 Very to	 H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H332 Harmful if inhaled. H340 May cause genetic defects. H373 May cause damage to organs through prolonged or repeated exposure. H410 Very toxic to aquatic life with long lasting effects. 	
Full text of classifications [CLP/GHS]	: Acute Tox. 2 Acute Tox. 3 Acute Tox. 4 Aquatic Chronic 1 Aquatic Chronic 3 Eye Dam. 1 Muta. 1B Skin Sens. 1 Skin Sens. 1A STOT RE 2	ACUTE TOXICITY - Category 2 ACUTE TOXICITY - Category 3 ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category GERM CELL MUTAGENICITY - Category 1B SKIN SENSITIZATION - Category 1 SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	
Date of printing	: 18, Apr, 2024.	, - 0 ,	
Date of issue/ Date of revision	: 18, Apr, 2024		
Date of previous issue	: 15, Oct, 2023		
	: If there is no previous val information.	idation date please contact your supplier for more	
Version	: 3		

Notice to reader

In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.

SUMI(s) will be added to the SDS for products if both the following conditions are met:

• The product is classified as hazardous for health

• The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country,

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II POWDURA® TGIC Polyester Powder Coating - Regal Red PRS8-C0008

SECTION 16: Other information

federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.