SAFETY DATA SHEET

B65B720

Section 1. Identification

Product name	: Pro Industrial™ Waterbased Acrolon™ 100 HS Waterbased Urethane (Part A) Black
Product code	: B65B720
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
: SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2
: Warning
: May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024
B65B720	Pro Industrial™ Waterbased Black	Acrolon™ 100 HS V	/aterbased Urethane (Part A)	

Version : 16.01 1/13 SHW-85-NA-GHS-US

Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Carbon Black	≤3	1333-86-4
Bis(pentamethyl-4-piperidyl)sebacate	≤1	41556-26-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms	effects, acute and delayed
Potential acute health effe	ects
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>ptoms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate me	edical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:16.01	3/13
B65B720	Pro Industrial™ Waterbased Black	Acrolon™ 100 HS V	Vaterbased Urethane (Part A)		SHW-85-I	NA-GHS-US	

Section 5. Fire-fighting measures

Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	equipment and emergency procedures	
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.	
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	n
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
Methods and materials for co	<u>inment and cleaning up</u>	
Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material an place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.	
Large spill	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Was spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated	h

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous.
	Do not reuse container.

absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

: 2/4/2024

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue
B65B720	Pro Industrial™ Waterbased / Black	Acrolon™ 100 HS W	aterbased Urethane (Part A)

Section 7. Handling and storage

Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Carbon Black	1333-86-4	NIOSH REL (United States, 10/2020). TWA: 3.5 mg/m ³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2023). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction
Bis(pentamethyl-4-piperidyl)sebacate	41556-26-7	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits	
Carbon black	1333-86-4	 Exposure limits CA British Columbia Provincial (Canada, 6/2022). TWA: 3 mg/m³ 8 hours. Form: Inhalable CA Ontario Provincial (Canada, 6/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable particulate matter. CA Quebec Provincial (Canada, 6/2022). TWAEV: 3 mg/m³ 8 hours. Form: inhalable dust CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes. TWA: 3.5 mg/m³ 8 hours. 	
2-Butoxyethanol	111-76-2	 CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 97 mg/m³ 8 hours. 8 hrs OEL: 20 ppm 8 hours. CA British Columbia Provincial (Canada, 6/2022). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 20 ppm 8 hours. CA Quebec Provincial (Canada, 6/2022). TWAEV: 20 ppm 8 hours. 	
Date of issue/Date of revision : 4/19/2024 Da	te of previous issue	: 2/4/2024 Version : 16.01 5/13	
65B720 Pro Industrial™ Waterbased Acrolon™ 100 HS Water Black	rbased Urethane (Part A)	SHW-85-NA-GHS-US	

Section 8. Exposure controls/personal protection

•	•	•	
			CA Saskatchewan Provincial (Canada, 7/2013). STEL: 30 ppm 15 minutes. TWA: 20 ppm 8 hours.
Occupational exposure lin	nits (Mexico)		
		CAS #	Exposure limits
		0,40 #	
None.			
Biological exposure indice No exposure indices known			
Biological exposure indice	<u>es (Canada)</u>		
No exposure indices known	1.		
Biological exposure indice No exposure indices known			
Appropriate engineering controls	local exhaust vent	ilation or other e	umes, gas, vapor or mist, use process enclosures, ngineering controls to keep worker exposure to ecommended or statutory limits.
Environmental exposure controls	: Emissions from ve they comply with th cases, fume scrub	entilation or work he requirements bbers, filters or e	process equipment should be checked to ensure of environmental protection legislation. In some ngineering modifications to the process equipment ons to acceptable levels.
Individual protection meas	ures		
Hygiene measures	eating, smoking ar Appropriate techni Contaminated wor	nd using the lava ques should be k clothing should ning before reus	noroughly after handling chemical products, before atory and at the end of the working period. used to remove potentially contaminated clothing. d not be allowed out of the workplace. Wash ing. Ensure that eyewash stations and safety on location.
Eye/face protection	assessment indica gases or dusts. If	ates this is neces contact is possi	approved standard should be used when a risk sary to avoid exposure to liquid splashes, mists, ole, the following protection should be worn, unless degree of protection: safety glasses with side-
Skin protection			
Hand protection	worn at all times w necessary. Consid during use that the noted that the time glove manufacture	when handling ch dering the paran e gloves are still to breakthroug ers. In the case	ves complying with an approved standard should be emical products if a risk assessment indicates this is neters specified by the glove manufacturer, check retaining their protective properties. It should be n for any glove material may be different for different of mixtures, consisting of several substances, the of be accurately estimated.
Body protection		e risks involved a	the body should be selected based on the task being nd should be approved by a specialist before
Other skin protection		being performed	tional skin protection measures should be selected d and the risks involved and should be approved by a luct.

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>				
Physical state	: Li	quid.		
Color	: B	lack.		
Odor	: N	ot available.		
Odor threshold	: N	ot available.		
рН	: 7			
Melting point/freezing point	: N	ot available.		
Boiling point, initial boiling point, and boiling range	: 1	00°C (212°F)		
Flash point	: C	losed cup: 110°C (230°F) [Pensky-Martens Closed Cup]		
Evaporation rate	: 0	09 (butyl acetate = 1)		
Flammability	: N	ot available.		
Lower and upper explosion limit/flammability limit	: Not available.			
Vapor pressure	: 2	3 kPa (17.5 mm Hg)		
Relative vapor density	: 1	[Air = 1]		
Relative density	: 1	05		
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: Not applicable.			
Auto-ignition temperature	: Not available.			
Decomposition temperature	e : Not available.			
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	: Not applicable.			
Heat of combustion	: 0.602 kJ/g			

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredien	ts.	
Chemical stal	oility	: The product is stable.	
Possibility of reactions	hazardous	: Under normal conditions of storage and use, hazardous reactions will not occur.	
Conditions to	avoid	: No specific data.	
Incompatible	materials	: No specific data.	
Date of issue/Dat	te of revision	: 4/19/2024 Date of previous issue : 2/4/2024 Version : 16.01	7/13
B65B720	Pro Industrial™ Wat Black	ased Acrolon™ 100 HS Waterbased Urethane (Part A) SHW-85-NA-GHS-U	s

Section 10. Stability and reactivity

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Carbon Black	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristicsEye contact: No specific data.

Date of issue	e/Date of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 16.01	8/13
B65B720	Pro Industrial™ Waterb Black	oased Acrolon™ 100 HS	Waterbased Urethane (Part A)		SHW-85-NA-GHS-US	

Section 11. Toxicological information

Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate ef	fects and also chronic effects from short and long term exposure					
<u>Short term exposure</u>						
Potential immediate effects	: Not available.					
Potential delayed effects	: Not available.					
Long term exposure						
Potential immediate effects	: Not available.					
Potential delayed effects	: Not available.					
Potential chronic health effects						
Not available.						
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.					
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.					
Mutagenicity	: No known significant effects or critical hazards.					
Teratogenicity	: No known significant effects or critical hazards.					
Developmental effects	: No known significant effects or critical hazards.					
Fertility effects	: Suspected of damaging fertility.					

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:16.01
B65B720	Pro Industrial™ Waterbased Black	Acrolon™ 100 HS V	Vaterbased Urethane (Part A)		SHW-85-	NA-GHS-US

9/13

Section 12. Ecological information

Not available.

<u>Mobility in soil</u>

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

: 2/4/2024

Section 14. Transport information

Special precautions for user	:	Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.
Transport in bulk according to IMO instruments	:	Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-Methyl-4-isothiazolin-3-one

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

 International lists
 : Australia inventory (AIIC): Not determined.
China inventory (IECSC): Not determined.
Japan inventory (CSCL): Not determined.
Japan inventory (ISHL): Not determined.
Korea inventory (ISHL): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.
Taiwan Chemical Substances Inventory (TCSI): Not determined.
Thailand inventory: Not determined.
Turkey inventory: Not determined.
Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Date of issue/Date	e of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:16.01	11/13
B65B720	Pro Industrial™ Waterbased Black	Acrolon™ 100 HS	Waterbased Urethane (Part A)		SHW-85-	NA-GHS-US	

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification Jus	Justification		
SKIN SENSITIZATION - C CARCINOGENICITY - Ca TOXIC TO REPRODUCTI	egory 2 Calculation m	ethod		
<u>History</u>				
Date of printing	: 4/19/2024			
Date of issue/Date of revision	: 4/19/2024			
Date of previous issue	: 2/4/2024			
Version	: 16.01			
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution Fro as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations	ion Factor nonized System of Classification and Labelling of Chemicals Air Transport Association ulk Container Maritime Dangerous Goods of the octanol/water partition coefficient onal Convention for the Prevention of Pollution From Ships, 1973 rotocol of 1978. ("Marpol" = marine pollution)		

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

: 2/4/2024