SAFETY DATA SHEET

GP3589A62

Section 1. Identification

Product name	: Resuflor™ 3589 Smooth Epoxy Floor Coating (Part A) Parchment
Product code	: GP3589A62
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of the	ne substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company Product Information	 US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year US / Canada: 1-800-524-5979 Maximum Nat Available
Telephone Number	Mexico: Not Available
Transportation Emergency Telephone Number	: US / Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 8.4% (oral), 13.6% (dermal), 15.1% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

Precautionary statements

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. Please refer to the SDS for additional information. Keep out of reach of children. Do not
	transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Epoxy Polymer	≥50 - ≤75	1675-54-3
Epoxy Polymer	≤10	25085-99-8
Phenol, 4-Nonyl-, Branched	≤10	84852-15-3
Titanium Dioxide	≤10	13463-67-7
Trimethylolpropane triacrylate	≤3	15625-89-5
Alkyl Glycidyl Ether	≤3	68609-97-2
Phenol, 2-nonyl-, branched	<1	91672-41-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	2/13
GP3589A62	Resuflor™ 3589 Smoo Parchment	th Epoxy Flooi	Coating (Part A)		SHW-85-	NA-GHS-US	

Section 4. First aid measures

Inhalation	: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects	
Eye contact	Causes serious eye damage.
Inhalation	No known significant effects or critical hazards.
Skin contact	Causes severe burns. May cause an allergic skin reaction.
Ingestion	No known significant effects or critical hazards.
Over-exposure signs/sympto	<u>ms</u>
Eye contact	Adverse symptoms may include the following: pain watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	3/13
GP3589A62	Resuflor™ 3589 Smoo Parchment	th Epoxy Floor (Coating (Part A)		SHW-85-	NA-GHS-US	

Section 4. First aid measures

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	iv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	4/13
GP3589A62	Resuflor™ 3589 Smoo Parchment	th Epoxy Floor (Coating (Part A)		SHW-85-	NA-GHS-US	

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling **Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Advice on general Eating, drinking and smoking should be prohibited in areas where this material is 5 handled, stored and processed. Workers should wash hands and face before eating, occupational hygiene drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. **Conditions for safe storage, :** Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials including any (see Section 10) and food and drink. Store locked up. Keep container tightly closed incompatibilities and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Epoxy Polymer	1675-54-3	None.
Epoxy Polymer	25085-99-8	None.
Phenol, 4-Nonyl-, Branched	84852-15-3	None.
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust
		ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles
Trimethylolpropane triacrylate	15625-89-5	OARS WEEL (United States, 4/2022). Absorbed through skin. TWA: 1 mg/m ³ 8 hours.
Alkyl Glycidyl Ether	68609-97-2	None.
Phenol, 2-nonyl-, branched	91672-41-2	None.

Occupational exposure limits (Canada)

Date of issue/Date of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	5/13
GP3589A62 Resuflor™ Parchment	3589 Smooth Epoxy Floc	or Coating (Part A)		SHW-85-I	NA-GHS-US	

Section 8. Exposure controls/personal protection

Ingredient name	CAS #	Exposure limits
Trimethylolpropane triacrylate	15625-89-5	OARS WEEL (United States, 4/2022). Absorbed through skin. TWA: 1 mg/m ³ 8 hours.

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	 If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measu	<u>res</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	6/13
GP3589A62	Resuflor™ 3589 Smoo Parchment	th Epoxy Floor	Coating (Part A)		SHW-85	NA-GHS-US	

Section 8. Exposure controls/personal protection

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>		
Physical state	: Liquid.	
Color	: Not available.	
Odor	: Not available.	
Odor threshold	Not available.	
рН	Not applicable.	
Melting point/freezing point	: Not available.	
Boiling point, initial boiling point, and boiling range	: Not available.	
Flash point	: Closed cup: 116°C (240.8°F) [Pensky-Martens Closed Cup]	
Evaporation rate	: Not available.	
Flammability	: Not available.	
Lower and upper explosion limit/flammability limit	: Not available.	
Vapor pressure	: Not available.	
Relative vapor density	Not available.	
Relative density	: 1.18	
Solubility(ies)	:	
Media	Result	
cold water	Not soluble	
Partition coefficient: n- octanol/water	: Not applicable.	ł
Auto-ignition temperature	: Not available.	
Decomposition temperature	: Not available.	
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)	
Molecular weight	Not applicable.	
Heat of combustion	: 1.571 kJ/g	
	• • • •	1

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.

Date of issue/Date	e of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	7/13
GP3589A62	Resuflor™ 3589 Parchment	Smooth Epoxy Floo	r Coating (Part A)		SHW-85-	NA-GHS-US	

Section 10. Stability and reactivity

Incompatible materials

: No specific data.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Epoxy Polymer	LD50 Dermal	Rabbit	20 g/kg	-
Phenol, 4-Nonyl-, Branched	LD50 Oral	Rat	1300 mg/kg	-
Trimethylolpropane triacrylate	LD50 Dermal	Rabbit	5170 mg/kg	-
Alkyl Glycidyl Ether	LD50 Oral	Rat	17100 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Epoxy Polymer	Eyes - Severe irritant	Rabbit	-	24 hours 2	-
				mg	
	Skin - Mild irritant	Rabbit	-	500 mg	-
Phenol, 4-Nonyl-, Branched	Eyes - Severe irritant	Rabbit	-	100 mg	-
-	Skin - Severe irritant	Rabbit	-	24 hours 500	-
				mg	
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	
Trimethylolpropane triacrylate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				mg	
Alkyl Glycidyl Ether	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				uL	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Epoxy Polymer	-	3	-
Titanium Dioxide		2B	-
Trimethylolpropane triacrylate		2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	8/13
GP3589A62	Resuflor™ 3589 Smoo Parchment	th Epoxy Floor	Coating (Part A)		SHW-85	NA-GHS-US	

Section 11. Toxicological information

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure	: Not available.	
Potential acute health effe	<u>s</u>	
Eye contact	: Causes serious eye damage.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: Causes severe burns. May cause an allergic skin reaction.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the p	ysical, chemical and toxicological characteristics	
Eye contact	: Adverse symptoms may include the following: pain watering redness	
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	

	skeletal malformations
Skin contact	: Adverse symptoms may include the following: pain or irritation redness blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate ef	fects and also chronic effects from short and long term exp	osure
<u>Short term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Long term exposure		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Potential chronic health e	fects	
Not available.		
General	: Once sensitized, a severe allergic reaction may occur when very low levels.	a subsequently exposed to
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on c exposure.	duration and level of
Mutagenicity	: No known significant effects or critical hazards.	
Date of issue/Date of revision	: 2/6/2024 Date of previous issue : 1/29/2024	Version : 27.02
GP3589A62 Resuflor™ 3589 Parchment	9 Smooth Epoxy Floor Coating (Part A)	SHW-85-NA-GHS-US

9/13

Section 11. Toxicological information

Teratogenicity

: Suspected of damaging the unborn child.

- Developmental effects Fertility effects
- : No known significant effects or critical hazards.
- : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	19305.78 mg/kg

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Phenol, 4-Nonyl-, Branched	Acute EC50 0.03 mg/l Marine water Acute EC50 0.027 mg/l Marine water Acute EC50 0.044 mg/l Acute LC50 17 µg/l Marine water	Algae - Skeletonema costatum Algae - Skeletonema costatum Crustaceans - Moina macrocopa Fish - Pleuronectes americanus - Larvae	72 hours 96 hours 48 hours 96 hours
	Chronic EC10 0.012 mg/l Marine water Chronic NOEC 5 μg/l Fresh water	Algae - Skeletonema costatum Crustaceans - Gammarus fossarum - Adult	96 hours 21 days
	Chronic NOEC 7.4 µg/l Fresh water	Fish - <i>Pimephales promelas</i> - Embryo	33 days
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Phenol, 4-Nonyl-, Branched	-	740	High
Alkyl Glycidyl Ether		160 to 263	Low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a

Date of issue/Date	of revision	: 2/6/2024	Date of previous issue	: 1/29/2024	Version	: 27.02	10/13
	Resuflor™ 3589 Smootł Parchment	n Epoxy Floor C	Coating (Part A)		SHW-85-	NA-GHS-US	

Section 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Parchment

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	UN3066	UN3066	UN3066	UN3066	UN3066
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT. Marine pollutant (Phenol, 4-Nonyl-, Branched, Trimethylolpropane triacrylate)
Transport	8	8	8	8	8
hazard class(es)	CORIGUE 8		*	1 Alexandre	
Packing group	III	III	Ш		111
Environmental hazards	No.	No.	No.	Yes. The environmentally hazardous substance mark is not required.	Yes.
Additional information	-	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8).	-	The environmentally hazardous substance mark may appear if required by other transportation regulations.	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency</u> <u>schedules</u> F-A, S B
	ERG No.	ERG No.	ERG No.		
	153	153	153		
Special precautions	consid mode suitabl to ship of the p danger	nodal shipping descripter container sizes. The of transport (sea, air, y for that mode of transment, and compliance berson offering the prous goods must be the all actions in case of the other section.	e presence of a shi etc.), does not indic nsport. All packagin e with the applicable oduct for transport. rained on all of the r	pping description for ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	a particular is packaged for suitability prior ole responsibility unloading
Date of issue/Date of rev GP3589A62 Resu					on : 27.02 11/

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: Phenol, 4-Nonyl-, Branched; Phenol, 2-nonyl-, branched

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AlIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Section 16. Other information

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1B	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method

motory	
Date of printing	: 2/6/2024
Date of issue/Date of revision	: 2/6/2024
Date of previous issue	: 1/29/2024
Version	: 27.02
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer. or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.